



Dual Compensated Porosity Log

DIGITAL LOG (785) 625-3858

API No.

15-039-21102-00-00

Company Murfin Drilling Company, Inc.

Well Stealy No. 1-21 X

Field Unknown

County Decatur State Kansas

Location

W/2 - NE - NE - SW
2310' FSL & 2300' FWL

Other Services
DIL
MEL/BHCS

Sec: 21

Twp: 3 S

Rge: 27 W

Elevation

Permanent Datum Ground Level Elevation 2619
Log Measured From Kelly Bushing 5 Ft. Above Perm. Datum
Drilling Measured From Kelly Bushing

K.B. 2624
D.F.
G.L. 2619

Date

8/21/2009

Run Number

One

Type Log

CNL / CDL

Depth Driller

3850

Depth Logger

3842

Bottom Logged Interval

3821

Top Logged Interval

3200

Type Fluid In Hole

Chemical

Salinity, PPM CL

2200

Density

8.8

Level

Full

Max. Rec. Temp. F

115

Operating Rig Time

5 Hours

Equipment -- Location

15 Hays

Recorded By

Becker

Witnessed By

Jeff Christian

Borehole Record

Casing Record

Run No

Bit

From

To

Size

Wgt.

24#

From

To

1

12.25

00

2210

8.625

24#

00

2210

2

7.875

2210

3850

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Thank you for using Log-Tech, Inc.
(785) 625-3858

Norcatour, Ks
10 West to Kanona Rd; 2 south (across tracks);
1 East; 1 South; 1/2 East; South after tanks

Database File: c:\warrior\data\murfin_stealy no. 1-21 x\murfinhd.db
Dataset Pathname: DIL/murfstk
Presentation Format: cdl
Dataset Creation: Fri Aug 21 09:55:28 2009
Charted by: Depth in Feet scaled 1:600

0	Gamma Ray	150
6	Caliper (in)	16

30	Compensated Density (pu)	-10
2	Bulk Density (g/cc)	3
15000	Line Tension (lb)	0
-0.25	Correction (g/cc)	0.25
	LSPD (ft/min)	









