



Dual Compensated Porosity Log

DIGITAL LOG (785) 625-3858

API No.

15-135-25,020-00-00

Company American Warrior, Inc.

Well Schniepp No. 1-31 NE

Field Wildcat

County Ness State Kansas

Location 2,150' FNL & 900' FEL

Other Services
DIL

Sec: 31 Twp: 18S Rge: 21W

Permanent Datum Ground Level Elevation 2123

Log Measured From Kelly Bushing 8 Ft. Above Perm. Datum

Drilling Measured From Kelly Bushing K.B. 2131
D.F. 2123
G.L. 2123

Date 2/5/2010

Run Number One

Type Log CNL / CDL

Depth Driller 4243

Depth Logger 4243

Bottom Logged Interval 4222

Top Logged Interval 3500

Type Fluid In Hole Chemical

Salinity, PPM CL 5100

Density 9.1

Level Full

Max. Rec. Temp. F 120

Operating Rig Time 2 Hours

Equipment -- Location 17 Hays

Recorded By J. Long

Witnessed By Jason Alm

Borehole Record

Run No Bit From To Size Wgt. From To

1 12.25 00 1383 8.625 24# 00 1383

2 7.875 1383 4243

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Thank you for using Log-Tech, Inc.
(785) 625-3858

Bazine (East Side), Waumbaugh Rd, South to stop sign, East across bridge, 1/4 South
1/2 East, North Into

Database File: c:\warrior\data\amwar_schniepp no. 1-31\amwarhd.db
Dataset Pathname: dil\awstack
Presentation Format: cdl
Dataset Creation: Fri Feb 05 20:52:20 2010
Charted by: Depth in Feet scaled 1:600

0	Gamma Ray	150
6	Caliper (in)	16

30	Compensated Density (pu)				-10
2	Bulk Density (g/cc)				3
15000	Line Tension (lb)				0
2.625	DGA (g/cc)	3.425	-0.25	Correction (g/cc)	0.25

LSPD
(ft/min)











