Company: Charles H. Gillis
Well #: 1
Field: Trumbles
County: Pike
State: Kansas
API #:
Other Services:
Permanent Datum: GL
Elevation: 1,000 ft
Log Measured From: KB
Drilling Measured From: KB
Date: 10-Jan-11
Run Number: 1
Depth Driller: 10,000 ft
Depth Logger: 10,000 ft
Bottom Logged Interval: 10,000 ft
Top Logged Interval: 9,000 ft
Type Fluid in Hole: Water
Salinity: 4000 ppm
Density: 8.4 lb/gal
Viscosity: 28 s/qt
Fluid Loss: 10 cc
Source of Sample: Flowline
Rm @ Measured Temp: 0.1 @ 70 °F
Rmf @ Measured Temp: 0.1 @ 70 °F
Rmc @ Measured Temp: 0.1 @ 70 °F
Source of Rmf and Rmc: Calculated
Rm @ BHT: 0.1 @ 70 °F
Time Since Circulation: 1 hr
Max Rec. Temp.: 70 °F
Equipment Number: 1
Location: Charles H. Gillis
Recorded By: Jeff Smith
Witnessed By: Mr. Gillis

The Perforators LLC

MICRO RESISTIVITY LOG

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

South of Medicine Lodge on 281 2 mi.
IR on Pleasant Valley Rd. Stay on main rd.
when rd. curves S go across 2 cattle guards and stay on lease rd to end.(approx. 2 miles).

Thanks for using The Perforators LLC Hays, KS. (785-621-4804)

The Perforators LLC

Main Pass

Database File: openHF.db
Dataset: pass1
Presentation Format: mwd
Dataset Creation: Wed Jan 01 23:48:03 2011 by Log Open Comet V0807
Charted by: Depth in Feet scaled 1:240

X	GR (GAPI)	150	0	MN 0" (Ohm-m) #2
X	MCAL (in)	16	0	MX 1" (Ohm-m) #2
X	BORE2 (in)	16	10000	LTEN (lb) 0

9400
9450
9500
9550
9600
9650
9700
9750
9800
9850
9900
9950
10000

X	GR (GAPI)	150	0	MN 0" (Ohm-m) #2
X	MCAL (in)	16	0	MX 1" (Ohm-m) #2
X	BORE2 (in)	16	10000	LTEN (lb) 0

The Perforators LLC

Repeat Pass

Database File: openHF.db
Dataset: pass2
Presentation Format: mwd
Dataset Creation: Wed Jan 01 23:48:09 2011 by Cats Open Comet V0807
Charted by: Depth in Feet scaled 1:240

X	GR (GAPI)	150	0	MN 0" (Ohm-m) #2
X	MCAL (in)	16	0	MX 1" (Ohm-m) #2
X	BORE2 (in)	16	10000	LTEN (lb) 0

4700
4750
4800
4850
4900
4950
5000

X	GR (GAPI)	150	0	MN 0" (Ohm-m) #2
X	MCAL (in)	16	0	MX 1" (Ohm-m) #2
X	BORE2 (in)	16	10000	LTEN (lb) 0

Calibration Report

Database File: openHF.db
Dataset Pathname: pass1
Dataset Creation: Wed Jan 01 23:56:12 2011 by Log Open Comet V0807

Mnemonic Calibration Report

Serial Model Performed

Cal Pmgm
Tue May 17 05:11:27 2011

	Readings			References			Results	
	Zero	Cal		Zero	Cal		m	b
Normal	0.0037	0.4528	V	0.0000	10.0000	Ohm-m	23.2556	-0.0837
Short	0.0037	0.4528	V	0.0000	10.0000	Ohm-m	23.2556	-0.0837
Caliper	0.3398	0.8979	V	6.0000	10.0000	in	1.7907	2.7211

Gamma Ray Calibration Report

Serial Number	2002
Tool Model	PGSD
Calibration	Tue Jan 11 11:54:27 2011
Calibration Value	10.00 GAPI
Background Reading	0.0 cps
Calibrator Reading	1.0 cps
Sensitivity	0.2200 GAPI/cps

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
GR	8.00		GR-PGSD (2005)	3.67	3.25	46.00
			ML-Perge (512)	8.67	3.50	100.00
SR	1.50					
LR	3.00					
MCAL	1.00					

Dataset
Total Length: 12.34 ft
Total Weight: 146.00 lb

openHF.db: field:mwd:run1:pass3
Wed Jan 01 23:48:09 2011
1.000 ft