



MIDWEST SURVEYS
LOGGING - PERFORATING - CONSULTING SERVICES
P.O. Box 68, Osawatomie, KS 66064
913 / 755 - 2128

GAMMA RAY / NEUTRON / CCL

File No.

Company Oil Sources Corporation

Well Two Bros No.- 2

Field Paola - Rantoul

County Franklin State Kansas

Location 280' FNL & 1300' FEL

NW-NW-NE-NE

Other Services
Perforate

Sec 5 Twp 16s Rge 21e

Permanent Datum GL

Log Measured From GL

Drilling Measured From GL

Elevation K.B. NA
D.F. NA
G.L. NA

Date

Run Number One

Depth Driller 763.0

Depth Logger 748.2

Bottom Logged Interval 747.2

Top Log Interval 20.0

Fluid Level Full

Type Fluid Water

Density / viscosity NA

Salinity - PPM Cl NA

Max Recorded Temp NA

Estimated Cement Top 0.0

Equipment No. 107

Recorded By Steve Mandich

Witnessed By Kevin Kiewano

RUN

No. BIT

One 9.875"

Two 5.625"

FROM TO

0.0 20.0

763.0 783.0

SIZE WGT. FROM TO

7.00" 0.0 20.0

2.875" 0.0 754.75

CASING RECORD

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

TO

20.0

754.75

<