**The Perforators LLC**

# DUAL INDUCTION LOG

| | |
|---|---|
| Company | Charles N. Griffin |
| Well | Ash OWWO |
| Field | Medicine Lodge-Boggs |
| County | Barber |
| State | Kansas |

Company Charles N. Griffin
Well Ash OWWO
Field Medicine Lodge-Boggs
County Barber State Kansas
Location: API # : 15 007 20368 00 01
4485' FSL & 750' FEL
SEC 33 TWP 32S RGE 12W

Other Services
CDNL

| | | | |
|---|---|---|---|
| Permanent Datum | Ground Level | Elevation | 1615' |
| Log Measured From | KB 8' AGL | | |
| Drilling Measured From | KB | | |

Elevation
K.B. 1623'
D.F. 1622'
G.L. 1615'

| | | |
|---|---|---|
| Date | 8-16-11 | |
| Run Number | One | |
| Depth Driller | 4960' | |
| Depth Logger | 4965' | |
| Bottom Logged Interval | 4963' | |
| Top Log Interval | 3600' | |
| Casing Driller | 254' | |
| Casing Logger | 254' | |
| Bit Size | 7 7/8" | |
| Type Fluid in Hole | Chemical | |
| Density / Viscosity | 8.6/68/ | |
| pH / Fluid Loss | 12.0/10.4 | |
| Source of Sample | Pit | |
| Rm @ Meas. Temp | .32@82degf | |
| Rmf @ Meas. Temp | .24@82degf | |
| Rmc @ Meas. Temp | .51@82degf | |
| Source of Rmf / Rmc | Calculated | |
| Rm @ BHT | .23@116degf | |
| Time Circulation Stopped | 3:30 p.m. | |
| Time Logger on Bottom | 5:45 p.m. | |
| Maximum Recorded Temperature | 116 degf | |
| Equipment Number | T045 | |
| Location | Hays, KS. | |
| Recorded By | L. Smith | |
| Witnessed By | Mr. Bruce Reed | Mr. JR Griffin |

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

## Comments

South of Medicine Lodge on 281 2.5 mi. ,
W on Pleesent Valley Rd. Stay on main rd.,
when rd. curves S go across 2 cattle guards and stay on lease rd. to top of hill across from Griffin tank battery.

Thanks for using The Perforators LLC Hays, KS. (785-621-4604)

**The Perforators LLC**

## Main Pass

Database File: cgashowwooh.db
Dataset Pathname: pass2
Presentation Format: kdillin2
Dataset Creation: Tue Aug 16 17:58:26 2011 by Log Open-Cased 100827
Charted by: Depth in Feet scaled 1:600

**The Perforators LLC**

## Main Pass

Database File: cgashowwooh.db
Dataset Pathname: pass2
Presentation Format: kdil
Dataset Creation: Tue Aug 16 17:58:26 2011 by Log Open-Cased 100827
Charted by: Depth in Feet scaled 1:240

**The Perforators LLC**

## Repeat Pass

Database File: cgashowwooh.db
Dataset Pathname: pass1
Presentation Format: kdil
Dataset Creation: Tue Aug 16 17:46:51 2011 by Log Open-Cased 100827
Charted by: Depth in Feet scaled 1:240



### Calibration Report

Database File: cgashowwooh.db
Dataset Pathname: pass1
Dataset Creation: Tue Aug 16 17:46:51 2011 by Log Open-Cased 100827

### Dual Induction Calibration Report

Serial-Model: 080522-Probe
Surface Cal Performed: Fri Jul 29 15:35:44 2011
Downhole Cal Performed: Fri Jul 29 15:35:48 2011
After Survey Verification Performed: Fri Jul 29 15:35:57 2011

Surface Calibration

| Readings | References | Results |
|---|---|---|

| Loop: | Air | Loop | | Air | Loop | | m | b |
|---|---|---|---|---|---|---|---|---|
| Deep | -0.000 | 0.638 | V | 0.000 | 400.000 | mmho/m | 626.857 | 0.275 |
| Medium | 0.001 | 0.741 | V | 0.000 | 464.000 | mmho/m | 626.953 | -0.823 |

| Internal: | Zero | Cal | | Zero | Cal | | m | b |
|---|---|---|---|---|---|---|---|---|
| Deep | 0.000 | 0.638 | V | 0.000 | 400.000 | mmho/m | 627.013 | -0.291 |
| Medium | 0.001 | 0.741 | V | 0.000 | 464.000 | mmho/m | 627.190 | -0.915 |

Downhole Calibration

| | Readings | | | References | | | Results | |
|---|---|---|---|---|---|---|---|---|
| | Zero | Cal | | Zero | Cal | | m' | b' |
| Deep | 0.096 | 400.608 | mmho/m | 0.566 | 400.467 | mmho/m | 0.998 | 0.471 |
| Medium | -0.069 | 464.142 | mmho/m | 0.092 | 463.916 | mmho/m | 0.999 | 0.161 |
| LL3 | | 7.358 | V | | 750.000 | Ohm-m | | |
| | | 0.001 | V | | 12.000 | Ohm-m | | |
| | | -7.218 | V | | 3745.000 | mmho-m | | |

## Compensated Density Calibration Report

Serial-Model: 2501DHT-DHT
Source / Verifier: /
Master Calibration Performed: Fri Jul 29 13:49:52 2011

Master Calibration

| | Density | | Far Detector | Near Detector | |
|---|---|---|---|---|---|
| Magnesium | 1.730 | g/cc | 744.27 | 293.58 | cps |
| Aluminum | 2.700 | g/cc | 138.48 | 189.15 | cps |

Spine Angle = 75.35

Density/Spine Ratio = 0.558

| | Size | | Reading |
|---|---|---|---|
| Small Ring | 7.90 | in | 6064.22 |
| Large Ring | 14.00 | in | 10296.80 |

## Gamma Ray Calibration Report

Serial Number: 2000
Tool Model: P2000
Performed: Thu Jul 28 10:33:00 2011

Calibrator Value: 1.0 GAPI

Background Reading: 0.0 cps
Calibrator Reading: 1.0 cps

Sensitivity: 0.2200 GAPI/cps

## Neutron Calibration Report

Serial Number: 5108
Tool Model: PROBE
Performed: Sat Jul 30 10:54:34 2011

Calibrator Value: 1 NAPI

Calibrator Reading: 1 cps

Sensitivity: 1 NAPI/cps

| Sensor | Offset (ft) | Schematic | Description | Len (ft) | OD (in) | Wt (lb) |
|---|---|---|---|---|---|---|
| | |  | None | 0.75 | 1.50 | 5.00 |
| NEU | 37.96 | | NEU-PROBE (5108)<br>Probe | 4.92 | 3.63 | 85.00 |
| GR | 32.57 | | GR-P2000 (2000) | 3.67 | 3.25 | 40.00 |
| | | | CDL-DHT (2501DHT)<br>Digital High Temp CDL Tool | 9.69 | 4.00 | 201.00 |
| LSD | 23.78 | | | | | |
| DCAL | 23.49 | | | | | |
| SSD | 23.24 | | | | | |
| HEADVOLT | 21.47 | | | | | |
| CILD | 10.60 | | DIL-Probe (080522)<br>Probe Dual Induction | 21.47 | 4.00 | 345.00 |
| SP | 10.60 | | | | | |
| CILM | 6.89 | | | | | |
| RLL3 | 1.70 | | | | | |

Dataset: cgashowwooh.db: field/well/run1/pass2
Total Length: 40.49 ft
Total Weight: 676.00 lb
O.D. 4.00 in