Company SOUTHWINDS ENERGY, LLC
Well MELANDER #35
Field WAYSIDE-HAVANA
County MONTGOMERY Date 8-18-12
State KANSAS

ORNISH
WIRELINE SERVICES, INC.
CHANUTE, KANSAS

GAMMA RAY
CORRELATION
CEMENT BOND
COMPLETION LOG

MELANDER #35
SOUTHWINDS ENERGY, LLC
WAYSIDE-HAVANA
MONTGOMERY
KANSAS

Company SOUTHWINDS ENERGY, LLC
Well MELANDER #35
Field WAYSIDE-HAVANA
County MONTGOMERY Date 8-18-12
State KANSAS Section 35 Twp 34S Rge 16E

Permanent Datum: GL Elevation: 1000 ft above Perm. Datum
Log Measured From: KB 10 ft above Perm. Datum
Drilling Measured From: KB
Elevation: KB 1010 GL 1000

Date: 8-18-12
Run Number: ONE
Depth Driller: 1000
Depth Logger: 1000
Bottom Logged Interval: 1000
Top Logged Interval: 0
Type Fluid in Hole: WATER
Salinity, PPM Cl: 1000
Density / Viscosity: 8.4 / 28
pH / Fluid Loss: 7 / 0
Source of Sample: PIT
Rm @ Meas. Temp: .1 @ 70
Rmf @ Meas. Temp: .1 @ 70
Rmc @ Meas. Temp: .1 @ 70
Source of Rmf / Rmc: MEAS / MEAS
Rm @ BHT: .1 @ 70
Time Circulation Stopped: 1:00
Time Logger on Bottom: 2:30
Maximum Recorded Temperature: 70
Equipment Number: 1
Location: 15-34S-16E
Recorded By: JOE
Witnessed By: MR. MELANDER

Casing Record

| | Size | Wgt | Grade | From | To |
|---|---|---|---|---|---|
| Surface String | 8 5/8 | 24 | NEW | 0 | 20 |
| Production String | 4 1/2 | 9.5 | NEW | 0 | 1000 |

Bit Record

| Bit No | Type | Size | From | To |
|---|---|---|---|---|
| 1 | | 6 3/4 | 0 | 1000 |

Tubing Record

| | Size | Wgt | Grade | From | To |
|---|---|---|---|---|---|
| Tubing | 2 3/8 | 4.7 | NEW | 0 | 1000 |

Type Completion: NEW WELL
Packer Type: NONE
Bottom Hole Temp: 70
Pump Unit: NONE
Rod String: NONE
Oil Prod. During Test: 0 BOPD
Water Prod. During Test: 0 BWPD
Gas Prod. During Test: 0 MCFPD
Choke Size: 0
Oil Gravity: 0
Gas Gravity: 0
Gas-Oil Ratio: 0
Pump Size: 0
Stroke Length: 0
Pump Speed: 0
Shots Per Foot: 0
Perforations: 0

Remarks: RAN 1000' OF 4 1/2 CASING. CEMENTED WITH 100 SACKS OF 60/40 POZ. 2% GEL. 1/4# FLOCELE PER SACK. PLUG DOWN @ 2:30 PM 8-18-12. CIRCULATED CEMENT TO SURFACE.

T.D. 1000'

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretations and we shall not, except to the extent of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set forth in our current Price Schedule.

Comments

THANK YOU

| Service | Offset (ft) | Schematic | Description | Len (ft) | OD (in) | Wt (lb) |
|---|---|---|---|---|---|---|
| TEMP | 17.12 | | | | | |
| WVFSFT<br>WVFCAL<br>WVFSFT | 15.03<br>15.03<br>14.03 | | CBL/TEXICO 1KB,7x2 w/ Temp (Dec) (STD)<br>*Gauss Mid Eqpt 7-11/16" Dual Receiver with Temp | 9.79 | 1.69 | 50.00 |
| WVFTEMP<br>WVFENC | 10.62<br>10.62 | | | | | |
| GR | 7.29 | | GR-TITAN, 1KB [TITAN_GR1]<br>*Titan 1-1/4" Gamma Ray | 4.75 | 1.69 | 20.00 |
| CCL | 4.73 | | CCL-TITAN [TITN]<br>*ITAN 1-11/16 CCL | 1.53 | 1.69 | 8.00 |
| NEU | 0.63 | | *NEU-TITAN [TITNEU]<br>*ITAN 1-11/4" Neutron | 4.33 | 1.69 | 25.00 |

Dataset: <interior #35 (8) fieldfield>run1pass1
Top: 22.37 ft
Log Interval: 1000 ft
Scale: 1:50 in

Database File: h:\interior #35 (8)
Dataset Pathname: pass1
Presentation Format: cbl
Dataset Creation: Tue Sep 18 11:44:02 2012 by Log Std-Casedhole 09/97
Charted by: Depth in Feet scaled 1:240

| X | Caller Locator | | | | | X |
|---|---|---|---|---|---|---|
| 1000 | Gamma Ray | 1000 | 1200 | AMPSFT (mV) | 200 | VDL |
| 150 | GR | 900 | 1100 | TTSFT (usec) | 200 | 1200 |
| | | | 150 | | 1650 | 100 |

PERFORATIONS
2" DML RTG (1)
30 SHOTS @ 60° 45°-0°

| X | Caller Locator | | | | | X |
|---|---|---|---|---|---|---|
| 1000 | Gamma Ray | 1000 | 1200 | AMPSFT (mV) | 200 | VDL |
| 150 | GR | 900 | 1100 | TTSFT (usec) | 200 | 1200 |
| | | | 150 | NEU (cps) | 1650 | 100 |

Database File: h:\interior #35 (8)
Dataset Pathname: pass1
Presentation Format: cbl
Dataset Creation: Tue Sep 18 11:44:02 2012 by Log Std-Casedhole 09/97
Charted by: Depth in Feet scaled 1:240

| X | | | | | X |
|---|---|---|---|---|---|
| 150 | GR | 900 | 300.0 | CCL (V) 100 | 1200 |
| 150 | | | 150 | | 1650 |

PERFORATIONS
2" DML RTG
30 SHOTS @ 60° 45°-0°