Company	JACK HORTON
Well	MELANDER #16
Field	WAYSIDE-HAVANA
County	MONTGOMERY
State	KANSAS

ORNISH WIRELINE SERVICES, INC. CHANUTE, KANSAS

GAMMA RAY CASING COLLAR CEMENT BOND CORRELATION LOG

JACK HORTON MELANDER #16 WAYSIDE-HAVANA MONTGOMERY County KANSAS

Company: JACK HORTON
Well: MELANDER #16
Field: WAYSIDE-HAVANA
County: MONTGOMERY State: KANSAS
Location: API: 15-125-31630-00-00 Pos: NW SE SW Twp: 34S Rge: 14E
Permanent Datum: GROUND Elev.: 0
Log Measured From: KB 0 Ft. Above Perm. Datum
Drilling Measured From: KB
Elev.: K.B. 0 D.F. 0 G.L. 0
Date: 10-21-11
Run Number: ONE
Depth Driller: 1000
Depth Logger: 1000
Bottom Logged Interval: 1000
Top Logged Interval: SURFACE
Casing Driller: 8.625 @ 0
Casing Logger: 8.625 @ 0
Bit Size: 6.75
Type Fluid in Hole: WATER
Density / Viscosity: 8.4 / 28
pH / Fluid Loss: 7 / 0
Source of Sample: PIT
Rm @ Meas. Temp.: 0.1 @ 70
Rmf @ Meas. Temp.: 0.1 @ 70
Rmc @ Meas. Temp.: 0.1 @ 70
Source of Rmf / Rmc: MEAS / MEAS
Rm @ BHT: 0.1 @ 70
Time Since Circulation: 1 HOUR
Max. Rec. Temp. Deg. F: 70
Equipment / Location: 34 / CHANUTE
Recorded By: TIM
Witnessed By: MR. MARTIN

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except to the ease of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions as set out in our current Price Schedule.

Comments

THANK YOU

Service	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
TEMP	17.42					
WVFSFT	15.33		GBL TEMCO (WR %)F w Temp (Cal) (010)	9.75	1.69	50.00
WVFCAL	15.33		Telex 400 Deg F 1 11/16" Dual Receiver with Temp			
WVFSFT	14.33					
WVFTEMP	10.92					
WVFSYNC	10.92		GR-TTDBL 1000 (TTF150_021)	4.75	1.69	20.00
			Telex 11/16" Gamma Ray			
GR	7.59					
			CCL-11/16SL 1000 (TTF150)	1.83	1.69	7.50
CCL	5.05		Telex 11/16" Digital CCL			
			NEU-TTDAS (TTF871)	4.33	1.69	25.00
			Telex 11/16" Neutron			
NEU	0.83					

Cabled
Total Length: 22.01 ft
Total Weight: 102.50 lb
O.D: 1.69 in

instandard16.db: fieldsheet/run1/pass1
22.01 ft
102.50 lb
1.69 in

Database File: g:\instandard16.db
Dataset Pathname: pass1
Presentation Format: wvfc
Dataset Creation: Mon Oct 31 09:51:56 2011 by Log Rite Cassettes 0909 1
Charted by: Depth in Feet scaled 1:240

Caliper Locator	in
Gamma Ray	150
SP	300

AMPSFT (mv)	100 200
TTSFT (usec)	200
NEU (cps)	1000

VDL 1200

TEMPERATURE
2" GBL-WTR GUN
20 SHOTS 6x6 45SF

CCL
GR-WVF
NEU

Caliper Locator	in
Gamma Ray	150
SP	300

AMPSFT (mv)	100 200
TTSFT (usec)	200
NEU (cps)	1000

VDL 1200

Database File: g:\instandard16.db
Dataset Pathname: pass1
Presentation Format: gr-ccl
Dataset Creation: Mon Oct 31 09:51:56 2011 by Log Rite Cassettes 0909 1
Charted by: Depth in Feet scaled 1:240

Gamma Ray	
	150
SP	300
GR	150

CCL 0.05 200

NEU (cps) 1000

TEMPERATURE
2" GBL-WTR GUN
20 SHOTS 6x6 45SF

CCL
GR-WVF
NEU

Gamma Ray	
	150
SP	300
GR	150

CCL 0.05 200

NEU (cps) 1000

ORNISH WIRELINE SERVICES, INC. CHANUTE, KANSAS

Company JACK HORTON
Well MELANDER
Field WAYSIDE-HAVANA
County MONTGOMERY SEC 2 TWP 34S RGE 14E
State KANSAS Date 10-21-11