



MIDWEST SURVEYS
LOGGING - PERFORATING - CONSULTING SERVICES
P.O. Box 68, Osawatomie, KS 66064
913 / 755 - 2128

GAMMA RAY / NEUTRON / CCL

File No.

Company Altavista Energy, Inc.

Well McCann "B" No. A-5

Field Gardner

County Johnson State Kansas

Location 2175' FSL & 490' FEL

SW-NE-NE-SE

Sec. 15 Twp. 14S Rge. 22E

Permanent Datum GL Elevation N/A

Log Measured From GL

Drilling Measured From GL N/A

Date 03-05-2012

Run Number One

Depth Driller 919.0

Depth Logger 860.8

Bottom Logged Interval 859.8

Top Log Interval 200.0

Fluid Level Full

Type Fluid Water

Density / Viscosity NA NA

Salinity - PPM Cl NA

Max. Recorded Temp NA

Estimated Cement Top 0.0

Equipment No. 107 Osawatimie

Recorded By Steve Windisch

Witnessed By Doug Evans

BORE-HOLE RECORD

CASING RECORD

TO 22.0

FROM 0.0

SIZE 7.00"

WT. 0.0

FROM 0.0

TO 900.15

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"

FROM 0.0

TO 868.55

WT. 2.875"