



NABORS

**COMPLETION
& PRODUCTION
SERVICES CO.**

MICRO LOG

Company		DOWNING-NELSON OIL COMPANY, INC.	
Well	HILLMAN-DUBACH #1-31		
Field	WILDCAT		
County	TREGO	State	KANSAS
Location:		API # : 15-195-22809-0000	
SEC 31 TWP 12S RGE 21W		CDL/CNL DIL/SON	
Permanent Datum	GROUND LEVEL	Elevation	2275
Log Measured From	KELLY BUSHING 8' A.G.L.	K.B. 2283	
Drilling Measured From	KELLY BUSHING	D.F. 2281	
		G.L. 2275	
Date	10/7/12		
Run Number	TWO		
Depth Driller	4048		
Depth Logger	4048		
Bottom Logged Interval	4030		
Top Log Interval	3250		
Casing Driller	8 5/8" @ 219		
Casing Logger	217		
Bit Size	7 7/8		
Type Fluid in Hole	CHEMICAL MUD	CHLORIDES 1000 PPM	
Density / Viscosity	9.0/53		
pH / Fluid Loss	10.0/8.0		
Source of Sample	FLOWLINE		
Rim @ Meas. Temp	1.0 @ 55F		
Rmf @ Meas. Temp	.75 @ 55F		
Rmc @ Meas. Temp	1.20 @ 55F		
Source of Rmf / Rmc	MEASURED		
Rim @ BHT	.47 @ 117F		
Time Circulation Stopped	2 HOURS		
Time Logger on Bottom			
Maximum Recorded Temperature	117F		
Equipment Number	680		
Location	HAYS, KS.		
Recorded By	JASON CAPPELLUCCI		
Witnessed By	AL DOWNING		

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

THANK YOU FOR USING SUPERIOR WELL SERVICE (785) 628-6395
DIRECTIONS
HWY 40 & RIGA ELEVATOR - 1 W. - 1 1/4 N. - 1 W. - S. INTO

Database File:

009744ddn.db

Dataset Pathname:

pass7.1

Presentation Format:

_micro


Dataset Creation:


Sun Oct 07 09:34:44 2012 by Calc Open-Cased 090629

Charted by:

Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150	ABHV	0	MEL1.5 (Ohm-m)	40
6	CALIPER (in)	16	10 (ft3)	0 0	MEL2.0 (Ohm-m)	40
			TBHV			
			0 (ft3)	10		








3450


3500

3550

3600









REPEAT SECTION

Database File: 009744ddn.db
 Dataset Pathname: pass6.1
 Presentation Format: _micro
 Dataset Creation: Sun Oct 07 09:29:00 2012 by Calc Open-Cased 090629
 Charted by: Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150	ABHV	0	MEL1.5 (Ohm-m)	40
6	CALIPER (in)	16	10 (ft3) 0 0	0	MEL2.0 (Ohm-m)	40
			TBHV			
			0 (ft3) 10			





Calibration Report			
Database File:	009744ddn.db		
Dataset Pathname:	pass6.1		
Dataset Creation:	Sun Oct 07 09:29:00 2012 by Calc Open-Cased 090629		
MICRO Calibration Report			
Serial Number:	MICRO6		
Tool Model:	PROBE		
Performed:	Thu Aug 16 14:43:41 2012		
Caliper Calibration:	Gain=6.253	Offset=-1.608	
	Low Cal	High Cal	
References	5.800	13.000	
Readings	1.178	2.330	
1.5" Calibration:	Gain=30.075	Offset=0.300	
	Low Cal	High Cal	
References	0.000	20.000	
Readings	0.004	1.196	
2" Calibration:	Gain=30.041	Offset=0.500	
	Low Cal	High Cal	
References	0.000	20.000	
Readings	0.006	0.913	
Gamma Ray Calibration Report			
Serial Number:	#8		
Tool Model:	OPEN		
Performed:	Mon Jun 13 16:56:43 2011		
Calibrator Value:	150.0	GAPI	
Background Reading:	0.0	cps	
Calibrator Reading:	175.0	cps	
Sensitivity:	0.8371	GAPI/cps	