



NABORS

**COMPLETION
& PRODUCTION
SERVICES CO.**

DUAL INDUCTION LOG

Company		DOWNING-NELSON OIL COMPANY, INC.	
Well	HILLMAN-DUBACH #1-31		
Field	WILDCAT		
County	TREGO	State	KANSAS
Location:	SEC 31 TWP 12S RGE 21W 600' FNL & 270' FEL SE - NE - NE - NE		API # : 15-195-22809-0000 CDL/CNL MEL/SON
Permanent Datum	GROUND LEVEL	Elevation	2275
Log Measured From	KELLY BUSHING 8' A.G.L.		K.B. 2283
Drilling Measured From	KELLY BUSHING		D.F. 2281
			G.L. 2275
Date	10/7/12		
Run Number	ONE		
Depth Driller	4048		
Depth Logger	4048		
Bottom Logged Interval	4046		
Top Log Interval	00		
Casing Driller	8 5/8" @ 219		
Casing Logger	217		
Bit Size	7 7/8		
Type Fluid in Hole	CHEMICAL MUD	CHLORIDES 1000 PPM	
Density / Viscosity	9.0/53		
pH / Fluid Loss	10.0/8.0		
Source of Sample	FLOWLINE		
Rim @ Meas. Temp	1.0 @ 55F		
Rmf @ Meas. Temp	.75 @ 55F		
Rmc @ Meas. Temp	1.20 @ 55F		
Source of Rmf / Rmc	MEASURED		
Rim @ BHT	.47 @ 117F		
Time Circulation Stopped	2 HOURS		
Time Logger on Bottom			
Maximum Recorded Temperature	117F		
Equipment Number	680		
Location	HAYS, KS.		
Recorded By	JASON CAPPELLUCCI		
Witnessed By	AL DOWNING		

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

THANK YOU FOR USING SUPERIOR WELL SERVICE (785) 628-6395
 DIRECTIONS
 HWY 40 & RIGA ELEVATOR - 1 W. - 1 1/4 N. - 1 W. - S. INTO



NABORS
 COMPLETION
 & PRODUCTION

MAIN SECTION

Database File:

009744ddn.db

Dataset Pathname:

pass4.2

Presentation Format:

_dil2


Dataset Creation:


Sun Oct 07 08:04:21 2012 by Calc Open-Cased 090629

Charted by:

Depth in Feet scaled 1:600

0	Gamma Ray (GAPI)	150	0	RLL3 (Ohm-m)	50
-100	SP (mV)	100	0	Deep Induction (Ohm-m)	50
-----			1000	CILD (mmho/m)	0
			50	RILD X10 (Ohm-m)	500
			50	RLL3 X10 (Ohm-m)	500





450

500

550

600

650

700


750

800



850



900


950




1000
1050
1100
1150
1200
1250
1300
1350
1400
1450
1500








2100
2150
2200
2250
2300
2350
2400
2450
2500
2550
2600





2650

2700

2750

2800

2850

2900


2950


3000

3050

3100

3150





3200

3250

3300

3350

3400

3450


3500


3550

3600

3650

3700






**COMPLETION
& PRODUCTION
SERVICES CO.**

ANHYDRITE

Database File: 009744ddn.db
 Dataset Pathname: pass4.3
 Presentation Format: _dil
 Dataset Creation: Sun Oct 07 07:29:20 2012 by Calc Open-Cased 090629
 Charted by: Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150	0.2	SHALLOW GUARD (Ohm-m)	2000
-100	SP (mV)	100	0.2	MEDIUM INDUCTION (Ohm-m)	2000
-250	Rxo/Rt	50	0.2	DEEP INDUCTION (Ohm-m)	2000




0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	Rxo/Rt	50

1650

1700


1750

1800





0.2	SHALLOW GUARD (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000

0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	Rxo/Rt	50



0.2	SHALLOW GUARD (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000






3450


3500

3550

3600

3650







3700

3750

3800

3850






3900

3950

4000


LTD 4048
4050




NABORS
COMPLETION
& PRODUCTION
SERVICES CO.

REPEAT SECTION

0	GAMMA RAY (GAPI)	150	0.2	SHALLOW GUARD (Ohm-m)	2000
-100	SP (mV)	100	0.2	MEDIUM INDUCTION (Ohm-m)	2000
-250	Rxo/Rt	50	0.2	DEEP INDUCTION (Ohm-m)	2000





Calibration Report

Database File: 009744ddn.db
Dataset Pathname: pass3.1
Dataset Creation: Sun Oct 07 07:04:15 2012 by Calc Open-Cased 090629

Dual Induction Calibration Report

Serial-Model: PROBE8-DILG
Surface Cal Performed: Fri Aug 01 06:33:19 2008
Downhole Cal Performed: Mon Jul 28 11:08:27 2008
After Survey Verification Performed: Mon Jul 28 11:08:27 2008

Surface Calibration								
Readings				References			Results	
Loop:	Air	Loop		Air	Loop		m	b
Deep	0.015	0.648	V	0.000	400.000	mmho/m	632.616	-9.730
Medium	0.029	0.796	V	0.000	464.000	mmho/m	605.049	-17.680
Internal:	Zero	Cal		Zero	Cal		m	b
Deep	0.017	0.657	V	0.000	400.000	mmho/m	625.153	-10.619
Medium	0.016	0.757	V	0.000	464.000	mmho/m	625.992	-9.739

Downhole Calibration								
Readings				References			Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	2.011	405.777	mmho/m	1.000	0.000
Medium	0.000	0.000	mmho/m	7.590	503.393	mmho/m	1.000	0.000
LL3		7.500	V		1500.000	Ohm-m		
		0.000	V		20.000	Ohm-m		
		-7.200	V		3800.000	mmho-m		

After Survey Verification								
Readings				Targets			Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
Medium	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
LL3		1.000	Ohm-m		1.000	Ohm-m		
		0.000	Ohm-m		0.000	Ohm-m		
		1.000	mmho-m		1.000	mmho-m		

Compensated Density Calibration Report

Serial-Model: GEAR4-GEARHART
Source / Verifier: 143 / 143
Master Calibration Performed: Mon Mar 19 19:07:19 2012

Master Calibration

	Density			Far Detector		Near Detector	
Magnesium	1.710	g/cc		1015.91		497.51	cps
Aluminum	2.600	g/cc		227.67		350.20	cps
	Spine Angle = 76.79			Density/Spine Ratio = 0.579			
	Size			Reading			
Small Ring	8.00	in		3.21		V	
Large Ring	14.00	in		5.46		V	

Compensated Neutron Calibration Report
--

Serial Number:	6I
Tool Model:	G

CALIBRATION						
Detector	Readings		Target		Normalization	
Short Space	1.00	cps	1.00	cps	1.0000	
Long Space	1.00	cps	1.00	cps	1.0000	

Gamma Ray Calibration Report

Serial Number:	#8	
Tool Model:	OPEN	
Performed:	Mon Jun 13 16:56:43 2011	
Calibrator Value:	150.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	175.0	cps
Sensitivity:	0.8371	GAPI/cps