

Company

COLT ENERGY INC.

Well

UNGEHEUER, D & B # G2-C

Field

CRITZER

County

LINN

State

KANSAS

Location:

SEC 34 TWP 21S RGE 22E
NW/4 SW/4
101W FS. & 180 F.ML

API #: 15-107-24604-0000

Offer Services
CDUS/MN

Permanant Datum

SEC 34 TWP 21S RGE 22E

Elevation

1004' est

Drilling Measured From

GL

GL 1004' est

Date

Run Number

ONE

Depth Driller

8307

Bottom Logged Interval

825

Top Log Interval

Casing Inner

8.625 @ 21"

Casing Outer

8.625 @ 21"

Case Seal

8.625 @ 21"

Top of Hole

WATER

Density / Viscosity

pH / Fluid Loss

Source of Sample

Rm @ Meas. Temp

Rmt @ Meas. Temp

Source of Rmt / Rmc

Rm @ BHT

Time Circulation Stopped

Maximum Recorded Temperature

Equipment Number

Location

Recorded By

OW2
HOMINY, OK
LOWER
MR. STEGBMAN

Witnessed By

DUAL INDUCTION
LL3/GR LOG

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

OW2-8135
CREW : JOHNSON

Database File:

ow2-8135 colt energy.db

Dataset Pathname:

DIL/pass1.2

Presentation Format:

dil2nomed

Dataset Creation:

Tue Apr 24 13:10:31 2012 by Calc SOC 111108

Charted by:

Depth in Feet scaled 1:600

0

GR (GAPI)

150

0

RLL3 (Ohm-m)

50

0

RILD (Ohm-m)

50

1000

CILD (mmho/m)

0

50

100

150

200

250

300

350

400

450

500

550

600

650

700

750

800

0

GR (GAPI)

150

0

RLL3 (Ohm-m)

50

0

RILD (Ohm-m)

50

1000

CILD (mmho/m)

0

Database File:

ow2-8135 colt energy.db

Dataset Pathname:

DIL/pass1.1

Presentation Format:

dil5air

Dataset Creation:

Tue Apr 24 13:10:19 2012 by Calc SOC 111108

Charted by:

Depth in Feet scaled 1:240

0

GR (GAPI)

150

0.2

RILD (Ohm-m)

2000

0.2

RLL3 (Ohm-m)

2000

0.2

RILM (Ohm-m)

2000

50

100

150

200

250

300

350

400

450

500

550

600

650

700

750

800

0

GR (GAPI)

150

0.2

RILD (Ohm-m)

2000

0.2

RLL3 (Ohm-m)

2000

0.2

RILM (Ohm-m)

2000

Sensor

Offset (ft)

Schematic

Description

Len (ft)

OD (in)

Wt (lb)

CableHead
Insulation Sub

1.42

3.00

20.00

DIL-GEAR (158)
Dual Induction Electrical Log

20.08

4.00

345.00

CILD
SP

10.92
10.92

CILM

7.00

RLL3

1.67

Dataset:

ow2-8135 colt energy.db: field/well/DIL/pass1

Total Length:

21.50 ft

Total Weight:

365.00 lb

O.D.:

4.00 in