



**COMPLETION
& PRODUCTION
SERVICES CO.**

**DUAL
INDUCTION
LOG**

Company DOWNING - NELSON OIL CO., INC.
Well LW #1-18
Field RIGA NORTHWEST
County TREGO State KANSAS

Company DOWNING - NELSON OIL CO., INC.
Well LW #1-18
Field RIGA NORTHWEST
County TREGO
State KANSAS

Location: API #: 15-195-22817
1225' FNL & 930' FWL
SEC 18 TWP 13S RGE 21W
Permanent Datum GROUND LEVEL Elevation 2210
Log Measured From KELLY BUSHING 8' A.G.L.
Drilling Measured From KELLY BUSHING
Other Services
CDL/CNL
MICRO
Elevation
K.B. 2218
D.F.
G.L. 2210

Date	10-23-12
Run Number	ONE
Depth Driller	4080
Depth Logger	4080
Bottom Logged Interval	4078
Top Log Interval	00
Casing Driller	220
Casing Logger	219
Bit Size	7.875
Type Fluid in Hole	CHEMICAL MUD
Density / Viscosity	9.3 / 57
pH / Fluid Loss	10.0 / 8.8
Source of Sample	FLOWLINE
Rim @ Meas. Temp	1.00 @ 62F
Rmf @ Meas. Temp	0.75 @ 62F
Rmc @ Meas. Temp	1.20 @ 62F
Source of Rmf / Rmc	MEASURED
Rim @ BHT	.530 @ 116F
Time Circulation Stopped	2 HOURS
Time Logger on Bottom	9:45 A.M.
Maximum Recorded Temperature	116F
Equipment Number	860
Location	HAYS, KS.
Recorded By	RUPP
Witnessed By	RON NELSON

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

NABORS COMPLETION & PRODUCTION CO.
THANK YOU FOR YOUR BUSINESS
DIRECTIONS: ELLIS & OLD #40, W TO 360th, 2 1/8S TO TANK BATTERIES, 200'W, N & W INTO ON THE LEASE RD.





**COMPLETION
& PRODUCTION**

MAIN SECTION

Database File: 009937ddn.db
 Dataset Pathname: pass3.2
 Presentation Format: dil2
 Dataset Creation: Tue Oct 23 11:40:11 2012
 Charted by: Depth in Feet scaled 1:600

0	Gamma Ray (GAPI)	150	0	RLL3 (Ohm-m)	50
			0	Deep Induction (Ohm-m)	50
			1000	CILD (mmho/m)	0
			50	RILD X10 (Ohm-m)	500
			50	RLL3 X10 (Ohm-m)	500





450

500

550

600

650

700



750


800

850



900



950






1000
1050
1100
1150
1200
1250
1300
1350
1400
1450
1500







2100

2150

2200

2250

2300

2350



2400


2450

2500

2550

2600





2650

2700

2750

2800

2850

2900


2950


3000

3050



3100


3150





3200
3250
3300
3350
3400
3450
3500
3550
3600
3650
3700







MAIN SECTION

Database File: 009937ddn.db
 Dataset Pathname: pass3.2
 Presentation Format: dil
 Dataset Creation: Tue Oct 23 11:40:11 2012
 Charted by: Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	100
-100	SP (mV)	100
-250	RxoRt	50
0	MINMK	20

0.2	RLL3 (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000



0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	RxoRt	50
0	MINMK	20

0.2	RLL3 (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000


**& PRODUCTION
SERVICES CO.**

WELL LOG


Database File: 009937ddn.db
 Dataset Pathname: pass3.2
 Presentation Format: dil
 Dataset Creation: Tue Oct 23 11:40:11 2012
 Charted by: Depth in Feet scaled 1:240


0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	RxoRt	50
0	MINMK	20

0.2	RLL3 (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000



3200
3250
3300
3350







3400

3450

3500

3550






3600



3650


3700

3750

3800








0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	RxoRt	50
0	MINMK	20

4050

--- TD ---



0.2	RLL3 (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000




REPEAT SECTION


Database File: 009937ddn.db
 Dataset Pathname: pass2.2
 Presentation Format: dil
 Dataset Creation: Tue Oct 23 11:15:56 2012 by Calc Open-Cased 090629
 Charted by: Depth in Feet scaled 1:240


0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	RxoRt	50
0	MINMK	20

0.2	RLL3 (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000



3900






3950

4000

4050

0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	RxoRt	50
0	MINMK	20



0.2	RLL3 (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000

Calibration Report

Database File: 009937ddn.db
 Dataset Pathname: pass3.2
 Dataset Creation: Tue Oct 23 11:40:11 2012

Dual Induction Calibration Report

Serial-Model: DIL5-GEAR
 Performed: Tue Oct 23 09:24:49 2012

Loop:	Readings			References			Results	
	Air	Loop		Air	Loop		m	b
Deep	0.004	0.654	V	0.000	400.000	mmho/m	470.000	-11.000
Medium	-0.005	0.737	V	0.000	462.500	mmho/m	500.000	-7.000
Internal:	Zero	Cal		Zero	Cal		m	b
Deep	0.006	0.655	V	0.000	400.000	mmho/m	615.668	-3.483
Medium	0.010	0.747	V	0.000	462.500	mmho/m	627.607	-6.064

Compensated Density Calibration Report

Serial-Model: GEAR1-GEARHART
 Source / Verifier: 147 / 147
 Master Calibration Performed: Tue Oct 23 10:17:51 2012

Master Calibration

	Density		Far Detector	Near Detector	
Magnesium	1.710	g/cc	1205.67	613.10	cps
Aluminum	2.590	g/cc	277.64	430.46	cps
Spine Angle = 76.46			Density/Spine Ratio = 0.583		
	Size		Reading		
Small Ring	9.50	in	4.69	V	
Large Ring	14.00	in	6.52	V	

Compensated Neutron Calibration Report

Serial Number: NUE_2I
 Tool Model: G

CALIBRATION

Detector	Readings		Target		Normalization
Short Space	1.00	cps	1.00	cps	1.0000
Long Space	1.00	cps	1.00	cps	1.0000

Gamma Ray Calibration Report

Serial Number: GR5
 Tool Model: OPEN
 Performed: Tue Oct 23 09:24:00 2012

Calibrator Value: 1.0 GAPI

Background Reading: 0.0 cps
 Calibrator Reading: 1.0 cps

Sensitivity: 0.7500 GAPI/cps