ORNISH
WIRELINE OPERATIONS
CHANUTE, KANSAS

GAMMA RAY CASING COLLAR CEMENT BOND CORRELATION LOG

Company: G & J OIL COMPANY, INC.
Well: MEADOWS #12-16
Field: WAYSIDE-HAVANA
County: MONTGOMERY
State: KANSAS

Company G & J OIL COMPANY, INC
Well MEADOWS #12-16
Field WAYSIDE-HAVANA
County MONTGOMERY
State KANSAS
Location SEC 1 TWP 34S RGE 14E
Permanent Datum Ground Level
Log Measured From KB
Drilling Measured From KB
Elevation KB 0 ft
GL 0 ft
DF 0 ft
API Serial No.
Date 10-17-12
Run Number ONE
Depth Driller 1700 ft
Depth Logger 1700 ft
Bottom Logged Interval 1700 ft
Top Logged Interval 0 ft
Casing Driller 7 in @ 1700 ft
Casing Logger 1700 ft
Bit Size 6.25 in
Type Fluid in Hole WATER
Density / Viscosity 8.4 / 28
pH / Fluid Loss
Source of Sample
Rm @ Measured Temp
Rmf @ Measured Temp
Rmc @ Measured Temp
Source of Rmf / Rmc
Rm @ BHT
Time Since Circulation
Time Logger on Bottom 10-17-12 12:00
Max Recorded Temperature
Equipment Number
Location
Recorded By
Witnessed By

All interpretations we may express based on inferences from electrical or other measurements are our opinion and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except to the extent of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set forth in our current Price Schedule.

Comments

THANK YOU

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	ID (in)
TEMP	17.42					
AVFSFT	15.33		CBL/TEXCO-1606 1x2 w Temp (Cal) (SYS Telem 400 bps) + 11/16" Cast Resin-45 with Temp	9.75	1.69	50.00
AVFLFAL	15.33					
AVFSFT	14.33					
AVFTEMP	10.92		GR-TITAN, 1606 (TITTRR_SSTC	4.75	1.69	20.00
AVFSYNC	10.92		Telem + 11/16" Gamma Ray			
GR	7.59					
CCL	5.05		CCL-TITAN, 1606 (TITTRR	1.83	1.69	7.50
			Telem + 11/16" Gamma Ray			
NEU	0.63		NEU-TITAN (TITNEU	4.33	1.69	25.00
			TITAN + 11/16" Sonde			

Dataset: meadows #12-16 db: fieldwithcurrtypass1
Time Length: 03:11 h
Time Weight: 0.0 s
CCI: 1.59 in

Database File: h:\meadows #12-16.db
Dataset Name: field_a
Presentation Format: ornl_a
Dataset Creation: Wed Oct 17 11:11:56 2012 by Log Std Case/hole 09001
Charted by: Depth in Feet scaled 1:240

	Collar Locator		AMPSFT (mm)	100 200	VDL	1200
0	Gamma Ray	150	1200	TTIFT (usec) 200		
150	gr	300	1700	TTIFT (usec) 300		
			NEU (SPE	1600		

PERFORATION
1 CNL RTG
13 SHOTS @ 644'-650'
20 SHOTS @ 654'-664'

TTIFT
NEU
AMPSFT

	Collar Locator		AMPSFT (mm)	100 200	VDL	1200
0	Gamma Ray	150	1200	TTIFT (usec) 200		
150	gr	300	1700	TTIFT (usec) 300		
			NEU (SPE	1600		

Database File: h:\meadows #12-16.db
Dataset Name: field_a
Presentation Format: gr-ccl-neu
Dataset Creation: Wed Oct 17 11:11:56 2012 by Log Std Case/hole 09001
Charted by: Depth in Feet scaled 1:240

	CCL(SPE)		NEU (SPE	1600
0	GR	150		

PERFORATION
1 CNL RTG
13 SHOTS @ 644'-650'
20 SHOTS @ 654'-664'

TTIFT
NEU
CCL

	CCL(SPE)		NEU (SPE	1600
150	GR	300		

ORNISH
WIRELINE OPERATIONS
CHANUTE, KANSAS

Company G & J OIL COMPANY, INC
Well MEADOWS #12-16
Field WAYSIDE-HAVANA
County MONTGOMERY
State KANSAS
Location SEC 1 TWP 34S RGE 14E
Permanent Datum Ground Level
Log Measured From KB
Drilling Measured From KB
Elevation KB 0 ft
GL 0 ft
DF 0 ft
API Serial No.
Date 10-17-12
Run Number ONE
Depth Driller 1700 ft
Depth Logger 1700 ft
Bottom Logged Interval 1700 ft
Top Logged Interval 0 ft
Casing Driller 7 in @ 1700 ft
Casing Logger 1700 ft
Bit Size 6.25 in
Type Fluid in Hole WATER
Density / Viscosity 8.4 / 28
pH / Fluid Loss
Source of Sample
Rm @ Measured Temp
Rmf @ Measured Temp
Rmc @ Measured Temp
Source of Rmf / Rmc
Rm @ BHT
Time Since Circulation
Time Logger on Bottom 10-17-12 12:00
Max Recorded Temperature
Equipment Number
Location
Recorded By
Witnessed By