



**MIDWEST SURVEYS**  
 LOGGING - PERFORATING - CONSULTING SERVICES  
 P.O. Box 68, Osawatomie, KS 66064  
 913 / 755 - 2128

**GAMMA RAY / NEUTRON / CCL**

File No. \_\_\_\_\_

Company Triple "T" Oil, LLC.

Well South Beckmeyer No. - 55

Field Paola / Rantoul

County Franklin State Kansas

Location 495' FSL & 2145' FEL  
NE-SW-SW-SE

Sec. 32 Type 15s Rq. 21e  
Perforated Datum GL Elevation NA  
Log Measured From GL  
Drilling Measured From GL

Date 11-19-2012

Run Number One

Depth Diller 819.0

Depth Logger 778.0

Bottom Logged Interval 777.0

Top Log Interval 20.0

Fluid Level

Type Fluid Water

Density / Viscosity NA

Salinity - PPM Cl NA

Max Recorded Temp NA

Estimated Cement Top 0.0

Equipment No. Location 104 Osawatimie

Recorded By Gary Windisch

Witnessed By Lance Town

BORE-HOLE RECORD

NO. BIT FROM TO SIZE WGT. FROM TO

One 9.875" 0.0 21.0 6.75" 0.0 21.0

Two 5.625" 21.0 819.0 2.875" 0.0 795.0

Bottom 782.0

CASING RECORD

TO

782.0

AI

Set

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0

0.0

2.875"

0.0

795.0

782.0

819.0

21.0

6.75"

0.0

21.0</