

ORNISH

WIRELINE SERVICES, INC.

CHANUTE, KANSAS

GAMMA RAY

NEUTRON

COMPLETION LOG

Company

TAILWATER, INC.

Well

WHITESIDE #6-T

Field

GARNETT SHOESTRING

County

ANDERSON

State

KANSAS

Location:

E2/NE/NE-SW
2310 FSL & 2475 FWL
SEC 22 TWP 20S RGE 20E

API # : 15-003-25417-00-00

Other Services

Permanent Down

Log Measured From

Drilling Measured From

GL

GL

GL

Elevation

958 EST.

K.B.

D.F.

GL 958 EST.

Date

4-24-2012

Run Number

1-NW

Depth Driller

801'

Depth Logger

783'

Top Log Interval

0

Bottom Logged Interval

783'

Fluid Level

FULL

Type Fluid

WATER

Production Casing

2-7/8" @ 791'

Max. Recorded Temp.

7~ @ 224'

Estimated Cement Top

Calculated Cement Top

Amount & Type Cement

Amount & Type Admix

Drilling Contractor

EVANS ENERGY

Equipment Number

107

Location

Recorded By

UDEN, D.

Witnessed By

HUTCHINSON, D.

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

THANK YOU

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
GR	7.59		GR-TITAN_169 (TIT169_001) Titan 1 11/16" Gamma Ray	4.75	1.69	20.00
CCL	5.05		CCL-TITAN_169 (TIT169) Titan 1 11/16" Logging CCL	1.83	1.69	7.50
NEU	0.63		NEU-TITAN_169 (TIT169_001) Titan 1 11/16" Neutron	4.33	1.69	20.00
Dataset: whiteside #6-t.db: field/well/run1/pass1 Total Length: 10.92 ft Total Weight: 47.50 lb O.D.: 1.69 in						

Database File: g:\whiteside #6-t.db
Dataset Pathname: pass1
Presentation Format: dirk 1
Dataset Creation: Tue Apr 24 11:41:17 2012 by Log Std Casedhole 07122
Charted by: Depth in Feet scaled 1:240

150	gr	300	100	NEU	1500	
0	GR	150		13	CCL	-1

PERFORATIONS
11 SHOTS @ 622' TO 627'
13 SHOTS @ 661' TO 667'
7 SHOTS @ 725' TO 728'
7 SHOTS @ 736' TO 739'
7 SHOTS @ 741' TO 744'
45 TOTAL PERFORATIONS
2 SPF

GR → NEU → CCL →

ORNISH

WIRELINE SERVICES, INC.

CHANUTE, KANSAS

Company

TAILWATER, INC.

Well

WHITESIDE #6-T

Field

GARNETT SHOESTRING

County

ANDERSON

State

KANSAS

Date

4-24-2012