



Microresistivity Log

Pioneer Energy Services

API No.

15-051-26497-00-00

Company **Staab Oil Company**

Well **Furthmeyer #1**

Field **Unnamed**

County **Ellis** State **Kansas**

Location **980' FNL & 1125' FWL**

Sec: **29** Twp: **12S** Rge: **19W**

Other Services
CNL/CDL
DIL

Permanent Datum **Ground Level** Elevation **2167**

Log Measured From **Kelly Bushing** 5 Ft. Above Perm. Datum

Drilling Measured From **Kelly Bushing** Elevation **2172**
D.F. **2167**
G.L. **2167**

Date **03-25-2013**

Run Number **Two**

Depth Driller **3910**

Depth Logger **3907**

Bottom Logged Interval **3906**

Top Log Interval **3150**

Casing Driller **8.625 @ 210**

Casing Logger **210**

Bit Size **7.875**

Type Fluid in Hole **Chemical**

Salinity,ppm CL **1900**

Density / Viscosity **9.4 @ 56**

pH / Fluid Loss **10.0 @ 8.0**

Source of Sample **Flowline**

Rm @ Meas. Temp **0.75 @ 54**

Rmf @ Meas. Temp **0.56 @ 54**

Rmc @ Meas. Temp **1.01 @ 54**

Source of Rmf / Rmc **Charts**

Rm @ BHT **0.35 @ 117**

Operating Rig Time **3 1/2 Hours**

Max Rec. Temp. F **117**

Equipment Number **91**

Location **Hays**

Recorded By **D.Schmidt**

Witnessed By **Frank Staab**

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.


Comments

Thank you for using Log-Tech, Inc.
(785) 625-3858

Yocemento,
4 North to Locust Grove, 1 3/4 West,
South into

Database File: staab_032513hd.db
Dataset Pathname: dil/stbstk
Presentation Format: micro
Dataset Creation: Mon Mar 25 21:46:24 2013
Charted by: Depth in Feet scaled 1:240

Charted by: Depth in Feet scaled 1:210		
0	Gamma Ray (GAPI)	150
6	MCAL (in)	16
2.875	Mud Cake (in)	7.875
-200	SP (mV)	0




3150

3200

3250

3300

0	Micro Inverse 1 X 1 (Ohm-m)	40
0	Micro Normal 2" (Ohm-m)	40
10000	Line Weight (lb)	0
		LSPD (ft/min)




-29

-29

-29

-28




3350

3400

3450

3500

3550





-29


-29

-28

-28

-28






0	Gamma Ray (GAPI)	150
6	MCAL (in)	16
2.875	Mud Cake (in)	7.875
-200	SP (mV)	0

3800

3850

3900



0	Micro Inverse 1 X 1 (Ohm-m)	40
0	Micro Normal 2" (Ohm-m)	40
10000	Line Weight (lb)	0

LSPD
(ft/min)