

Comments

THANKS FOR USING PERF-TECH WIRELINE
785-623-3969
ALEXANDER KS,
2 1/2 WEST, SOUTH INTO

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

<<< Fold Here >>>

Database File: 00430138.db
Dataset Pathname: pass3
Presentation Format: 3x5
Dataset Creation: Tue Apr 30 16:13:01 2013 by Log SCH 120126
Charted by: Depth in Feet scaled 1:240

0 Gamma Ray (GAPI) 150 0 3' AMPLITUDE (mV) 100 200 5' Variable Density 1100
775 3' TRAVEL TIME (usec) 275
9 Collar Locator -1

3000
3050
3100
3150
3200
3250
3300
3350
3400
3450
3500
3550
3600
3650
3700
3750
3800
3850
3900
3950
4000
4050
4100
4150
4200

LOGGED TD @ 217

0 Gamma Ray (GAPI) 150 0 3' AMPLITUDE (mV) 100 200 5' Variable Density 1100
775 3' TRAVEL TIME (usec) 275
9 Collar Locator -1

4050
4100
4150
4200

LOGGED TD @ 217

0 Gamma Ray (GAPI) 150 0 3' AMPLITUDE (mV) 100 200 5' Variable Density 1100
775 3' TRAVEL TIME (usec) 275
9 Collar Locator -1

4050
4100
4150
4200

LOGGED TD @ 217

Database File: 00430138.db
Dataset Pathname: pass2
Presentation Format: 3x5
Dataset Creation: Tue Apr 30 16:08:08 2013 by Log SCH 120126
Charted by: Depth in Feet scaled 1:240

0 Gamma Ray (GAPI) 150 0 3' AMPLITUDE (mV) 100 200 5' Variable Density 1100
775 3' TRAVEL TIME (usec) 275
9 Collar Locator -1

4050
4100
4150
4200

LOGGED TD @ 217

0 Gamma Ray (GAPI) 150 0 3' AMPLITUDE (mV) 100 200 5' Variable Density 1100
775 3' TRAVEL TIME (usec) 275
9 Collar Locator -1

4050
4100
4150
4200

LOGGED TD @ 217