



Dual Compensated Porosity Log

Pioneer Energy Services

API No.

15-063-22,076-00-00

Company H & C Oil Operating, Inc.

Well Herl #27-2

Field Wildcat

County Gove

State Kansas

Location

460' FNL & 470' FEL

Other Services
DIL
MEL

Sec: 27

Twp: 13 S

Rge: 26 W

Elevation

Permanent Datum Ground Level Elevation 2381
Log Measured From Kelly Bushing 11 Ft. Above Perm. Datum
Drilling Measured From Kelly Bushing

K.B. 2392
D.F.
G.L. 2381

Date 2/6/2013

Run Number

One

Type Log

CNL / CDL

Depth Driller

4290

Depth Logger

4289

Bottom Logged Interval

4268

Top Logged Interval

3500

Type Fluid In Hole

Chemical

Salinity, PPM CL

2000

Density

9.3

Level

Full

Max. Rec. Temp. F

119

Operating Rig Time

4 Hours

Equipment -- Location

15 Days

Recorded By

D. Martin

Witnessed By

Marc Downing

Borehole Record

Casing Record

Run No.

Bit

From

To

Size

Wgt.

From

To

1 12.25

00

270

8.625

24#

00

270

2 7.875

270

4290

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Thank you for using Pioneer Energy Services
www.pioneerres.com
785 625 3858

Collyer, KS
8 1/2 S, 4 W, S Into

Database File: c:\warrior\data\h&c_herl #27-2\h&chd.db
Dataset Pathname: DIL\hcstk
Presentation Format: cdl
Dataset Creation: Wed Feb 06 11:30:15 2013
Charted by: Depth in Feet scaled 1:600

0	Gamma Ray	150
6	Caliper (GAPI)	16

30	Compensated Density		-10
2	Bulk Density		3
15000	Line Tension		0
2.625	DGA	3.425	-0.25
		Correction	0.25
LSPD			











