



Dual Compensated Porosity Log

Pioneer Energy Services

API No.

15-109-21,156-00-00

Company Brito Oil Company, Inc.

Well Fairleigh "G" No.1-19

Field Wildcat

County Logan

State Kansas

Location 400' FNL & 990' FEL

Other Services
DIL/MEL

Sec: 19 Twp: 15S Rge: 32W

Permanent Datum Ground Level Elevation 2791
Log Measured From Kelly Bushing 9 Ft. Above Perm. Datum
Drilling Measured From Kelly Bushing

Elevation
K.B. 2800
D.F. 2791
G.L. 2791

Date 2/27/2013

Run Number One

Type Log CNL / CDL

Depth Driller 4540

Depth Logger 4545

Bottom Logged Interval 4524

Top Logged Interval 3500

Type Fluid In Hole Chemical

Salinity, PPM CL 4,000

Density 9.4

Level Full

Max. Rec. Temp. F 121

Operating Rig Time 4 Hours

Equipment -- Location 17 Days

Recorded By C. Desaire

Witnessed By Kevin Kessler

Borehole Record

Casing Record

Run No. Bit From To Size Wgt. From To

One 12.25 00 236 8.625 23# 00 236

Two 7.875 236 TD

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Thank you for using Log-Tech, Inc.
(785) 625-3858

Oakley KS, S to Gold Rd, 4 1/2 W, 2 S to Tank Batt,
1 1/2 E, S between fences to the second gate, E along fence

Database File: britohd.db
Dataset Pathname: dil/britstk
Presentation Format: cdl
Dataset Creation: Wed Feb 27 13:25:04 2013
Charted by: Depth in Feet scaled 1:600

0	Gamma Ray (GAPI)	150
6	Caliper (in)	16

30	Compensated Density (pu)		-10
2	Bulk Density (g/cc)		3
15000	Line Tension (lb)		0
2.625	DGA (g/cc)	3.425	-0.25
	Correction (g/cc)		0.25

LSPD
(ft/min)















