Company	CHEVRON U.S.A. Inc.
Well	CHEVRON OKD 6369
Field	CHEVRON OKD FIELD, SAN JUAN
County	SAN JUAN
State	NEW MEXICO
Other Services	
Permanent Datum	GROUND LEVEL
Elevation	5,744 ft
Log Measured From	KELLY BUSHING
Drilling Measured From	KELLY BUSHING
Elevation	5,756 ft
Elevation	5,744 ft
Elevation	5,744 ft
Date	10-Jun-2015
Run Number	ONE
Depth Driller	1,500 ft
Depth Logger	1,500 ft
Bottom Logged Interval	1,500 ft
Top Logged Interval	SURFACE
Casing Driller	8.625 in @ 1,500 ft
Casing Logger	1,500 ft
Bit Size	7.875 in
Type Fluid in Hole	LSND
Density	9.2 lbm/gal
Viscosity	45 s
PH	9.5
Fluid Loss	5.6 cm3
Source of Sample	FLOWLINE
Rm @ Meas Temp	0.95 @ 70 degF
Rmf @ Meas Temp	0.75 @ 70 degF
Rmc @ Meas Temp	1.2 @ 70 degF
Source of Rmf / Rmc	MEASURED / MEASURED
Rm @ BHT	0.5 @ 150 degF
Time Since Circulation	4 hours
Max Rec Temp	150 degF
Equipment / Location	3 / FARMINGTON
Recorded By	JOHNSON
Witnessed By	CREW

DUAL INDUCTION LATEROLOG

Run	Bit Size	Depth Driller	Depth Logger	Bottom Logged Interval	Top Logged Interval	Casing Driller	Casing Logger
ONE	7.875 in	1,500 ft	1,500 ft	1,500 ft	SURFACE	8.625 in @ 1,500 ft	1,500 ft

Run	Density	Viscosity	PH	Fluid Loss	Source of Sample	Rm @ Meas Temp	Rmf @ Meas Temp	Rmc @ Meas Temp	Source of Rmf / Rmc	Rm @ BHT	Time Since Circulation	Max Rec Temp	Equipment / Location	Recorded By	Witnessed By
ONE	9.2 lbm/gal	45 s	9.5	5.6 cm3	FLOWLINE	0.95 @ 70 degF	0.75 @ 70 degF	1.2 @ 70 degF	MEASURED / MEASURED	0.5 @ 150 degF	4 hours	150 degF	3 / FARMINGTON	JOHNSON	CREW

Run	Service Order	Depth Driller	Depth Logger	Bottom Logged Interval	Top Logged Interval	Casing Driller	Casing Logger	Bit Size
ONE	DIL	1,500 ft	1,500 ft	1,500 ft	SURFACE	8.625 in @ 1,500 ft	1,500 ft	7.875 in

Run	Density	Viscosity	PH	Fluid Loss	Source of Sample	Rm @ Meas Temp	Rmf @ Meas Temp	Rmc @ Meas Temp	Source of Rmf / Rmc	Rm @ BHT	Time Since Circulation	Max Rec Temp	Equipment / Location	Recorded By	Witnessed By
ONE	9.2 lbm/gal	45 s	9.5	5.6 cm3	FLOWLINE	0.95 @ 70 degF	0.75 @ 70 degF	1.2 @ 70 degF	MEASURED / MEASURED	0.5 @ 150 degF	4 hours	150 degF	3 / FARMINGTON	JOHNSON	CREW

All logs and data are approximations only and are not intended to be a guarantee of what should be encountered in your well and are not to be construed as a representation, and no warranty of any kind is made by Schlumberger as to the accuracy of any log, data, or interpretation, and Schlumberger shall not be liable for any loss or damage resulting from the use of any log, data, or interpretation, whether such error is caused by negligence or not, and Schlumberger shall not be liable for any consequential damages.

Customer(s):

OXID 6369

Township: 31N

Range: 13W

CREW: JOHNSON

2" DIL SECTION

Company File: 1st EDIT-Unichem techlib db
Dataset Pathname: 2in.dlis.3
Presentation Format: DIL
Dataset Creation: Wed Jun 10 08:45:20 Cst Utc 2015
Charted by Depth in Feet scaled 1:240

GR (GAPI)	150
0	
SP (mV)	200

RLA1 (Ohm.m)	50
RLA2 (Ohm.m)	50
RLA3 (Ohm.m)	50
1000	CILD (mmho/m) 0
1000	CILM (mmho/m) 0

RLA4 (Ohm.m)	50
RLA5 (Ohm.m)	50
RLA6 (Ohm.m)	50
1000	CILD (mmho/m) 0
1000	CILM (mmho/m) 0

5" DIL SECTION

Company File: 1st EDIT-Unichem techlib db
Dataset Pathname: 5in.dlis.3
Presentation Format: DIL
Dataset Creation: Wed Jun 10 08:45:20 Cst Utc 2015
Charted by Depth in Feet scaled 1:240

GR (GAPI)	150
0	
SP (mV)	200

0.2	Deep Resistivity (Ohm.m)	2000
0.2	Medium Resistivity (Ohm.m)	2000
0.2	Shallow Resistivity (Ohm.m)	2000

0.2	Deep Resistivity (Ohm.m)	2000
0.2	Medium Resistivity (Ohm.m)	2000
0.2	Shallow Resistivity (Ohm.m)	2000

Service	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			Cablehead	1.42	3.65	80.00
CILD SP CILM RLA1	72.92 72.92 7.83 1.67		DIL-SGNR-CAB Telemetry Cartridge	21.58	4.50	345.00

Dataset Pathname: 1st EDIT-Unichem techlib db Techlib/DIL.Data.1
Presentation Format: DIL
Type Weight: 80.00 lb
Type Length: 41.00 ft