NABORS
COMPLETION & PRODUCTION SERVICES CO.

DUAL INDUCTION LOG

Company SHELBY RESOURCES, LLC.
Well EAKIN #7-7
Field
County PAWNEE State KANSAS

Location: API #: 15-145-21715
1906' FNL & 1980' FEL
SEC 7 TWP 22S RGE 16W

Permanent Datum GROUND LEVEL Elevation 2006
Log Measured From KELLY BUSHING 13' A.G.L.
Drilling Measured From KELLY BUSHING

Other Services
CDL/CNL
SONIC/MEL

Elevation
K.B. 2019
D.F.
G.L. 2006

Company SHELBY RESOURCES, LLC.
Well EAKIN #7-7
Field
County PAWNEE State KANSAS
Location: 1906' FNL & 1980' FEL SEC 7 TWP 22S RGE 16W

Date	6-10-13		
Run Number	ONE		
Depth Driller	3985		
Depth Logger	3986		
Bottom Logged Interval	3984		
Top Log Interval	00		
Casing Driller	1037		
Casing Logger	1032		
Bit Size	7.875		
Type Fluid in Hole	CHEMICAL MUD		
Density / Viscosity	8.8 / 49		
pH / Fluid Loss	11.0 / 8.0		
Source of Sample	FLOWLINE		
Rm @ Meas. Temp	0.75 @ 88F		
Rmf @ Meas. Temp	0.56 @ 88F		
Rmc @ Meas. Temp	0.90 @ 88F		
Source of Rmf / Rmc	MEASURED		
Rm @ BHT	.570 @ 115F		
Time Circulation Stopped	2 HOURS		
Time Logger on Bottom	6:30 A.M.		
Maximum Recorded Temperature	115F		
Equipment Number	860		
Location	HAYS, KS.		
Recorded By	RUPP		
Witnessed By	JEREMY SCHWARTZ	KEITH REAVIS	

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

NABORS COMPLETION & PRODUCTION SERVICES
785-628-6395
THANK YOU FOR YOUR BUSINESS
DIRECTIONS: LARNED S TO K-56, S OVER BRIDGE, S INTO.


NABORS
COMPLETION & PRODUCTION


MAIN SECTION


SERVICES CO.


Database File: 010190ddn.db
Dataset Pathname: pass3.1A
Presentation Format: _dil2
Dataset Creation: Fri May 10 08:07:30 2013 by Calc Open-Cased 090629
Charted by: Depth in Feet scaled 1:600


0	Gamma Ray (GAPI)	150
0	RLL3 (Ohm-m)	50
0	Deep Induction (Ohm-m)	50
1000	CILD (mmho/m)	0
50	RILD X10 (Ohm-m)	500
50	RLL3 X10 (Ohm-m)	500






450
500
550
600
650
700
750
800
850
900
950



1000
1050
1100
1150
1200
1250
1300
1350
1400
1450
1500


1550
1600
1650
1700
1750
1800
1850
1900
1950
2000
2050


2100
2150
2200
2250
2300
2350
2400
2450
2500
2550
2600


2650
2700
2750
2800
2850
2900
2950
3000
3050
3100
3150


3200
3250
3300
3350
3400
3450
3500
3550
3600
3650
3700




NABORS
COMPLETION & PRODUCTION SERVICES CO.


MAIN SECTION


Database File: 010190ddn.db
Dataset Pathname: pass3.1A
Presentation Format: _dil
Dataset Creation: Fri May 10 08:07:30 2013 by Calc Open-Cased 090629
Charted by: Depth in Feet scaled 1:240


0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	RxoRt	50
0	MINMK	20


0.2	RLL3 (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000




3350
3400
3450
3500


3550
3600
3650
3700
3750


3800
MINMK
3850
RxoRt
3900
FR GR
3950



0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	RxoRt	50
0	MINMK	20

0.2	RLL3 (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000


NABORS
COMPLETION & PRODUCTION SERVICES CO.


REPEAT SECTION

Database File: 010190ddn.db
Dataset Pathname: pass2.1A
Presentation Format: _dil
Dataset Creation: Fri May 10 06:52:22 2013 by Calc Open-Cased 090629
Charted by: Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	RxoRt	50
0	MINMK	20

0.2	RLL3 (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000





Calibration Report

Database File: 010190ddn.db
Dataset Pathname: pass3.1A
Dataset Creation: Fri May 10 08:07:30 2013 by Calc Open-Cased 090629

Dual Induction Calibration Report

Serial-Model:	PROBE7-DILG
Surface Cal Performed:	Fri May 10 07:15:47 2013
Downhole Cal Performed:	Sat Jan 19 19:51:38 2013
After Survey Verification Performed:	Sat Jan 19 19:51:38 2013

Surface Calibration

	Readings			References			Results	
Loop:	Air	Loop		Air	Loop		m	b
Deep	0.793	0.790	V	0.000	400.000	mmho/m	620.000	5.000
Medium	0.992	1.002	V	0.000	464.000	mmho/m	660.000	-42.000
Internal:	Zero	Cal		Zero	Cal		m	b
Deep	0.041	0.642	V	0.000	400.000	mmho/m	664.874	-27.011

Medium	0.035	0.802	V	0.000	464.000	mmho/m	604.936	-21.367

Downhole Calibration

	Readings			References			Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	135384.000	27094.500	mmho/m	135400.000	27082.400	mmho/m	1.000	-19.259
Medium	-47330.100	-9381.740	mmho/m	-47327.100	-9389.280	mmho/m	1.000	-10.154
LL3		7.322	V		1400.000	Ohm-m		
		0.038	V		20.000	Ohm-m		
		-7.273	V		4000.000	mmho-m		

After Survey Verification

	Readings			Targets			Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	135384.000	27094.500	mmho/m	1.000	0.000
Medium	0.000	0.000	mmho/m	-47330.100	-9381.740	mmho/m	1.000	0.000
LL3		0.000	Ohm-m		1400.000	Ohm-m		
		0.000	Ohm-m		20.000	Ohm-m		
		0.000	mmho-m		4000.000	mmho-m		

Compensated Density Calibration Report

Serial-Model: GEAR1-GEARHART
Source / Verifier: 147 / 147
Master Calibration Performed: Fri May 10 06:08:48 2013

Master Calibration

	Density		Far Detector	Near Detector	
Magnesium	1.710	g/cc	1205.77	610.74	cps
Aluminum	2.600	g/cc	271.21	419.72	cps

Spine Angle = 75.89 Density/Spine Ratio = 0.579

	Size		Reading	
Small Ring	7.60	in	3.69	V
Large Ring	14.00	in	6.52	V

Compensated Neutron Calibration Report

Serial Number: NEU_4I
Tool Model: G

CALIBRATION

Detector	Readings		Target		Normalization
Short Space	1.00	cps	1.00	cps	1.0000
Long Space	1.00	cps	1.00	cps	1.0000

Gamma Ray Calibration Report

Serial Number: GR5
Tool Model: OPEN
Performed: Fri May 10 07:15:14 2013

Calibrator Value: 1.0 GAPI

Background Reading: 0.0 cps
Calibrator Reading: 1.0 cps

Sensitivity: 0.9000 GAPI/cps