

HALLIBURTON

BOREHOLE COMPENSATED SONIC ARRAY LOG

COMPANY WELL FIELD/BLOCK COUNTY STATE	BEREXCO LLC CRAIG 1-35 MANNING NW SCOTT KANSAS
Permanent Datum Log measured from Drilling measured from	Sect. 35 Twp. 17S Rge. 31W Elev. 2917.0 ft 12.0 ft above perm. Datum G.L. 2917.0 ft
API No. Location (SHL) 925 FSL & 1674 FEL SW NE SW SE	Other Services: MICROLOG DSNT, SDLT ACRT
COMPANY WELL FIELD/BLOCK COUNTY STATE	BEREXCO LLC CRAIG 1-35 MANNING NW SCOTT KANSAS

Date	11-Feb-14
Run No.	ONE
Depth - Driller	4695.00 ft
Depth - Logger	4695.0 ft
Bottom - Logged Interval	4668.0 ft
Top - Logged Interval	418.0 ft
Casing - Driller	8.625 in @ 420.0 ft
Casing - Logger	418.0 ft @
Bit Size	7.875 in @
Type Fluid in Hole	WATER BASED
Density	9.7 ppg @ 52.00 s/qt
PH	9.00 pH @ 7.0 cp/m
Source of Sample	MUD PIT
Rm @ Meas. Temperature	0.900 ohmm @ 75.00 degF @
Rmf @ Meas. Temperature	0.73 ohmm @ 75.00 degF @
Rmc @ Meas. Temperature	1.210 ohmm @ 75.00 degF @
Source Rmf	MEASURED
Rmc	MEASURED
Rm @ BHT	0.59 ohmm @ 119.0 degF @
Time Since Circulation	5.0 hr
Time on Bottom	11-Feb-14 19:28
Max. Rec. Temperature	119.0 degF @ 4695.0 ft @
Equipment	11230668 LIBERAL
Recorded By	J. BOLLOW
Witnessed By	I. BOSMEIJER

Fold here

Service Ticket No.: 901111896 API Serial No.: 15-171-21024-00-00 PGM Version: WL INSITE R3.8.4 (Build 5)

CHANGE IN MUD TYPE OR ADDITIONAL SAMPLE				RESISTIVITY SCALE CHANGES			
Date	Sample No.			Type Log	Depth	Scale Up Hole	Scale Down Hole
Depth-Driller							
Type Fluid in Hole							
Density	Viscosity						
Ph	Fluid Loss						
Source of Sample				RESISTIVITY EQUIPMENT DATA			
Rm @ Meas. Temp	@	@		Run No.	Tool Type & No.	Pad Type	Tool Pos.
Rmf @ Meas. Temp.	@	@					
Rmc @ Meas. Temp.	@	@					
Source Rmf	Rmc						
Rm @ BHT	@	@					
Rmf @ BHT	@	@					
Rmc @ BHT	@	@					

EQUIPMENT DATA							
GAMMA		ACOUSTIC		DENSITY		NEUTRON	
Run No.	ONE	Run No.	ONE	Run No.		Run No.	
Serial No.	10748374	Serial No.	10747684	Serial No.		Serial No.	
Model No.	GTET	Model No.	BSAT	Model No.		Model No.	
Diameter	3.625"	No. of Cent.	2	Diameter		Diameter	
Detector Model No.	T-102	Spacing	6"	Log Type		Log Type	
Type	SCINT			Source Type		Source Type	
Length	8'	LSA [Y/N]	NO	Serial No.		Serial No.	
Distance to Source	10'	FWDA [Y/N]	NO	Strength		Strength	

LOGGING DATA

GENERAL			GAMMA		ACOUSTIC		DENSITY		NEUTRON		
Run No.	Depth		Speed	Scale		Scale		Matrix	Scale		Matrix
	From	To	ft/min	L	R	L	R		L	R	
ONE	4695	418	REC	0	150	30	-10	47.6			

DIRECTIONAL INFORMATION

Maximum Deviation @ KOP @

Remarks: ANNULAR HOLE VOLUME CALCULATED FOR 5.5-INCH CASING

CHLORIDES REPORTED AT 4,000 PPM

LCM REPORTED AT 1.5 LB/BBL

GTET-DSNT-SDLT-BSAT-ACRT RUN IN COMBINATION

PRE-CALS NOT PERFORMED, DST EQUIPMENT LEFT ON CATWALK

TODAY'S CREW: D. MILLER & E. ZAPIEN


THANK YOU FOR CHOOSING HALLIBURTON ENERGY SERVICES LIBERAL, KS. 620-624-8123


HALLIBURTON DOES NOT GUARANTEE THE ACCURACY OF ANY INTERPRETATION OF THE LOG DATA, CONVERSION OF LOG DATA TO PHYSICAL ROCK PARAMETERS OR RECOMMENDATIONS WHICH MAY BE GIVEN BY HALLIBURTON PERSONNEL OR WHICH APPEAR ON THE LOG OR IN ANY OTHER FORM. ANY USER OF SUCH DATA, INTERPRETATIONS, CONVERSIONS, OR RECOMMENDATIONS AGREES THAT HALLIBURTON IS NOT RESPONSIBLE EXCEPT WHERE DUE TO GROSS NEGLIGENCE OR WILLFUL MISCONDUCT, FOR ANY LOSS, DAMAGES, OR EXPENSES RESULTING FROM THE USE THEREOF.


HALLIBURTON

HALLIBURTON Plot Time: 11-Feb-14 20:54:17
 Plot Range: 400 ft to 4699.33 ft
 Data: CRAIG_1-35\Well Based\CASING\
 Plot File: \BSAT\BSAT_5_MAIN_LIB

5 INCH MAIN LOG










700



800



Acou Porosity

Delta T





Gamma API


Caliper

1200

1300

Accu Porosity

Delta T





1400

1500

Gamma API

Caliper






1600


1700

Gamma API




Alpha P Grossly


Delta II



1800

1900







2000

2100


2200






2300


2400






2500

2600




Acou Perosity


Delta T



2700


2800






2900

3000






3100

3200

3300



Gamma API


Caliper



Acou Porosity


Delta-T






3600


3700






3800

3900



Acoustic Porosity

Delta T





4000

4100

Gamma API

Caliper






4200

4300


4400

Gamma AP




Acoustic Porosity

Delta




4500

4600



Acou Porosity

Delta T




15K	Tens pounds	0	MD 1 : 240 ft		ITTT
6	Caliper inches	16	Tension Pull 10 0	140	Delta-T microsec per ft
0	Gamma API api	150	Tension Pull	30	Acou Porosity percent
SHALE					

HALLIBURTON Plot Time: 11-Feb-14 20:54:28
 Plot Range: 400 ft to 4699.33 ft
 Data: CRAIG_1-35\Well Based\CASING\
 Plot File: \\BSAT\BSAT_5_MAIN_LIB


5 INCH MAIN LOG

HALLIBURTON Plot Time: 11-Feb-14 20:54:28
 Plot Range: 4400 ft to 4698.42 ft
 Data: CRAIG_1-35\Well Based\REPEAT\
 Plot File: \\BSAT\BSAT_5_REP_LIB

REPEAT SECTION






SHALE					
0	Gamma API api	150	30	Acou Porosity percent	-10
6	Caliper inches	16	140	Delta-T microsec per ft	40
15K	Tension pounds	0	MD 1 : 240 ft		ITTT



4500

4600





15K	Tension	0
	pounds	
6	Caliper	16
	inches	
0	Gamma API	150
	api	
SHALE		

MD		ITTT
1 : 240		
ft		
140	Delta-T	40
	microsec per ft	
30	Acou Porosity	-10
	percent	

HALLIBURTON Plot Time: 11-Feb-14 20:54:30
 Plot Range: 4400 ft to 4698.42 ft
 Data: CRAIG_1-35\Well Based\REPEAT\
 Plot File: \\BSAT\BSAT_5_REP_LIB

REPEAT SECTION

HALLIBURTON

TOOL STRING DIAGRAM REPORT

Description	Overbody Description	O.D.	Diagram	Sensors @ Delays	Length	Accumulated Length
CH_HOS-HOSTILE 37.50 lbs		Ø 2.750 in →		← Temperature @ 75.79 ft	3.03 ft	76.82 ft
SP Sub-12345678 60.00 lbs		Ø 3.625 in →		← SP @ 72.01 ft	3.74 ft	73.79 ft
GTET-10748374 165.00 lbs		Ø 3.625 in →		← GammaRay @ 63.99 ft	8.52 ft	70.05 ft

DSNT-10735145
174.00 lbs

DSN Decentralizer-
10755066
6.60 lbs

Ø 5.000 in* →
Ø 3.625 in →

9.69 ft

← DSN Far @ 54.59 ft
← DSN Near @ 53.84 ft

61.53 ft

SDLT-10673803
360.00 lbs

SDLT Pad-10673790
65.00 lbs
Microlog Pad-10673803
8.00 lbs

Ø 4.500 in →
Ø 4.750 in* →
Ø 4.750 in* →

10.81 ft

← Microlog @ 44.03 ft
← SDL Caliper @ 43.84 ft
← SDL @ 43.83 ft

51.84 ft

Flex Joint-00000001
140.00 lbs

Ø 3.625 in →

5.67 ft

41.03 ft

Centralizer 25-00000001
8.00 lbs

Ø 4.000 in* →

35.36 ft

BSAT-10747684
300.00 lbs

Ø 3.625 in →

15.77 ft

← Sonic Receivers @ 26.84 ft

19.58 ft

ACRt Instrument-
10929776
50.00 lbs

Centralizer 25-00000002
8.00 lbs


Ø 4.000 in* →
Ø 3.625 in →

5.03 ft

← Mud Resistivity @ 13.19 ft

← ACRt @ 9.21 ft

14.55 ft



ACRt Sonde-
10929775
200.00 lbs

Ø 3.625 in →

14.22 ft


Bull Nose-00000001
5.00 lbs

Ø 2.750 in →

0.33 ft

0.33 ft

0.00 ft



Mnemonic	Tool Name	Serial Number	Weight (lbs)	Length (ft)	Accumulated Length (ft)	Max.Log. Speed (fpm)
CH_HOS	Hostile Cable Head with Load Cell	HOSTILE	37.50	3.03	73.79	300.00
SP	SP Sub	12345678	60.00	3.74	70.05	300.00
GTET	Gamma Telemetry Tool	10748374	165.00	8.52	61.53	60.00
DSNT	Dual Spaced Neutron	10735145	174.00	9.69	51.84	60.00
DCNT	DSN Decentralizer	10755066	6.60	5.13 *	55.17	300.00
SDLT	Spectral Density Tool	10673803	360.00	10.81	41.03	60.00
MICP	Microlog Pad	10673803	8.00	1.00 *	43.53	60.00
SDLP	Density Insite Pad	10673790	65.00	2.55 *	43.24	60.00
FLEX	Flex Joint	00000001	140.00	5.67	35.36	300.00
BSAT	Borehole Sonic Array Tool	10747684	300.00	15.77	19.58	60.00
OBCEN	Centralizer - 25 in. Overbody	00000001	8.00	2.08 *	32.82	300.00
ACRt	Array Compensated True Resistivity Instrument Section	10929776	50.00	5.03	14.55	300.00
OBCEN	Centralizer - 25 in. Overbody	00000002	8.00	2.08 *	16.30	300.00
ACRt	Array Compensated True Resistivity Sonde Section	10929775	200.00	14.22	0.33	300.00
BLNS	Bull Nose	00000001	5.00	0.33	0.00	300.00
Total			1,587.10	76.82		

* Not included in Total Length and Length Accumulation.

Data: CRAIG_1-35\0001 SP-GTET-DSN-SDL-FLEX-BSAT-ACRT-BN\IDLE

Date: 11-Feb-14 18:15:21

HALLIBURTON

PARAMETERS REPORT

Depth (ft)	Tool Name	Mnemonic	Description	Value	Units
TOP					
	SHARED	BS	Bit Size	7.875	in
	SHARED	UBS	Use Bit Size instead of Caliper for all applications.	No	
	SHARED	MDBS	Mud Base	Water	
	SHARED	MDWT	Borehole Fluid Weight	9.700	ppg
	SHARED	WAGT	Weighting Agent	Natural	
	SHARED	BSAL	Borehole salinity	0.00	ppm
	SHARED	FSAL	Formation Salinity NaCl	0.00	ppm
	SHARED	KPCT	Percent K in Mud by Weight?	0.00	%
	SHARED	RMUD	Mud Resistivity	2.000	ohmm
	SHARED	TRM	Temperature of Mud	75.0	degF
	SHARED	CSD	Logging Interval is Cased?	No	
	SHARED	ICOD	AHV Casing OD	5.500	in
	SHARED	ST	Surface Temperature	75.0	degF
	SHARED	TD	Total Well Depth	4695.00	ft
	SHARED	BHT	Bottom Hole Temperature	200.0	degF
	SHARED	SVTM	Navigation and Survey Master Tool	NONE	
	SHARED	AZTM	High Res Z Accelerometer Master Tool	GTET	

SHARED	TEMM	Temperature Master Tool	NONE	
SHARED	BHSM	Borehole Size Master Tool	NONE	
Rwa / CrossPlot	XPOK	Process Crossplot?	Yes	
Rwa / CrossPlot	FCHO	Select Source of F	Automatic	
Rwa / CrossPlot	AFAC	Archie A factor	0.6200	
Rwa / CrossPlot	MFAC	Archie M factor	2.1500	
Rwa / CrossPlot	RMFR	Rmf Reference	0.10	ohmm
Rwa / CrossPlot	TMFR	Rmf Ref Temp	75.00	degF
Rwa / CrossPlot	RWA	Resistivity of Formation Water	0.05	ohmm
Rwa / CrossPlot	ADP	Use Air Porosity to calculate CrossplotPhi	No	
GTET	GROK	Process Gamma Ray?	Yes	
GTET	GRSO	Gamma Tool Standoff	0.000	in
GTET	GEOK	Process Gamma Ray EVR?	No	
GTET	TPOS	Tool Position for Gamma Ray Tools.	Eccentered	
DSNT	DNOK	Process DSN?	Yes	
DSNT	DEOK	Process DSN EVR?	No	
DSNT	NLIT	Neutron Lithology	Limestone	
DSNT	DNSO	DSN Standoff - 0.25 in (6.35 mm) Recommended	0.250	in
DSNT	DNTP	Temperature Correction Type	None	
DSNT	DPRS	DSN Pressure Correction Type	None	
DSNT	SHCO	View More Correction Options	No	
DSNT	UTVD	Use TVD for Gradient Corrections?	No	
DSNT	LHWT	Logging Horizontal Water Tank?	No	
SDLT	CLOK	Process Caliper Outputs?	Yes	
SDLT Pad	DNOK	Process Density?	Yes	
SDLT Pad	DNOK	Process Density EVR?	No	
SDLT Pad	CB	Logging Calibration Blocks?	No	
SDLT Pad	SPVT	SDLT Pad Temperature Valid?	Yes	
SDLT Pad	DTWN	Disable temperature warning	No	
SDLT Pad	DMA	Formation Density Matrix	2.710	g/cc
SDLT Pad	DFL	Formation Density Fluid	1.000	g/cc
Microlog Pad	MLOK	Process MicroLog Outputs?	Yes	
BSAT	MBOK	Compute BCAS Results?	Yes	
BSAT	FLLO	Frequency Filter Low Pass Value?	5000	Hz
BSAT	FLHI	Frequency Filter High Pass Value?	27000	Hz
BSAT	DTFL	Delta -T Fluid	189.00	uspf
BSAT	DTMT	Delta -T Matrix Type	User define	
BSAT	DTMA	Delta -T Matrix	47.60	uspf
BSAT	DTSH	Delta -T Shale	100.00	uspf
BSAT	SPEQ	Acoustic Porosity Equation	Wyllie	
ACRt Sonde	RTOK	Process ACRt?	Yes	
ACRt Sonde	MNSO	Minimum Tool Standoff	1.50	in
ACRt Sonde	TCS1	Temperature Correction Source	FP Lwr & FP Up	
ACRt Sonde	TPOS	Tool Position	Free Hanging	
ACRt Sonde	RMOP	Rmud Source	Mud Cell	
ACRt Sonde	RMIN	Minimum Resistivity for MAP	0.20	ohmm
ACRt Sonde	RMIN	Maximum Resistivity for MAP	200.00	ohmm
ACRt Sonde	THQY	Threshold Quality	0.50	
ACRt Sonde	MRFX	Fixed mud resistivity	2000	ohmm

BOTTOM

HALLIBURTON**INPUTS, DELAYS AND FILTERS TABLE**

Mnemonic	Input Description	Delay (ft)	Filter Type	Filter Length (ft)
Depth Panel				
TENS	Tension	0.00	NO	
CH_HOS				
DHTN	Downhole Tension	0.00	BLK	0.000
SP Sub				
PLTC	Plot Control Mask	72.01	NO	
SP	Spontaneous Potential	72.01	BLK	1.250
SPR	Raw Spontaneous Potential	72.01	NO	
SPO	Spontaneous Potential Offset	72.01	NO	
GTET				
TPUL	Tension Pull	63.99	NO	
GR	Natural Gamma Ray API	63.99	TRI	1.750
GRU	Unfiltered Natural Gamma Ray API	63.99	NO	
EGR	Natural Gamma Ray API with Enhanced Vertical Resolution	63.99	W	1.416 , 0.750
ACCZ	Accelerometer Z	0.00	BLK	0.083
DEVI	Inclination	0.00	NO	
DSNT				
TPUL	Tension Pull	53.74	NO	
RNDS	Near Detector Telemetry Counts	53.84	BLK	1.417
RFDS	Far Detector Telemetry Counts	54.59	TRI	0.583
DNTT	DSN Tool Temperature	53.84	NO	
DSNS	DSN Tool Status	53.74	NO	
ERNR	Near Detector Telemetry Counts EVR	53.84	BLK	0.000
ERFD	Far Detector Telemetry Counts EVR	54.59	BLK	0.000
ENTM	DSN Tool Temperature EVR	53.84	NO	
SDLT				
TPUL	Tension Pull	43.84	NO	
PCAL	Pad Caliper	43.84	TRI	0.250
ACAL	Arm Caliper	43.84	TRI	0.250
BSAT				
TPUL	Tension Pull	26.84	NO	
STAT	Status	26.84	NO	
DLYT	Delay Time	26.84	NO	
SI	Sample Interval	26.84	NO	
TXRX	Raw Telemetry 10 Receivers	26.84	NO	
FRMC	Tool Frame Count	26.84	NO	
GMOD	Gain processing mode	19.58	NO	
ACRt Sonde				
TPUL	Tension Pull	2.73	NO	
F1R1	ACRT 12KHz - 80in R value	8.98	BLK	0.000
F1X1	ACRT 12KHz - 80in X value	8.98	BLK	0.000
F1R2	ACRT 12KHz - 80in R value	8.98	BLK	0.000
F1X2	ACRT 12KHz - 80in X value	8.98	BLK	0.000

F1R2	ACRT 12KHz - 50in R value	6.48	BLK	0.000
F1X2	ACRT 12KHz - 50in X value	6.48	BLK	0.000
F1R3	ACRT 12KHz - 29in R value	4.98	BLK	0.000
F1X3	ACRT 12KHz - 29in X value	4.98	BLK	0.000
F1R4	ACRT 12KHz - 17in R value	3.98	BLK	0.000
F1X4	ACRT 12KHz - 17in X value	3.98	BLK	0.000
F1R5	ACRT 12KHz - 10in R value	3.48	BLK	0.000
F1X5	ACRT 12KHz - 10in X value	3.48	BLK	0.000
F1R6	ACRT 12KHz - 6in R value	3.23	BLK	0.000
F1X6	ACRT 12KHz - 6in X value	3.23	BLK	0.000
F2R1	ACRT 36KHz - 80in R value	8.98	BLK	0.000
F2X1	ACRT 36KHz - 80in X value	8.98	BLK	0.000
F2R2	ACRT 36KHz - 50in R value	6.48	BLK	0.000
F2X2	ACRT 36KHz - 50in X value	6.48	BLK	0.000
F2R3	ACRT 36KHz - 29in R value	4.98	BLK	0.000
F2X3	ACRT 36KHz - 29in X value	4.98	BLK	0.000
F2R4	ACRT 36KHz - 17in R value	3.98	BLK	0.000
F2X4	ACRT 36KHz - 17in X value	3.98	BLK	0.000
F2R5	ACRT 36KHz - 10in R value	3.48	BLK	0.000
F2X5	ACRT 36KHz - 10in X value	3.48	BLK	0.000
F2R6	ACRT 36KHz - 6in R value	3.23	BLK	0.000
F2X6	ACRT 36KHz - 6in X value	3.23	BLK	0.000
F3R1	ACRT 72KHz - 80in R value	8.98	BLK	0.000
F3X1	ACRT 72KHz - 80in X value	8.98	BLK	0.000
F3R2	ACRT 72KHz - 50in R value	6.48	BLK	0.000
F3X2	ACRT 72KHz - 50in X value	6.48	BLK	0.000
F3R3	ACRT 72KHz - 29in R value	4.98	BLK	0.000
F3X3	ACRT 72KHz - 29in X value	4.98	BLK	0.000
F3R4	ACRT 72KHz - 17in R value	3.98	BLK	0.000
F3X4	ACRT 72KHz - 17in X value	3.98	BLK	0.000
F3R5	ACRT 72KHz - 10in R value	3.48	BLK	0.000
F3X5	ACRT 72KHz - 10in X value	3.48	BLK	0.000
F3R6	ACRT 72KHz - 6in R value	3.23	BLK	0.000
F3X6	ACRT 72KHz - 6in X value	3.23	BLK	0.000
RMUD	Mud Resistivity	12.52	BLK	0.000
F1RT	Transmitter Current Raw 12K X Receiver	2.73	BLK	0.000
F1XT	Transmitter Reference 12 KHz Imaginary Signal	2.73	BLK	0.000
F2RT	Transmitter Reference 36 KHz Real Signal	2.73	BLK	0.000
F2XT	Transmitter Reference 36 KHz Imaginary Signal	2.73	BLK	0.000
F3RT	Transmitter Reference 72 KHz Real Signal	2.73	BLK	0.000
F3XT	Transmitter Reference 72 KHz Imaginary Signal	2.73	BLK	0.000
TFPU	Upper Feedpipe Temperature Calculated	2.73	BLK	0.000
TFPL	Lower Feedpipe Temperature Calculated	2.73	BLK	0.000
ITMP	Instrument Temperature	2.73	BLK	0.000
TCVA	Temperature Correction Values Loop Off	2.73	NO	
TIDV	Instrument Temperature Derivative	2.73	NO	
TUDV	Upper Temperature Derivative	2.73	NO	
TLDV	Lower Temperature Derivative	2.73	NO	
TRBD	Receiver Board Temperature	2.73	NO	
SDLT Pad				
TPUL	Tension Pull	43.83	NO	
NAB	Near Above	43.66	BLK	0.920
NHI	Near Cesium High	43.66	BLK	0.920
NLO	Near Cesium Low	43.66	BLK	0.920
NVA	Near Valley	43.66	BLK	0.920

NBA	Near Barite	43.66	BLK	0.920
NDE	Near Density	43.66	BLK	0.920
NPK	Near Peak	43.66	BLK	0.920
NLI	Near Lithology	43.66	BLK	0.920
NBAU	Near Barite Unfiltered	43.66	BLK	0.250
NLIU	Near Lithology Unfiltered	43.66	BLK	0.250
FAB	Far Above	44.01	BLK	0.250
FHI	Far Cesium High	44.01	BLK	0.250
FLO	Far Cesium Low	44.01	BLK	0.250
FVA	Far Valley	44.01	BLK	0.250
FBA	Far Barite	44.01	BLK	0.250
FDE	Far Density	44.01	BLK	0.250
FPK	Far Peak	44.01	BLK	0.250
FLI	Far Lithology	44.01	BLK	0.250
PTMP	Pad Temperature	43.84	BLK	0.920
NHV	Near Detector High Voltage	43.24	NO	
FHV	Far Detector High Voltage	43.24	NO	
ITMP	Instrument Temperature	43.24	NO	
DDHV	Detector High Voltage	43.24	NO	

Microlog Pad

TPUL	Tension Pull	44.03	NO	
MINV	Microlog Lateral	44.03	BLK	0.750
MNOR	Microlog Normal	44.03	BLK	0.750

Data: CRAIG_1-35\0001 SP-GTET-DSN-SDL-FLEX-BSAT-ACRT-BNIDLE

Date: 11-Feb-14 18:18:11

COMPANY	BEREXCO LLC		
WELL	CRAIG 1-35		
FIELD	MANNING NW		
COUNTY	SCOTT	STATE	KANSAS

HALLIBURTON

**BOREHOLE COMPENSATED
SONIC ARRAY
LOG**