

**NABORS****COMPLETION
& PRODUCTION
SERVICES CO.****COMPENSATED
DENSITY / NEUTRON
LOG**

Company	BLACK DIAMOND OIL, INC.		
Well	BELDEN UNIT #1		
Field	HANSEN ESTATE NW		
County	NORTON	State	KANSAS
Company	BLACK DIAMOND OIL, INC.		
Well	BELDEN UNIT #1		
Field	HANSEN ESTATE NW		
County	NORTON	State	KANSAS
Location:	API # : 15-137-20682-0000		Other Services
	330' FNL & 2640' FEL		DIL/MEL
	C - N/2 - N/2 - N/2		
	SEC 28 TWP 4S RGE 22W		
Permanent Datum	GROUND LEVEL	Elevation	2236
Log Measured From	KELLY BUSHING 5' A.G.L.		
Drilling Measured From	KELLY BUSHING	Elevation	K.B. 2241 D.F. 2239 G.L. 2236
Date	2/19/14		
Run Number	ONE		
Depth Driller	3665		
Depth Logger	3668		
Bottom Logged Interval	3644		
Top Log Interval	3000		
Casing Driller	8 5/8"@208'		
Casing Logger	208		
Bit Size	7 7/8"		
Type Fluid in Hole	CHEMICAL MUD	CHLORIDES 750 PPM	
Density / Viscosity	9.3/52		
pH / Fluid Loss	10.0/6.8		
Source of Sample	FLOWLINE		
Rim @ Meas. Temp	1.50@80F		
Rmf @ Meas. Temp	1.13@80F		
Rmc @ Meas. Temp	1.80@80F		
Source of Rmf / Rmc	MEASUREMENT		
Rim @ BHT	1.06@113F		
Time Circulation Stopped	2 HOURS		
Time Logger on Bottom	12:30 A.M.		
Maximum Recorded Temperature	113F		
Equipment Number	4854		
Location	HAYS, KANSAS		
Recorded By	JEFF LUEBBERS		
Witnessed By	HERB DEINES		

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

THANK YOU FOR USING "NABORS" HAYS, KANSAS (785) 628-6395
DIRECTIONS

EDMOND, KS. 1 1/2E. ON HWY 9 TO "RD. E5", 2 1/2N. TO TANK BATTERY, 1/2W. ON TRAIL, 1/2 N.
THROUGH GATE, TAKE RIGHT FORK N, & W.

Database File:

22255ddn.db

Dataset Pathname:

pass3.6

Presentation Format:

den_neu


Dataset Creation:


Thu Feb 20 01:59:00 2014

Charted by:

Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150	ABHV	30	COMPENSATED DENSITY (pu)	-10
6	CALIPER (in)	16	10 (ft3)	0 30	COMPENSATED NEUTRON (pu)	-10
0	MINMK	20	TBHV		-0.25 CORRECTION (g/cc)	0.25
			0 (ft3)	10		







3200


3250

3300

3350









REPEAT SECTION

Database File: 22255ddn.db
 Dataset Pathname: pass2.14
 Presentation Format: den_neu
 Dataset Creation: Thu Feb 20 01:02:08 2014
 Charted by: Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150	ABHV	30	COMPENSATED DENSITY (pu)	-10
6	CALIPER (in)	16	10 (ft3)	0 30	COMPENSATED NEUTRON (pu)	-10
0	MINMK	20	TBHV		-0.25 CORRECTION (g/cc)	0.25
			0 (ft3)	10		





Calibration Report

Database File: 22255ddn.db
Dataset Pathname: pass3.6
Dataset Creation: Thu Feb 20 01:59:00 2014

Dual Induction Calibration Report

Serial-Model:	PROBE9-DILG
Surface Cal Performed:	Thu Feb 20 00:34:41 2014
Downhole Cal Performed:	Mon Jul 28 12:02:56 2008
After Survey Verification Performed:	Mon Jul 28 12:02:56 2008

Surface Calibration								
Readings			References				Results	
Loop:	Air	Loop		Air	Loop		m	b
Deep	-0.014	0.629	V	0.000	400.000	mmho/m	650.000	50.000
Medium	0.039	0.728	V	0.000	464.000	mmho/m	660.000	-23.000
Internal:	Zero	Cal		Zero	Cal		m	b
Deep	0.011	0.610	V	0.000	400.000	mmho/m	667.135	-7.256
Medium	0.005	0.712	V	0.000	464.000	mmho/m	655.677	-3.102

Downhole Calibration								
Readings			References				Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	14.508	388.384	mmho/m	1.000	0.000
Medium	0.000	0.000	mmho/m	166.367	504.400	mmho/m	1.000	0.000
LL3		7.500	V		1400.000	Ohm-m		
		0.000	V		20.000	Ohm-m		
		-7.200	V		4000.000	mmho-m		

After Survey Verification								
Readings			Targets				Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
Medium	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
LL3		1.000	Ohm-m		1.000	Ohm-m		
		0.000	Ohm-m		0.000	Ohm-m		
		1.000	mmho-m		1.000	mmho-m		

Litho Density Calibration Report								
Serial: 004N				Model: PRB				

Master Calibration				Performed Mon Jun 03 09:36:56 2013				
	Background	Magnesium		Aluminum		Sandstone		
Window 1	1417.6	10391.4		3464.6		11537.5		cps
Window 2	1295.0	8959.7		3050.1		9816.4		cps
Window 3	1105.1	5464.2		2051.0		5838.8		cps
Window 4	315.0	317.7		312.9		319.8		cps
Long Space	0.0	7664.6		1755.0		8521.3		cps
Short Space	1.8	1582.4		1040.8		1699.4		cps
Rho		1.7100		2.5900		1.3800		g/cc
Pe		0.0000		2.5700		1.5500		
Rib Angle	: 44.1	Rib Slope	: 0.970	Density/Spine Ratio			: 0.574	
Spine Angle	: 74.1	Spine Slope	: 3.519	Spine Intercept			: -17.0	

Before Survey Verification				Performed Wed Dec 31 18:00:00 1969				
Window 1	0.0	0.0		0.0		0.0		cps
Window 2	0.0	0.0		0.0		0.0		cps
Window 3	0.0	0.0		0.0		0.0		cps
Window 4	0.0	0.0		0.0		0.0		cps
Long Space	0.0	0.0		0.0		0.0		cps
Short Space	0.0	0.0		0.0		0.0		cps
Measured Rho		0.0000		0.0000		0.0000		g/cc
Measured Correction		0.0000		0.0000		0.0000		g/cc
Measured Pe				0.0000		0.0000		

After Survey Verification

Performed Wed Dec 31 18:00:00 1969

Window 1	0.0	0.0	0.0	0.0	cps
Window 2	0.0	0.0	0.0	0.0	cps
Window 3	0.0	0.0	0.0	0.0	cps
Window 4	0.0	0.0	0.0	0.0	cps
Long Space	0.0	0.0	0.0	0.0	cps
Short Space	0.0	0.0	0.0	0.0	cps
Measured Rho		0.0000	0.0000	0.0000	g/cc
Measured Correction		0.0000	0.0000	0.0000	g/cc
Measured Pe			0.0000	0.0000	

Compensated Neutron Calibration Report

Serial Number: 070808
Tool Model: Probe

PRE-SURVEY VERIFICATION

Detector	Readings	Measured	Target
Short Space	cps		
Long Space	cps	pu	pu

POST-SURVEY VERIFICATION

Detector	Readings	Measured	Target
Short Space	cps		
Long Space	cps	pu	pu

Gamma Ray Calibration Report

Serial Number: 070558
Tool Model: OPEN_GR
Performed: Wed Feb 19 23:54:43 2014

Calibrator Value: 1.0 GAPI

Background Reading: 0.0 cps
Calibrator Reading: 1.0 cps

Sensitivity: 0.2200 GAPI/cps