




ARRAY COMPENSATED
TRUE RESISTIVITY
LOG


----- Fold here -----



LOGGING DATA


GENERAL			GAMMA		ACOUSTIC			DENSITY			NEUTRON			
Run	Depth		Speed	Scale		Scale		Matrix	Scale		Matrix	Scale		Matrix
No.	From	To	ft/min	L	R	L	R		L	R		L	R	
ONE	5578	265	REC	0	150									
DIRECTIONAL INFORMATION														
Maximum Deviation @								KOP @						
Remarks: ANNULAR HOLE VOLUME CALCULATED FOR 5.5 INCH CASING														
CHLORIDES REPORTED AT 4000 MG/L														
LCM REPORTED AT 6 PPB														
TODAY'S CREW V. JAIME K. KING														
THANK YOU FOR CHOOSING HALLIBURTON ENERGY SERVICES LIBERAL, KANSAS 620-624-8123														
HALLIBURTON DOES NOT GUARANTEE THE ACCURACY OF ANY INTERPRETATION OF THE LOG DATA, CONVERSION OF LOG DATA TO PHYSICAL ROCK PARAMETERS OR RECOMMENDATIONS WHICH MAY BE GIVEN BY HALLIBURTON PERSONNEL OR WHICH APPEAR ON THE LOG OR IN ANY OTHER FORM. ANY USER OF SUCH DATA, INTERPRETATIONS, CONVERSIONS, OR RECOMMENDATIONS AGREES THAT HALLIBURTON IS NOT RESPONSIBLE EXCEPT WHERE DUE TO GROSS NEGLIGENCE OR WILLFUL MISCONDUCT, FOR ANY LOSS, DAMAGES, OR EXPENSES RESULTING FROM THE USE THEREOF.														
HALLIBURTON														






















3800


3900

4000

4100

4200





4300



4400


4500

4600

4700

4800






4900


5000

5100

5200

5300





0	Gamma API	150	MD 1 : 600 ft	0	20in Resistivity 2ft Res	50	
	api				ohm-metre		
	SP			0	90in Resistivity 2ft Res	50	
	-]20[+				ohm-metre		
				1000	90in Conductivity 2ft Res	0	
					mmho per metre		

HALLIBURTON


Plot Time: 19-Feb-14 21:45:20
Plot Range: 255 ft to 5583 ft
Data: SCHOOL_TST_22-5\Well Based\DAQ-0001-005\
Plot File: \\-LOCAL-\\SCHOOL_TST_22-5\\0001 SP-GTET-DSN-SDL-FLEX-BSAT-ACRT-BNIACRTIACRT_2_lib


2 INCH MAIN LOG


HALLIBURTON

Plot Time: 19-Feb-14 21:45:20
Plot Range: 3598 ft to 5583 ft
Data: SCHOOL_TST_22-5\Well Based\DAQ-0001-005\
Plot File: \\-LOCAL-\\SCHOOL_TST_22-5\\0001 SP-GTET-DSN-SDL-FLEX-BSAT-ACRT-BNIACRTIACRT_5_main_lib

5 INCH MAIN LOG









3800

3900


4000






4100

4200







SP

4300


4400






4500


4600






4700

4800







4900

5000


5100






5200

5300







5400

5500

FRSP





SP -]20[+		MD 1 : 240 ft	10K Tension 0 pounds	
0	Gamma API 150 api		0.2	10in Resistivity 2ft Res 2000 ohmm
SHALE			0.2	20in Resistivity 2ft Res 2000 ohmm
			0.2	30in Resistivity 2ft Res 2000 ohm-metre
			0.2	60in Resistivity 2ft Res 2000 ohmm
			0.2	90in Resistivity 2ft Res 2000 ohmm

HALLIBURTON


Plot Time: 19-Feb-14 21:45:25
Plot Range: 3598 ft to 5583 ft
Data: SCHOOL_TST_22-5\Well Based\DAQ-0001-005\
Plot File: \\LOCAL-ISCHOOL_TST_22-5\0001 SP-GTET-DSN-SDL-FLEX-BSAT-ACRT-BNIACRT\ACRT_5_main_lib


5 INCH MAIN LOG

HALLIBURTON

Plot Time: 19-Feb-14 21:45:25
Plot Range: 5300 ft to 5582.92 ft
Data: SCHOOL_TST_22-5\Well Based\DAQ-0001-004\
Plot File: \\LOCAL-ISCHOOL_TST_22-5\0001 SP-GTET-DSN-SDL-FLEX-BSAT-ACRT-BNIACRT\ACRT_5_repeat_lib


REPEAT SECTION






5400

5500





0	SP -]20[+	MD 1 : 240 ft	0.2	10in Resistivity 2ft Res ohmm	2000	10K	Tension pounds	0
	Gamma API							
	api							
	SHALE							
			0.2	20in Resistivity 2ft Res ohmm	2000			
			0.2	30in Resistivity 2ft Res ohm-metre	2000			
			0.2	60in Resistivity 2ft Res ohmm	2000			
			0.2	90in Resistivity 2ft Res ohmm	2000			

HALLIBURTON


Plot Time: 19-Feb-14 21:45:29
Plot Range: 5300 ft to 5582.92 ft
Data: SCHOOL_TST_22-5\Well Based\DAQ-0001-004\
Plot File: \\-LOCAL-ISCHOOL_TST_22-5\0001 SP-GTET-DSN-SDL-FLEX-BSAT-ACRT-BNIACRT\ACRT_5_repeat_lib


REPEAT SECTION

HALLIBURTON

TOOL STRING DIAGRAM REPORT

Description	Overbody Description	O.D.	Diagram	Sensors @ Delays	Length	Accumulated Length
CH_HOS-HOSTILE 37.50 lbs		Ø 2.750 in →		← Temperature @ 75.79 ft	3.03 ft	76.82 ft
SP Sub-12345678 60.00 lbs		Ø 3.625 in →		← SP @ 72.01 ft	3.74 ft	73.79 ft
GTET-10748374 165.00 lbs		Ø 3.625 in →		← GammaRay @ 63.99 ft	8.52 ft	70.05 ft





Mnemonic	Tool Name	Serial Number	Weight (lbs)	Length (ft)	Accumulated Length (ft)	Max.Log. Speed (fpm)
CH_HOS	Hostile Cable Head with Load Cell	HOSTILE	37.50	3.03	73.79	300.00
SP	SP Sub	12345678	60.00	3.74	70.05	300.00
GTET	Gamma Telemetry Tool	10748374	165.00	8.52	61.53	60.00
DSNT	Dual Spaced Neutron	10735145	174.00	9.69	51.84	60.00
DCNT	DSN Decentralizer	10755066	6.60	5.13	* 55.17	300.00
SDLT	Spectral Density Tool	10673803	360.00	10.81	41.03	60.00
MICP	Microlog Pad	10673803	8.00	1.00	* 43.53	60.00
SDLP	Density Insite Pad	10673790	65.00	2.55	* 43.24	60.00
FLEX	Flex Joint	00000001	140.00	5.67	35.36	300.00
BSAT	Borehole Sonic Array Tool	10747684	300.00	15.77	19.58	60.00
OBCEN	Centralizer - 25 in. Overbody	00000001	8.00	2.08	* 32.82	300.00
ACRt	Array Compensated True Resistivity Instrument Section	10929776	50.00	5.03	14.55	300.00
OBCEN	Centralizer - 25 in. Overbody	00000002	8.00	2.08	* 16.30	300.00
ACRt	Array Compensated True Resistivity Sonde Section	10929775	200.00	14.22	0.33	300.00
BLNS	Bull Nose	00000001	5.00	0.33	0.00	300.00
Total			1,587.10	76.82		
						* Not included in Total Length and Length Accumulation.
Data: SCHOOL_TST_22-5I0001 SP-GTET-DSN-SDL-FLEX-BSAT-ACRT-BN					IDLE	Date: 19-Feb-14 18:01:15

HALLIBURTON

CALIBRATION REPORT

NATURAL GAMMA RAY TOOL SHOP CALIBRATION			
Tool Name:	GTET - 10748374	Reference Calibration Date:	25-Nov-13 16:08:30
Engineer:	SHELDON INGERSOLL	Calibration Date:	03-Feb-14 18:18:39
Software Version:	WL INSITE R3.8.4 (Build 5)	Calibration Version:	1
Calibrator Source S/N: TB-185			
Calibrator API Reference:228.00 api			
Equivalent Calibrator API Reference:232.0 api			
Measurement	Measured	Calibrated	Units
Background	44.9	44.5	api
Background + Calibrator	279.2	276.5	api
Calibrator	234.3	232.0	api
NATURAL GAMMA RAY TOOL FIELD CALIBRATION			
Tool Name:	GTET - 10748374	Reference Calibration Date:	03-Feb-14 18:18:39
Engineer:	J. BOLLOM	Calibration Date:	18-Feb-14 18:13:43
Software Version:	WL INSITE R3.8.4 (Build 5)	Calibration Version:	1
Calibrator Source S/N: TB-185			
Calibrator API Reference:228.00 api			

Field Verification	Shop	Field	Units
Background	44.5	43.7	api
Background + Calibrator	276.5	278.5	api
Calibrator	232.0	234.8	api
Shop	Field	Difference	Tolerance
232.0	234.8	-2.8	+/- 9.00

ARRAY COMPENSATED TRUE RESISTIVITY SHOP CALIBRATION

Tool Name:	ACRt Sonde - 10929775	Reference Calibration Date:	31-Dec-13 11:40:54
Engineer:	THOMAS HYDE	Calibration Date:	19-Feb-14 09:38:10
Software Version:	WL INSITE R3.8.4 (Build 5)	Calibration Version:	1
Host Tool Name:	ACRt Instrument - 10929776		

TYPICAL GAIN RANGE

Subarray	R12KHz			R36KHz			R72KHz		
	Lower	(mmho/m)	Upper	Lower	(mmho/m)	Upper	Lower	(mmho/m)	Upper
A1 (80")	0.95	1.03	1.05	0.95	1.03	1.05	0.95	1.02	1.05
A2 (50")	0.95	1.04	1.05	0.95	1.04	1.05	0.95	1.04	1.05
A3 (29")	0.95	1.01	1.05	0.95	1.01	1.05	0.95	1.00	1.05
A4 (17")	0.95	1.04	1.05	0.95	1.03	1.05	0.95	1.03	1.05
A5 (10")	N/A	N/A	N/A	0.95	1.03	1.05	0.95	1.03	1.05
A6 (6")	N/A	N/A	N/A	0.95	1.01	1.05	0.95	1.01	1.05

TYPICAL SONDE OFFSET RANGE

Subarray	R12KHz			R36KHz			R72KHz		
	Lower	(mmho/m)	Upper	Lower	(mmho/m)	Upper	Lower	(mmho/m)	Upper
A1 (80")	-5	-1.68	2	-6	-4.66	-2	-8	-4.97	-2
A2 (50")	-7	-2.70	0	-7	-4.41	0	-7	-4.62	0
A3 (29")	-27	-15.09	-9	-9	-4.78	-3	-7	-2.91	-1
A4 (17")	-180	-105.60	-60	-45	-33.09	-15	-39	-25.82	-13
A5 (10")	N/A	N/A	N/A	-150	-120.85	-50	-80	-55.79	-10
A6 (6")	N/A	N/A	N/A	175	277.69	525	90	139.05	270

TRANSMITTER CURRENT GAIN

Signal	Lower	R	Upper
12K	0.6	0.83	1.3
36K	1.0	1.16	2.0
72K	1.0	1.45	2.0

R-MUD VERIFICATION

Signal	Lower (ohm-m)	Measured (ohm-m)	Upper (ohm-m)
Mud Cell	0.95	0.99	1.05

PASS/FAIL SUMMARY

GAIN RANGE CHK	PASS
SONDE OFFSET RANGE CHK	PASS
Tx CURRENT GAIN	PASS
Rmud VERIFICATION	PASS

TOOL OK TO LOG

CALIBRATION SUMMARY

Sensor	Shop	Field	Post	Difference	Tolerance	Units
--------	------	-------	------	------------	-----------	-------

Sensor	Shop	Field	Post	Difference	Tolerance	Units
GTET-10748374						
Gamma Ray Calibrator	232.0	234.8	-----	-2.8	+/- 9.00	api
ACRt Sonde-10929775						
Mud Cell	0.99	-----	-----	0.00	-----	ohm-m
Data: SCHOOL_TST_22-5I0001 SP-GTET-DSN-SDL-FLEX-BSAT-ACRT-BNIDLE						
Date: 19-Feb-14 18:19:41						



PARAMETERS REPORT

Depth (ft)	Tool Name	Mnemonic	Description	Value	Units
TOP					
	SHARED	BS	Bit Size	7.875	in
	SHARED	UBS	Use Bit Size instead of Caliper for all applications.	No	
	SHARED	MDBS	Mud Base	Water	
	SHARED	MDWT	Borehole Fluid Weight	9.400	ppg
	SHARED	WAGT	Weighting Agent	Natural	
	SHARED	BSAL	Borehole salinity	0.00	ppm
	SHARED	FSAL	Formation Salinity NaCl	0.00	ppm
	SHARED	KPCT	Percent K in Mud by Weight?	0.00	%
	SHARED	RMUD	Mud Resistivity	2.000	ohmm
	SHARED	TRM	Temperature of Mud	75.0	degF
	SHARED	CSD	Logging Interval is Cased?	No	
	SHARED	ICOD	AHV Casing OD	5.500	in
	SHARED	ST	Surface Temperature	55.0	degF
	SHARED	TD	Total Well Depth	5580.00	ft
	SHARED	BHT	Bottom Hole Temperature	200.0	degF
	SHARED	SVTM	Navigation and Survey Master Tool	NONE	
	SHARED	AZTM	High Res Z Accelerometer Master Tool	GTET	
	SHARED	TEMM	Temperature Master Tool	NONE	
	SHARED	BHSM	Borehole Size Master Tool	NONE	
	Rwa / CrossPlot	XPOK	Process Crossplot?	Yes	
	Rwa / CrossPlot	FCHO	Select Source of F	Automatic	
	Rwa / CrossPlot	AFAC	Archie A factor	0.6200	
	Rwa / CrossPlot	MFAC	Archie M factor	2.1500	
	Rwa / CrossPlot	RMFR	Rmf Reference	0.10	ohmm
	Rwa / CrossPlot	TMFR	Rmf Ref Temp	75.00	degF
	Rwa / CrossPlot	RWA	Resistivity of Formation Water	0.05	ohmm
	Rwa / CrossPlot	ADP	Use Air Porosity to calculate CrossplotPhi	No	
	GTET	GROK	Process Gamma Ray?	Yes	
	GTET	GRSO	Gamma Tool Standoff	0.000	in
	GTET	GEOK	Process Gamma Ray EVR?	No	
	GTET	TPOS	Tool Position for Gamma Ray Tools.	Eccentered	
	DSNT	DNOK	Process DSN?	Yes	
	DSNT	DEOK	Process DSN EVR?	No	
	DSNT	NLIT	Neutron Lithology	Limestone	
	DSNT	DNSO	DSN Standoff - 0.25 in (6.35 mm) Recommended	0.250	in
	DSNT	DNTP	Temperature Correction Type	None	
	DSNT	DPRS	DSN Pressure Correction Type	None	

DSNT	SHCO	View More Correction Options	No	
DSNT	UTVD	Use TVD for Gradient Corrections?	No	
DSNT	LHWT	Logging Horizontal Water Tank?	No	
SDLT	CLOK	Process Caliper Outputs?	Yes	
SDLT Pad	DNOK	Process Density?	Yes	
SDLT Pad	DNOK	Process Density EVR?	No	
SDLT Pad	CB	Logging Calibration Blocks?	No	
SDLT Pad	SPVT	SDLT Pad Temperature Valid?	Yes	
SDLT Pad	DTWN	Disable temperature warning	No	
SDLT Pad	DMA	Formation Density Matrix	2.710	g/cc
SDLT Pad	DFL	Formation Density Fluid	1.000	g/cc
Microlog Pad	MLOK	Process MicroLog Outputs?	Yes	
BSAT	MBOK	Compute BCAS Results?	Yes	
BSAT	FLLO	Frequency Filter Low Pass Value?	5000	Hz
BSAT	FLHI	Frequency Filter High Pass Value?	27000	Hz
BSAT	DTFL	Delta -T Fluid	189.00	uspf
BSAT	DTMT	Delta -T Matrix Type	User define	
BSAT	DTMA	Delta -T Matrix	47.60	uspf
BSAT	DTSH	Delta -T Shale	100.00	uspf
BSAT	SPEQ	Acoustic Porosity Equation	Wylie	
ACRt Sonde	RTOK	Process ACRt?	Yes	
ACRt Sonde	MNSO	Minimum Tool Standoff	1.50	in
ACRt Sonde	TCS1	Temperature Correction Source	FP Lwr & FP Up	
ACRt Sonde	TPOS	Tool Position	Free Hanging	
ACRt Sonde	RMOP	Rmud Source	Mud Cell	
ACRt Sonde	RMIN	Minimum Resistivity for MAP	0.20	ohmm
ACRt Sonde	RMIN	Maximum Resistivity for MAP	200.00	ohmm
ACRt Sonde	THQY	Threshold Quality	0.50	
ACRt Sonde	MRFX	Fixed mud resistivity	2000	ohmm
BOTTOM				
Data: SCHOOL_TST_22-5I0001 SP-GTET-DSN-SDL-FLEX-BSAT-ACRT-BNIDLE				Date: 19-Feb-14 18:20:54

HALLIBURTON INPUTS, DELAYS AND FILTERS TABLE				
Mnemonic	Input Description	Delay (ft)	Filter Type	Filter Length (ft)
Depth Panel				
TENS	Tension	0.00	NO	
CH_HOS				
DHTN	DownholeTension	0.00	BLK	0.000
SP Sub				
PLTC	Plot Control Mask	72.01	NO	
SP	Spontaneous Potential	72.01	BLK	1.250
SPR	Raw Spontaneous Potential	72.01	NO	
SPO	Spontaneous Potential Offset	72.01	NO	
GTET				
TPUL	Tension Pull	63.99	NO	
GR	Natural Gamma Ray API	63.99	TRI	1.750
GRU	Unfiltered Natural Gamma Ray API	63.99	NO	
EGR	Natural Gamma Ray API with Enhanced Vertical Resolution	63.99	W	1.416 - 0.750

Radial Sampling Rate - 1000 Hz Enhanced Vertical Resolution				
ACCZ	Accelerometer Z	0.00	BLK	0.083
DEVI	Inclination	0.00	NO	
DSNT				
TPUL	Tension Pull	53.74	NO	
RNDS	Near Detector Telemetry Counts	53.84	BLK	1.417
RFDS	Far Detector Telemetry Counts	54.59	TRI	0.583
DNTT	DSN Tool Temperature	53.84	NO	
DSNS	DSN Tool Status	53.74	NO	
ERND	Near Detector Telemetry Counts EVR	53.84	BLK	0.000
ERFD	Far Detector Telemetry Counts EVR	54.59	BLK	0.000
ENTM	DSN Tool Temperature EVR	53.84	NO	
SDLT				
TPUL	Tension Pull	43.84	NO	
PCAL	Pad Caliper	43.84	TRI	0.250
ACAL	Arm Caliper	43.84	TRI	0.250
BSAT				
TPUL	Tension Pull	26.84	NO	
STAT	Status	26.84	NO	
DLYT	Delay Time	26.84	NO	
SI	Sample Interval	26.84	NO	
TXRX	Raw Telemetry 10 Receivers	26.84	NO	
FRMC	Tool Frame Count	26.84	NO	
GMOD	Gain processing mode	19.58	NO	
ACRt Sonde				
TPUL	Tension Pull	2.73	NO	
F1R1	ACRT 12KHz - 80in R value	8.98	BLK	0.000
F1X1	ACRT 12KHz - 80in X value	8.98	BLK	0.000
F1R2	ACRT 12KHz - 50in R value	6.48	BLK	0.000
F1X2	ACRT 12KHz - 50in X value	6.48	BLK	0.000
F1R3	ACRT 12KHz - 29in R value	4.98	BLK	0.000
F1X3	ACRT 12KHz - 29in X value	4.98	BLK	0.000
F1R4	ACRT 12KHz - 17in R value	3.98	BLK	0.000
F1X4	ACRT 12KHz - 17in X value	3.98	BLK	0.000
F1R5	ACRT 12KHz - 10in R value	3.48	BLK	0.000
F1X5	ACRT 12KHz - 10in X value	3.48	BLK	0.000
F1R6	ACRT 12KHz - 6in R value	3.23	BLK	0.000
F1X6	ACRT 12KHz - 6in X value	3.23	BLK	0.000
F2R1	ACRT 36KHz - 80in R value	8.98	BLK	0.000
F2X1	ACRT 36KHz - 80in X value	8.98	BLK	0.000
F2R2	ACRT 36KHz - 50in R value	6.48	BLK	0.000
F2X2	ACRT 36KHz - 50in X value	6.48	BLK	0.000
F2R3	ACRT 36KHz - 29in R value	4.98	BLK	0.000
F2X3	ACRT 36KHz - 29in X value	4.98	BLK	0.000
F2R4	ACRT 36KHz - 17in R value	3.98	BLK	0.000
F2X4	ACRT 36KHz - 17in X value	3.98	BLK	0.000
F2R5	ACRT 36KHz - 10in R value	3.48	BLK	0.000
F2X5	ACRT 36KHz - 10in X value	3.48	BLK	0.000
F2R6	ACRT 36KHz - 6in R value	3.23	BLK	0.000
F2X6	ACRT 36KHz - 6in X value	3.23	BLK	0.000
F3R1	ACRT 72KHz - 80in R value	8.98	BLK	0.000
F3X1	ACRT 72KHz - 80in X value	8.98	BLK	0.000
F3R2	ACRT 72KHz - 50in R value	6.48	BLK	0.000

F3R2	ACRT 72KHz - 50in R value	6.48	BLK	0.000
F3X2	ACRT 72KHz - 50in X value	6.48	BLK	0.000
F3R3	ACRT 72KHz - 29in R value	4.98	BLK	0.000
F3X3	ACRT 72KHz - 29in X value	4.98	BLK	0.000
F3R4	ACRT 72KHz - 17in R value	3.98	BLK	0.000
F3X4	ACRT 72KHz - 17in X value	3.98	BLK	0.000
F3R5	ACRT 72KHz - 10in R value	3.48	BLK	0.000
F3X5	ACRT 72KHz - 10in X value	3.48	BLK	0.000
F3R6	ACRT 72KHz - 6in R value	3.23	BLK	0.000
F3X6	ACRT 72KHz - 6in X value	3.23	BLK	0.000
RMUD	Mud Resistivity	12.52	BLK	0.000
F1RT	Transmitter Current Raw 12K X Receiver	2.73	BLK	0.000
F1XT	Transmitter Reference 12 KHz Imaginary Signal	2.73	BLK	0.000
F2RT	Transmitter Reference 36 KHz Real Signal	2.73	BLK	0.000
F2XT	Transmitter Reference 36 KHz Imaginary Signal	2.73	BLK	0.000
F3RT	Transmitter Reference 72 KHz Real Signal	2.73	BLK	0.000
F3XT	Transmitter Reference 72 KHz Imaginary Signal	2.73	BLK	0.000
TFPU	Upper Feedpipe Temperature Calculated	2.73	BLK	0.000
TFPL	Lower Feedpipe Temperature Calculated	2.73	BLK	0.000
ITMP	Instrument Temperature	2.73	BLK	0.000
TCVA	Temperature Correction Values Loop Off	2.73	NO	
TIDV	Instrument Temperature Derivative	2.73	NO	
TUDV	Upper Temperature Derivative	2.73	NO	
TLDV	Lower Temperature Derivative	2.73	NO	
TRBD	Receiver Board Temperature	2.73	NO	
SDLT Pad				
TPUL	Tension Pull	43.83	NO	
NAB	Near Above	43.66	BLK	0.920
NHI	Near Cesium High	43.66	BLK	0.920
NLO	Near Cesium Low	43.66	BLK	0.920
NVA	Near Valley	43.66	BLK	0.920
NBA	Near Barite	43.66	BLK	0.920
NDE	Near Density	43.66	BLK	0.920
NPK	Near Peak	43.66	BLK	0.920
NLI	Near Lithology	43.66	BLK	0.920
NBAU	Near Barite Unfiltered	43.66	BLK	0.250
NLIU	Near Lithology Unfiltered	43.66	BLK	0.250
FAB	Far Above	44.01	BLK	0.250
FHI	Far Cesium High	44.01	BLK	0.250
FLO	Far Cesium Low	44.01	BLK	0.250
FVA	Far Valley	44.01	BLK	0.250
FBA	Far Barite	44.01	BLK	0.250
FDE	Far Density	44.01	BLK	0.250
FPK	Far Peak	44.01	BLK	0.250
FLI	Far Lithology	44.01	BLK	0.250
PTMP	Pad Temperature	43.84	BLK	0.920
NHV	Near Detector High Voltage	43.24	NO	
FHV	Far Detector High Voltage	43.24	NO	
ITMP	Instrument Temperature	43.24	NO	
DDHV	Detector High Voltage	43.24	NO	
Microlog Pad				
TPUL	Tension Pull	44.03	NO	
MINV	Microlog Lateral	44.03	BLK	0.750
MNOR	Microlog Normal	44.03	BLK	0.750

Data: SCHOOL_TST_22-5\0001 SP-GTET-DSN-SDL-FLEX-BSAT-ACRT-BN\IDLE				Date: 19-Feb-14 18:21:03	
COMPANY	HERMAN L. LOEB, LLC.				
WELL	SCHOOL TRUST 22-5				
FIELD	HARDTNER				
COUNTY	BARBER	STATE		KANSAS	
HALLIBURTON			ARRAY COMPENSATED TRUE RESISTIVITY LOG		