



NABORS

**COMPLETION
& PRODUCTION
SERVICES CO.**

**DUAL
INDUCTION
LOG**

Company		SHELBY RESOURCES, LLC.	
Well		NANCY #3-17	
Field		TRAPP	
County		BARTON	
State		KANSAS	
Company		SHELBY RESOURCES, LLC.	
Well		NANCY #3-17	
Field		TRAPP	
County		BARTON	
State		KANSAS	
Location:		API # : 15-009-25969-00-00	
Permanent Datum		2146' FNL & 1701' FWL	
Log Measured From		NE - SW - SE - NW	
Drilling Measured From		SEC 17 TWP 17S RGE 13W	
GROUND LEVEL		Elevation 1965	
KELLY BUSHING 13' A.G.L.		Elevation K.B. 1978	
KELLY BUSHING		D.F. 1976	
		G.L. 1965	
Date	5/9/14		
Run Number	ONE		
Depth Driller	3525		
Depth Logger	3528		
Bottom Logged Interval	3526		
Top Log Interval	2800		
Casing Driller	8 5/8" @ 948		
Casing Logger	942		
Bit Size	7 7/8"		
Type Fluid in Hole	CHEMICAL MUD	CHLORIDES 4,400 PPM	
Density / Viscosity	9.2/68		
pH / Fluid Loss	11.0/7.2		
Source of Sample	FLOWLINE		
Rm @ Meas. Temp	0.60 @ 91F		
Rmt @ Meas. Temp	0.80 @ 91F		
Rmc @ Meas. Temp	0.96 @ 91F		
Source of Rmt / Rmc	MEASUREMENT		
Rm @ BHT	.65 @ 112F		
Time Circulation Stopped	2 HOURS		
Time Logger on Bottom			
Maximum Recorded Temperature	123F		
Equipment Number	4010		
Location	HAYS, KANSAS		
Recorded By	IAN MABB		
Witnessed By	JEREMY SCHWARTZ		

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

THANK YOU FOR USING NABORS, HAYS, KS. (785) 628-6395

DIRECTIONS:

HOSINGTON, KS. - 4 MILES NORTH ON SUSANK RD. - 1 MILE WEST - 1/4 SOUTH - EAST INTO


Database File: 24241ddn.db
 Dataset Pathname: pass5.2
 Presentation Format: _dil2
 Dataset Creation: Sat May 10 00:08:37 2014 by Calc Open-Cased 090629
 Charted by: Depth in Feet scaled 1:600


0	Gamma Ray (GAPI)	150
-100	SP (mV)	100

0	RLL3 (Ohm-m)	50	
0	RILD (Ohm-m)	50	

1000	CILD (mmho/m)		0
50	RILD X10 (Ohm-m)	500	

50	RLL3 X10 (Ohm-m)	500	





500

550

600

650

700

750


800


850

900

950

1000





1050

1100

1150

1200

1250

1300


1350


1400

1450

1500

1550





1600

1650

1700

1750

1800

1850


1900


1950

2000

2050

2100





2150

2200

2250

2300

2350

2400


2450


2500

2550

2600

2650





2700

2750

2800

2850

2900

2950



3000


3050

3100

3150


3200






Database File: 24241ddn.db
 Dataset Pathname: pass5.2
 Presentation Format: _dil
 Dataset Creation: Sat May 10 00:08:37 2014 by Calc Open-Cased 090629
 Charted by: Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150	0.2	SHALLOW GUARD (Ohm-m)	2000
-100	SP (mV)	100	0.2	DEEP INDUCTION (Ohm-m)	2000
-250	Rxo/Rt	50	0.2	MEDIUM INDUCTION (Ohm-m)	2000
0	MINMK	20			







2850

2900

2950

3000






3050


3100

3150

3200

3250







3300

3350

3400


3450






3500

LTD 3528






REPEAT SECTION


Database File: 24241ddn.db
 Dataset Pathname: pass4.1
 Presentation Format: _dil
 Dataset Creation: Fri May 09 23:05:30 2014 by Calc Open-Cased 090629
 Charted by: Depth in Feet scaled 1:240



3200

3250







3300

3350

3400

3450





Calibration Report

Database File: 24241ddn.db
 Dataset Pathname: pass5.2
 Dataset Creation: Sat May 10 00:08:37 2014 by Calc Open-Cased 090629

Dual Induction Calibration Report

Serial-Model: PROBE8-DILG
 Surface Cal Performed: Fri Aug 01 06:33:19 2008
 Downhole Cal Performed: Mon Jul 28 11:08:27 2008
 After Survey Verification Performed: Mon Jul 28 11:08:27 2008

Surface Calibration

Readings				References			Results	
Loop:	Air	Loop		Air	Loop		m	b
Deep	0.015	0.648	V	0.000	400.000	mmho/m	632.616	-9.730
Medium	0.029	0.796	V	0.000	464.000	mmho/m	605.049	-17.680
Internal:	Zero	Cal		Zero	Cal		m	b
Deep	0.017	0.657	V	0.000	400.000	mmho/m	625.153	-10.619
Medium	0.016	0.757	V	0.000	464.000	mmho/m	625.992	-9.739

Downhole Calibration

Readings				References			Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	2.011	405.777	mmho/m	1.000	0.000
Medium	0.000	0.000	mmho/m	7.590	503.393	mmho/m	1.000	0.000
LL3		7.500	V		1500.000	Ohm-m		
		0.000	V		20.000	Ohm-m		
		-7.200	V		3800.000	mmho-m		

After Survey Verification

Readings				Targets			Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
Medium	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
LL3		1.000	Ohm-m		1.000	Ohm-m		

	0.000	Ohm-m		0.000	Ohm-m
	1.000	mmho-m		1.000	mmho-m

Compensated Density Calibration Report

Serial-Model:	GEAR4-GEARHART
Source / Verifier:	143 / 143
Master Calibration Performed:	Wed Sep 18 03:03:09 2013
Before Survey Verification Performed:	
After Survey Verification Performed:	

Master Calibration

	Density		Far Detector	Near Detector	
Magnesium	1.710	g/cc	1075.98	532.39	cps
Aluminum	2.560	g/cc	286.51	422.88	cps
	Spine Angle = 80.13		Density/Spine Ratio = 0.633		
	Size		Reading		
Small Ring	8.00	in	3.21	V	
Large Ring	14.00	in	5.46	V	

Before Survey Verification

	Target		Measured	
		g/cc		g/cc
		g/cc		g/cc
		g/cc		g/cc

After Survey Verification

	Target		Measured	
		g/cc		g/cc
		g/cc		g/cc
		g/cc		g/cc

Compensated Neutron Calibration Report

Serial Number:	6I
Tool Model:	G

CALIBRATION

Detector	Readings	Target	Normalization
Short Space	1.00 cps	1.00 cps	1.0000
Long Space	1.00 cps	1.00 cps	1.0000

PRE-SURVEY VERIFICATION

Detector	Readings	Measured	Target
1) Short Space	cps		
Long Space	cps	pu	pu
2) Short Space	cps		
Long Space	cps	pu	
3) Short Space	cps		
Long Space	cps	pu	

POST-SURVEY VERIFICATION

Detector	Readings	Measured	Target
----------	----------	----------	--------

1)	Short Space Long Space	cps cps	pu	pu
2)	Short Space Long Space	cps cps	pu	pu
3)	Short Space Long Space	cps cps	pu	pu

Gamma Ray Calibration Report

Serial Number:	GR6	
Tool Model:	OPEN	
Performed:	Tue May 06 06:07:07 2014	
Calibrator Value:	150.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	276.0	cps
Sensitivity:	0.8035	GAPI/cps