Perf-Tech Wireline Services

DUAL RECEIVER CEMENT BOND LOG

Company	AMERICAN WARRIOR, INC.
Well	MELVIN No.2-16 UNIT
Field	MANTZ SOUTHEAST
County	NESS
State	KANSAS

Company AMERICAN WARRIOR, INC.
Well MELVIN No.2-16 UNIT
Field MANTZ SOUTHEAST
County NESS State KANSAS

Location: API # : 15-135-25,885-00-00
900' FSL & 2675' FWL
SEC 16 TWP 18S RGE 21W

Other Services

Permanent Datum GROUND LEVEL Elevation 2167
Log Measured From K.B. 8' A.G.L.
Drilling Measured From KELLY BUSHING

Elevation
K.B. 2175
D.F.
G.L. 2167

Date	SEPT 22, 2015
Run Number	ONE
Depth Driller	4265
Depth Logger	4260
Bottom Logged Interval	4259
Top Log Interval	
Open Hole Size	
Type Fluid	WATER
Density / Viscosity	
Max. Recorded Temp.	119F
Estimated Cement Top	
Time Well Ready	
Time Logger on Bottom	
Equipment Number	PT-05
Location	HAYS
Recorded By	BRAD LEIKER
Witnessed By	MR. SCOTT CORSAIR

Borehole Record				Tubing Record			
Run Number	Bit	From	To	Size	Weight	From	To
ONE	12.25	00	220				
TWO	7.875	00	4265				

Casing Record	Size	Wgt/Ft	Top	Bottom
Surface String	8 5/8	23#	00	220
Prot. String				
Production String	5 1/2	15.5#	00	4260
Liner				

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

THANK YOU FOR USING
PERF-TECH WIRELINE SERVICES, INC.
(785) 623-3969

BAZINE KS, EAST TO FF RD,
2 NORTH, 1/2 EAST,
NORTH INTO.

Perf-Tech Wireline Services — MAIN PASS

Database File: sept221505.db
Dataset Pathname: pass3
Presentation Format: 3x5
Dataset Creation: Tue Sep 22 08:26:57 2015 by Log 7.0 B1
Charted by: Depth in Feet scaled 1:240

0 Gamma Ray (GAPI) 150
0 3' AMPLITUDE (mV) 100
600 3'TRAVEL TIME (usec) 100
9 Collar Locator -1
200 Variable Density 5ft 1100

0 Gamma Ray (GAPI) 150
0 3' AMPLITUDE (mV) 100
600 3'TRAVEL TIME (usec) 100
9 Collar Locator -1
200 Variable Density 5ft 1100

Perf-Tech Wireline Services — REPEAT SECTION

Database File: sept221505.db
Dataset Pathname: pass2
Presentation Format: 3x5
Dataset Creation: Tue Sep 22 08:19:34 2015 by Log 7.0 B1
Charted by: Depth in Feet scaled 1:240

0 Gamma Ray (GAPI) 150
0 3' AMPLITUDE (mV) 100
600 3'TRAVEL TIME (usec) 100
9 Collar Locator -1
200 Variable Density 5ft 1100



0 Gamma Ray (GAPI) 150
0 3' AMPLITUDE (mV) 100
600 3'TRAVEL TIME (usec) 100
9 Collar Locator -1
200 Variable Density 5ft 1100