Perf-Tech Wireline Services

Company: MID-CONTINENT RESOURCES, INC.
KUHLMEYN 34
Field: SCHAEN
County: REES
State: KANSAS
Location: 1/4 1/4 1/4 SEC 34 TWP 16S RGE 20W
Permanent Datum: GROUND ELEV.
Log Measured From: KB 10 FT. ABOVE PERM. DATUM
Drilling Measured From: KB
Elev.: K.B. 2379 D.F. G.L.
Date: 10-Feb-10
Run No.: ONE
Depth-Driller: 4400
Depth-Logger: 4399
Bottom Logged Interval: 4399
Top Logged Interval: 3100
Type Fluid in Hole: CHEMICAL
Salinity, PPM Cl: 5,000
Density / Viscosity: 9.2 / 50
pH / Fluid Loss: 10.0 / 6.4
Source of Sample: FLOWLINE
Rm @ Meas. Temp.: .750 @ 90°F
Rmf @ Meas. Temp.: .600 @ 90°F
Rmc @ Meas. Temp.: 1.00 @ 90°F
Source of Rmf / Rmc: CALC / CALC
Rm @ BHT: .400 @ 120°F
Time Since Circulation: 12 HRS
Time on Bottom: 10:30 10-FEB-10
Max. Rec. Temp.: 120°F
Equipment Number: 2373
Location: HAYS, 15-12S-20W
Recorded By: BRIAN
Witnessed By: MR. CRAIG ROBERTS

Company: MID-CONTINENT RESOURCES, INC.
Well: HUMBURG No.1X
Location: NE/4 SW/4 SW/4 SEC. 34-T16S-R20W
County: REES
State: KANSAS
Field Service: DUAL RECEIVER CEMENT BOND LOG

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or wilful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

THANK YOU FOR USING
PERF-TECH WIRELINE SERVICES, INC.
(785) 623-3969

BAZINE, KS, 5 1/2 SOUTH,
WEST INTO.

Perf-Tech Wireline Services

MAIN PASS

Database File: feb101705.db
Dataset Pathname: pass2
Presentation Format: 1
Dataset Creation: Fri Feb 12 08:11:11 2010 by Log 7.0 B1
Charted by: Depth in Feet scaled 1:240

0	Gamma Ray (GAPI)	150	
		0	X AMPLITUDE (mV) 100
000		0	XTRAVEL TIME (usec) 100
		0	Collar Locator -1
			Variable Density 35 110

Top of Cement

Casing Collar Locator

XTRAVEL TIME

X AMPLITUDE

LOGGED TO 4399

Perf-Tech Wireline Services

REPEAT SECTION

Database File: feb101705.db
Dataset Pathname: pass2
Presentation Format: 2
Dataset Creation: Fri Feb 10 12:20:20 2017 by Log 7.0 B1
Charted by: Depth in Feet scaled 1:240

0	Gamma Ray (GAPI)	150	
		0	X AMPLITUDE (mV) 100
000		0	XTRAVEL TIME (usec) 100
		0	Collar Locator -1
			Variable Density 35 110