



DUAL INDUCTION LOG

Company		DIXON OPERATING COMPANY, LLC.	
Well		#1-9 SALEM	
Field		RATTLESNAKE CREEK	
County		STAFFORD	
State		KANSAS	
Location:		APL # : 15-185-24021-0000	
Permanent Datum		GROUND LEVEL	
Log Measured From		KELLY BUSHING 11' A.G.L.	
Drilling Measured From		KELLY BUSHING	
SEC 9		TWP 23S	
		RGE 12W	
Other Services		CDL/CNL/PE	
		MEL	
Elevation		K.B. 1859	
		D.F. 1857	
		G.L. 1848	
Date	7/14/18		
Run Number	ONE		
Depth Driller	3810		
Depth Logger	3812		
Bottom Logged Interval	3810		
Top Log Interval	00		
Casing Driller	8 5/8"@309'		
Casing Logger	309		
Bit Size	7 7/8"		
Type Fluid in Hole	CHEMICAL MUD	CHLORIDES 8,400 PPM	
Density / Viscosity	8.9/68		
pH / Fluid Loss	11.0/8.0		
Source of Sample	FLOWLINE		
Rm @ Meas. Temp	.400@90F		
Rmf @ Meas. Temp	.300@90F		
Rmc @ Meas. Temp	.480@90F		
Source of Rmf / Rmc	MEASUREMENT		
Rm @ BHT	.316@114F		
Time Circulation Stopped	2 HOURS		
Time Logger on Bottom	9:30 A.M.		
Maximum Recorded Temperature	114F		
Equipment Number	922339		
Location	HAYS, KANSAS		
Recorded By	JEFF LUEBBERS		
Witnessed By	BRUCE A. REED		


<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

THANK YOU FOR USING ELI WIRELINE HAYS, KANSAS (785) 628-6395
DIRECTIONS

ST. JOHN, KS., N. TO "RD. NE70", 5E. TO "50TH RD.", 1N., 1/4E. TO TANK BATTERY, S. & E. INTO



MAIN SECTION

Database File: 2661pe.db
Dataset Pathname: pass3.5
Presentation Format: dil2
Dataset Creation: Sat Jul 14 10:44:39 2018
Charted by: Depth in Feet scaled 1:600

0	Gamma Ray (GAPI)	150
-100	SP (mV)	100
0	RWA (Ohm-m)	1


0	RLL3 (Ohm-m)	50
---	--------------	----

0	RILD (Ohm-m)	50
---	--------------	----


1000	CILD (mmho/m)	0
------	---------------	---



50	RILD X10 (Ohm-m)	500
----	------------------	-----


50	RLL3 X10 (Ohm-m)	500
----	------------------	-----





0
50
100
150
200
250
300
350
400








1000
1050
1100
1150
1200
1250
1300
1350
1400
1450
1500





1550

1600

1650

1700

1750

1800


1850


1900

1950

2000

2050





2100

2150

2200

2250

2300

2350


2400


2450

2500

2550

2600





2650

2700

2750

2800

2850

2900


2950


3000

3050

3100

3150





3200

3250

3300

3350

3400

3450



3500



3550

3600

3650

3700







ANHYDRITE



Database File: 2661pe.db
 Dataset Pathname: pass3.6
 Presentation Format: _dil
 Dataset Creation: Sat Jul 14 10:44:56 2018
 Charted by: Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150	0.2	SHALLOW GUARD (Ohm-m)	2000
-100	SP (mV)	100	0.2	DEEP INDUCTION (Ohm-m)	2000
-250	Rxo/Rt	50	0.2	MEDIUM INDUCTION (Ohm-m)	2000
0	MINMK	20			








700



MAIN SECTION


Database File: 2661pe.db
 Dataset Pathname: pass3.5
 Presentation Format: _dil
 Dataset Creation: Sat Jul 14 10:44:39 2018
 Charted by: Depth in Feet scaled 1:240




2700

2750

2800







2850

2900

2950

3000







3050

3100

3150

3200






3250


3300

3350

3400

3450






3500

3550

3600

3650







3700

3750



3800


LTD 3812



REPEAT SECTION

Database File: 2661pe.db
 Dataset Pathname: pass2.3
 Presentation Format: _dil
 Dataset Creation: Sat Jul 14 09:30:19 2018 by Calc SOC 120430
 Charted by: Depth in Feet scaled 1:240






3600

3650

3700

3750

3800



0	GAMMA RAY (GAPI)	150	0.2	SHALLOW GUARD (Ohm-m)	2000
-100	SP (mV)	100	0.2	DEEP INDUCTION (Ohm-m)	2000
-250	Rxo/Rt	50	0.2	MEDIUM INDUCTION (Ohm-m)	2000
0	MINMK	20			

Calibration Report								
Database File:		1598ddn.db						
Dataset Pathname:		pass4						
Dataset Creation:		Wed Aug 30 02:13:00 2017 by Log SOC 120430						
Dual Induction Calibration Report								
Serial-Model:			PROBE7-DILG					
Surface Cal Performed:			Wed Aug 30 00:06:33 2017					
Downhole Cal Performed:			Mon Jul 28 12:02:56 2008					
After Survey Verification Performed:			Mon Jul 28 12:02:56 2008					
Surface Calibration								
Readings				References			Results	
Loop:	Air	Loop		Air	Loop		m	b
Deep	-0.014	0.629	V	0.000	400.000	mmho/m	620.000	0.000
Medium	0.039	0.728	V	0.000	464.000	mmho/m	675.000	-44.000
Internal:	Zero	Cal		Zero	Cal		m	b
Deep	0.011	0.610	V	0.000	400.000	mmho/m	667.135	-7.256
Medium	0.005	0.712	V	0.000	464.000	mmho/m	655.677	-3.102
Downhole Calibration								
Readings				References			Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	14.508	388.384	mmho/m	1.000	0.000
Medium	0.000	0.000	mmho/m	166.367	504.400	mmho/m	1.000	0.000
LL3		7.500	V		1400.000	Ohm-m		
		0.000	V		20.000	Ohm-m		
		-7.200	V		4000.000	mmho-m		
After Survey Verification								
Readings				Targets			Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
Medium	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
LL3		1.000	Ohm-m		1.000	Ohm-m		
		0.000	Ohm-m		0.000	Ohm-m		
		1.000	mmho-m		1.000	mmho-m		

Litho Density Calibration Report					
Serial: 002		Model: PRB			
Master Calibration			Performed Mon Aug 21 11:27:42 2017		
	Background	Magnesium	Aluminum	Sandstone	
Window 1	837.1	10632.5	2945.1	12110.1	cps
Window 2	772.0	9117.4	2570.1	10197.3	cps
Window 3	631.7	4669.0	1481.9	5042.9	cps

Window 4	187.0	187.5	185.9	189.9	cps
Long Space	0.0	8345.4	1798.1	9425.3	cps
Short Space	1.1	1927.9	1285.9	2050.2	cps
Rho		1.7100	2.5960	1.3800	g/cc
Pe		0.0000	2.5700	1.5500	
Rib Angle	: 45.2	Rib Slope	: 1.008	Density/Spine Ratio	: 0.558
Spine Angle	: 75.2	Spine Slope	: 3.790	Spine Intercept	: -19.6

Before Survey Verification			Performed Wed Dec 31 18:00:00 1969		
Window 1	0.0	0.0	0.0	0.0	cps
Window 2	0.0	0.0	0.0	0.0	cps
Window 3	0.0	0.0	0.0	0.0	cps
Window 4	0.0	0.0	0.0	0.0	cps
Long Space	0.0	0.0	0.0	0.0	cps
Short Space	0.0	0.0	0.0	0.0	cps
Measured Rho		0.0000	0.0000	0.0000	g/cc
Measured Correction		0.0000	0.0000	0.0000	g/cc
Measured Pe			0.0000	0.0000	

After Survey Verification			Performed Wed Dec 31 18:00:00 1969		
Window 1	0.0	0.0	0.0	0.0	cps
Window 2	0.0	0.0	0.0	0.0	cps
Window 3	0.0	0.0	0.0	0.0	cps
Window 4	0.0	0.0	0.0	0.0	cps
Long Space	0.0	0.0	0.0	0.0	cps
Short Space	0.0	0.0	0.0	0.0	cps
Measured Rho		0.0000	0.0000	0.0000	g/cc
Measured Correction		0.0000	0.0000	0.0000	g/cc
Measured Pe			0.0000	0.0000	

--

Compensated Neutron Calibration Report

Serial Number:	070808
Tool Model:	Probe

PRE-SURVEY VERIFICATION			
Detector	Readings	Measured	Target
Short Space	cps		
Long Space	cps	pu	pu

POST-SURVEY VERIFICATION			
Detector	Readings	Measured	Target
Short Space	cps		
Long Space	cps	pu	pu

Gamma Ray Calibration Report

Serial Number:	070558	
Tool Model:	OPEN_GR	
Performed:	Wed May 31 00:09:32 2017	
Calibrator Value:	1.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	1.0	cps

Sensitivity:

0.2800

GAPI/cps