



DUAL INDUCTION LOG

Company	NORSTAR PETROLEUM, INC.		
Well	THE SISTER'S #1-15		
Field	WILDCAT		
County	LANE	State	KANSAS
Company	NORSTAR PETROLEUM, INC.		
Well	THE SISTER'S #1-15		
Field	WILDCAT		
County	LANE	State	KANSAS
Location:	API # : 15-101-22567-0000		Other Services CDL/CNL/PE MEL
Permanent Datum	GROUND LEVEL	Elevation	2652
Log Measured From	KELLY BUSHING	7' A.G.L.	
Drilling Measured From	KELLY BUSHING		
SEC 15	TWP 19S	RGE 27W	
Date	9/14/17		
Run Number	ONE		
Depth Driller	4631		
Depth Logger	4630		
Bottom Logged Interval	4628		
Top Log Interval	00		
Casing Driller	8 5/8"@302'		
Casing Logger	305		
Bit Size	7 7/8"		
Type Fluid in Hole	CHEMICAL MUD	CHLORIDES 4,200 PPM	
Density / Viscosity	9.2/55		
pH / Fluid Loss	9.0/8.8		
Source of Sample	FLOWLINE		
Rim @ Meas. Temp	.950@90F		
Rmf @ Meas. Temp	.713@90F		
Rmc @ Meas. Temp	1.14@90F		
Source of Rmf / Rmc	MEASUREMENT		
Rim @ BHT	.701@122F		
Time Circulation Stopped	4 HOURS		
Time Logger on Bottom	6:30 P.M.		
Maximum Recorded Temperature	122F		
Equipment Number	922339		
Location	HAYS, KANSAS		
Recorded By	JEFF LUEBBERS		
Witnessed By	AARON YOUNG		

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

THANK YOU FOR USING ELI WIRELINE HAYS, KANSAS (785) 628-6395
DIRECTIONS
ALAMOTA, KS., 1/2E. ON HWY 96 TO "TURKEY RED RD.", 5 1/2S., E. INTO



MAIN SECTION

Database File: 1827pe.db
Dataset Pathname: pass3.9
Presentation Format: dil2
Dataset Creation: Thu Sep 14 20:39:23 2017
Charted by: Depth in Feet scaled 1:600

0	Gamma Ray (GAPI)	150
-100	SP (mV)	100
0	RWA (Ohm-m)	1


0	RLL3 (Ohm-m)	50
---	--------------	----

0	RILD (Ohm-m)	50
---	--------------	----


1000	CILD (mmho/m)	0
------	---------------	---


50	RILD X10 (Ohm-m)	500
----	------------------	-----

50	RLL3 X10 (Ohm-m)	500
----	------------------	-----



0
50
100
150
200
250
300
350
400





450

500

550

600

650

700


750


800

850



900



950






1000
1050
1100
1150
1200
1250
1300
1350
1400
1450
1500







2100

2150

2200

2250

2300

2350


2400


2450

2500

2550

2600





2650

2700

2750

2800

2850

2900


2950


3000

3050

3100

3150





3200

3250

3300

3350

3400

3450


3500


3550

3600

3650

3700





3750

3800

3850

3900

3950

4000


4050



4100

4150

4200

4250






ANHYDRITE

Database File: 1827pe.db
 Dataset Pathname: pass3.8
 Presentation Format: _dil
 Dataset Creation: Thu Sep 14 19:47:24 2017 by Calc SOC 120430
 Charted by: Depth in Feet scaled 1:240



-100	SP (mV)	100
-250	Rxo/Rt	50
0	MINMK	20

0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000




1950


2000

2050

0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	Rxo/Rt	50
0	MINMK	20



0.2	SHALLOW GUARD (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000




MAIN SECTION

Database File: 1827pe.db
 Dataset Pathname: pass3.9
 Presentation Format: _dil
 Dataset Creation: Thu Sep 14 20:39:23 2017
 Charted by: Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	Rxo/Rt	50
0	MINMK	20

0.2	SHALLOW GUARD (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000




3800


3850

3900

3950

4000







4050

4100

4150

4200






4250


4300

4350

4400

4450






4500

4550

4600

LTD 4630

0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	Rxo/Rt	50
0	MINMK	20




FR DEEP

FR MEDIUM

FR GUARD

0.2	SHALLOW GUARD (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000




DEDEAT SECTION

REPEAT SECTION

Database File: 1827pe.db
 Dataset Pathname: pass2.5
 Presentation Format: _dil
 Dataset Creation: Thu Sep 14 19:13:44 2017 by Calc SOC 120430
 Charted by: Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	Rxo/Rt	50
0	MINMK	20

0.2	SHALLOW GUARD (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000





4400

4450

4500

4550





Calibration Report									
Database File:		1598ddn.db							
Dataset Pathname:		pass4							
Dataset Creation:		Wed Aug 30 02:13:00 2017 by Log SOC 120430							
Dual Induction Calibration Report									
Serial-Model:		PROBE7-DILG							
Surface Cal Performed:		Wed Aug 30 00:06:33 2017							
Downhole Cal Performed:		Mon Jul 28 12:02:56 2008							
After Survey Verification Performed:		Mon Jul 28 12:02:56 2008							
Surface Calibration									
		Readings			References			Results	
Loop:	Air	Loop		Air	Loop		m	b	
Deep	-0.014	0.629	V	0.000	400.000	mmho/m	620.000	0.000	
Medium	0.039	0.728	V	0.000	464.000	mmho/m	675.000	-44.000	
Internal:	Zero	Cal		Zero	Cal		m	b	
Deep	0.011	0.610	V	0.000	400.000	mmho/m	667.135	-7.256	
Medium	0.005	0.712	V	0.000	464.000	mmho/m	655.677	-3.102	
Downhole Calibration									
		Readings			References			Results	
	Zero	Cal		Zero	Cal		m'	b'	
Deep	0.000	0.000	mmho/m	14.508	388.384	mmho/m	1.000	0.000	
Medium	0.000	0.000	mmho/m	166.367	504.400	mmho/m	1.000	0.000	
LL3		7.500	V		1400.000	Ohm-m			
		0.000	V		20.000	Ohm-m			
		-7.200	V		4000.000	mmho-m			

After Survey Verification			Readings		Targets		Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
Medium	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
LL3		1.000	Ohm-m		1.000	Ohm-m		
		0.000	Ohm-m		0.000	Ohm-m		
		1.000	mmho-m		1.000	mmho-m		

Litho Density Calibration Report								
Serial: 002			Model: PRB					

Master Calibration			Performed Mon Aug 21 11:27:42 2017					
	Background	Magnesium	Aluminum	Sandstone				
Window 1	837.1	10632.5	2945.1	12110.1			cps	
Window 2	772.0	9117.4	2570.1	10197.3			cps	
Window 3	631.7	4669.0	1481.9	5042.9			cps	
Window 4	187.0	187.5	185.9	189.9			cps	
Long Space	0.0	8345.4	1798.1	9425.3			cps	
Short Space	1.1	1927.9	1285.9	2050.2			cps	
Rho		1.7100	2.5960	1.3800			g/cc	
Pe		0.0000	2.5700	1.5500				
Rib Angle	: 45.2	Rib Slope	: 1.008	Density/Spine Ratio			: 0.558	
Spine Angle	: 75.2	Spine Slope	: 3.790	Spine Intercept			: -19.6	

Before Survey Verification			Performed Wed Dec 31 18:00:00 1969					
Window 1	0.0	0.0	0.0	0.0			cps	
Window 2	0.0	0.0	0.0	0.0			cps	
Window 3	0.0	0.0	0.0	0.0			cps	
Window 4	0.0	0.0	0.0	0.0			cps	
Long Space	0.0	0.0	0.0	0.0			cps	
Short Space	0.0	0.0	0.0	0.0			cps	
Measured Rho		0.0000	0.0000	0.0000			g/cc	
Measured Correction		0.0000	0.0000	0.0000			g/cc	
Measured Pe			0.0000	0.0000				

After Survey Verification			Performed Wed Dec 31 18:00:00 1969					
Window 1	0.0	0.0	0.0	0.0			cps	
Window 2	0.0	0.0	0.0	0.0			cps	
Window 3	0.0	0.0	0.0	0.0			cps	
Window 4	0.0	0.0	0.0	0.0			cps	
Long Space	0.0	0.0	0.0	0.0			cps	
Short Space	0.0	0.0	0.0	0.0			cps	
Measured Rho		0.0000	0.0000	0.0000			g/cc	
Measured Correction		0.0000	0.0000	0.0000			g/cc	
Measured Pe			0.0000	0.0000				

Compensated Neutron Calibration Report								
--	--	--	--	--	--	--	--	--

Serial Number:			070808					
Tool Model:			Probe					

PRE-SURVEY VERIFICATION								
Detector	Readings	Measured	Target					

Short Space	cps		
Long Space	cps	pu	pu
POST-SURVEY VERIFICATION			
Detector	Readings	Measured	Target
Short Space	cps		
Long Space	cps	pu	pu
Gamma Ray Calibration Report			
Serial Number:	070558		
Tool Model:	OPEN_GR		
Performed:	Wed May 31 00:09:32 2017		
Calibrator Value:	1.0	GAPI	
Background Reading:	0.0	cps	
Calibrator Reading:	1.0	cps	
Sensitivity:	0.2800	GAPI/cps	