GEOLOGIST'S REPORT

DRILL LINE TIME AND SAMPLE LOG

COMPANY: [illegible]
FIELD: [illegible]
SEC. [illegible] BLK. [illegible]
CONTRACTOR: [illegible]
SPUD: [illegible] COMP. [illegible]
TOTAL DEPTH: [illegible]
ELEVATIONS
KB: [illegible]
DF: [illegible]
GR: [illegible]
Water Depth: [illegible]
Field: [illegible] COUNTY: [illegible]

CONTACTOR SUPP. AND ENGINEERS: [illegible]
TYPE MUD: [illegible]
MAX. MUD WT.: [illegible] VISC.: [illegible] WL: [illegible] PH: [illegible]
CASING: [illegible]
TUBING: [illegible]
PERFORATIONS: [illegible]
PRODUCTIVE INTERVALS: [illegible]
INITIAL PRODUCTION: [illegible]
ELECTRICAL SURVEYS: [illegible]

REFERENCE WELL FOR STRUCTURE: [illegible]

REMARKS: [illegible]

LEGEND

Anhydrite | Salt | Bentonite | Shale | Gas sh | Dolomite | Oolitic Lime | Chert | Bituminite

DRILLING TIME IN MINUTES PER FOOT
Rate of Penetration Decreases
1" 5" 10" 15" 20" 30"

DEPTH | CONTAMINANT | SAMPLE DESCRIPTIONS | OIL SHOWS | REMARKS

2,950'
50
2,500'
50
1,000'
50
2,700'
50
3,350'
50
2,400'
50
3,000'
50
3,150'
50
3,200'
50
3,250'
50
3,300'
50
3,350'
50
3,400'
50
3,450'
50
3,500'

S