

Top - Bottom

A	BOREID	BOTTEMP	CASEOD	CASETHCK	FLUIDDEN	M	MATRXDEN
1	in 7.875	degF 100	in 5.5	in 0	g/cc 1	2	g/cc 2.71
NPORSEL	PERFS	SNDERR	SNDERRM	SPSHIFT	SRFTEMP	SZCOR	TDEPTH
Limestone	0	mmho/m 0	mmho/m 0	mV -210	degF 0	Off	ft 0

Sensor	Offset (ft)	Schematic		Description	Length (ft)	O.D. (in)	Weight (lb)
GR	33.00			GR-M&W (89-M&W)	3.00	3.50	50.00
CNLSC	29.90			CNT-M&W (tk10-MW)	5.50	3.50	100.00
CNSSC	29.15						
LSD DCAL SSD	20.85			CDL-M&W (168-986)	8.50	4.00	250.00
	20.83						
	20.35						
RLL3	15.80			DIL-M&W (1987)	18.50	3.50	220.00
RLL3F	15.79						
CILD	8.00						

CILM 4.70

SP 0.20

Dataset: garner_dennis_1.db: field/well/stack/pass3.1
Total length: 35.50 ft
Total weight: 620.00 lb
O.D.: 4.00 in





MAIN PASS


Database File garner_dennis_1.db
Dataset Pathname stack/pass3.1
Presentation Format cdl
Dataset Creation Fri Dec 01 12:10:24 2017
Charted by Depth in Feet scaled 1:600

0 GAMMA RAY (GAPI) 150
6 CALIPER (in) 16

30 COMPENSATED DENSITY (pu) -10
2 BULK DENSITY (g/cc) 3
15000 LINE TENSION (lb) 0
-0.25 CORRECTION (g/cc) 0.25











PIONEER
Pioneer Energy Services


MAIN PASS


Database File: garner_dennis_1.db
 Dataset Pathname: stack/pass3.1
 Presentation Format: cndlspec
 Dataset Creation: Fri Dec 01 12:10:24 2017
 Charted by: Depth in Feet scaled 1:240


0	GAMMA RAY (GAPI)	150	30	CNLS (pu)	-10
6	dcal (in)	16	30	COMPENSATED DENSITY (2.71 ma) (pu)	-10
6	BIT SIZE (in)	16	15000	LINE TENSION (lb)	0
			-0.25 CORRECTION (g/cc) 0.25		















4250

0	GAMMA RAY (GAPI)	150
6	dcal (in)	16
6	BIT SIZE (in)	16



30	CNLS (pu)	-10
30	COMPENSATED DENSITY (2.71 ma) (pu)	-10
15000	LINE TENSION (lb)	0
-0.25	CORRECTION (g/cc)	0.25




REPEAT SECTION

Database File garner_dennis_1.db
 Dataset Pathname stack/pass2.1
 Presentation Format cndlspec
 Dataset Creation Fri Dec 01 12:10:36 2017
 Charted by Depth in Feet scaled 1:240


0	GAMMA RAY (GAPI)	150
6	dcal (in)	16
6	BIT SIZE (in)	16


30	CNLS (pu)	-10
30	COMPENSATED DENSITY (2.71 ma) (pu)	-10
15000	LINE TENSION (lb)	0
-0.25	CORRECTION (g/cc)	0.25



4050

4100





Calibration Report							
Database File	garner_dennis_1.db						
Dataset Pathname	stack/pass3.1						
Dataset Creation	Fri Dec 01 12:10:24 2017						
Dual Induction Calibration Report							
Serial-Model:				1987-M&W			
Calibration Performed:				Tue Apr 11 17:07:38 2017			
Readings			References			Results	
Loop:	Air	Loop	Air	Loop		Gain	Offset
Deep	178.615	710.235	0.000	255.800	mmho/m	0.560	-36.500
Medium	161.982	1441.110	0.000	255.800	mmho/m	0.440	-110.500

Serial-Model:	168-986-M&W
Source / Verifier:	/
Master Calibration Performed:	Tue Apr 11 17:07:47 2017

Master Calibration

	Density		Far Detector	Near Detector	
Magnesium	1.755	g/cc	4691.86	4818.19	cps
Aluminum	2.700	g/cc	859.57	3020.22	cps
Spine Angle = 74.61			Density/Spine Ratio = 0.537		
	Size		Reading		
Small Ring	4.00	in	1.03		
Large Ring	14.00	in	1.23		

Compensated Neutron Calibration Report

Serial Number:	tk10-MW
Tool Model:	M&W
Calibration Performed:	Wed Nov 16 11:21:36 2016

Detector	Readings	Target	Normalization
Short Space	6240.00 cps	1000.00 cps	1.6025
Long Space	460.00 cps	1000.00 cps	1.9500

Gamma Ray Calibration Report

Serial Number:	89-M&W
Tool Model:	M&W
Calibration Performed:	Tue Apr 11 17:08:01 2017
Calibrator Value:	1000.0 GAPI
Background Reading:	0.0 cps
Calibrator Reading:	6.2 cps
Sensitivity:	0.5200 GAPI/cps



Company	THOMAS GARNER, INC.
Well	DENNIS NO. 1
Field	LEISS NORTHWEST
County	STAFFORD
State	KANSAS