ORNISH WIRELINE SERVICES, INC. CHANUTE, KANSAS

Company LAYMON OIL II, LLC
Well STOCKEBRAND #22-19
Field OWL CREEK
County WOODSON
State KS

Date 12-24-19

GAMMA RAY CEMENT EVALUATION LOG

LAYMON OIL II, LLC
STOCKEBRAND #22-19
OWL CREEK
WOODSON
KS

Sec 19 Twp 26S Rge 16E
API No. 15-207-28730-00-00
Elevation: 995 KB
1012 GL 995 DF
Other Services

Log Measured From: Ground Level
Drilling Measured From: KB
Permanent Datum: Ground Level

Date: 12-24-19
Run No: ONE
Depth Driller: 1060
Depth Logger: 1060
Bottom Logged Interval: 1060
Top Logged Interval: 0
Casing Driller: 8.625 @ 21
Casing Logger: 21
Bit Size: 7.875
Type Fluid in Hole: GEL/BIT
Density / Viscosity: 8.8 / 32
Max. Recorded Temp.: 70
Estimated Cement Top: 0
Operator Witnessed By: Rick Allen

Equipment Number: 109
Location: LAYMON OIL

Truck / Unit No.: 109
Recorded By: Tony Tidwell

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Service	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
GR	7.59		GR-TITAN_169 (TIT169_001) Titan 1.11/16" Gamma Ray	4.75	1.69	20.00
CCL	5.05		CCL-TITAN_169 (TIT169) Titan 1.11/16" Logging CCL	1.83	1.69	7.50
NEU	0.63		NEU-TITAN (TIT801) TITAN 1.11/16" Neutron	4.33	1.69	25.00

Dataset: stockebrand #22-19 db: fieldwithrun1=pass2
Tool String Length: 52.50 ft
Total Weight: 52.50 lb
O.D. 1.69 in

Database File: stockebrand #22-19.db
Dataset Pathname: pass2
Presentation Format: gr-ccl
Dataset Creation: Tue Dec 24 13:37:56 2019 by Log Std Casedhole 09061
Charted by: Depth in Feet scaled 1:240

150 gr 300 3 CCL3 0.200 NEU (cps) 1500
0 GR 150

PERFORATIONS
954-960' 16 SHOTS
940-946' 16 SHOTS
2 RTG

GR
NEU
CCL

ORNISH WIRELINE SERVICES, INC. CHANUTE, KANSAS

Company LAYMON OIL II, LLC
Well STOCKEBRAND #22-19
Field OWL CREEK
County WOODSON
State KS

Date 12-24-19