CORNISH WIRELINE SERVICES, INC.
CHANUTE, KANSAS

GAMMA RAY NEUTRON COMPLETION LOG

Company	LAYMON OIL II, LLC
Well	LIGHT A&B #15-19
Field	OWL CREEK
County	WOODSON SEC 16
State	KS

Company LAYMON OIL II, LLC
Well LIGHT A&B #15-19
Field OWL CREEK
County WOODSON State KS

Location: API #: 15-207-29737-00-00
1480' FSL 3795' FEL
SW-SW-NE-SW

SEC 16 TWP 25 RGE 16

Other Services

Permanent Datum	GL	Elevation	988
Log Measured From	GL		
Drilling Measured From	GL		

Elevation
K.B. 988
D.F.
G.L.

Date	11-19-2019		
Run Number	1NW		
Depth Driller			
Depth Logger	984.4		
Top Log Interval	0		
Bottom Logged Interval	984.4		
Fluid Level	SURF		
Type Fluid	WATER		
Production Casing	2 7/8" @ TD	@	@
Max. Recorded Temp.			
Estimated Cement Top			
Calculated Cement Top			
Amount & Type Cement			
Amount & Type Admix			
Drilling Contractor			
Equipment Number	109		
Location			
Recorded By	THAD TRAHAN		
Witnessed By	LUKE GALEMORE		

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			GR-TITAN_169 (TIT169_001) Titan 1 11/16" Gamma Ray	4.75	1.69	20.00
GR	7.59					
			CCL-TITAN_169 (TIT169) Titan 1 11/16" Logging CCL	1.83	1.69	7.50
CCL	5.05					
			NEU-TITAN (TIT801) TITAN 1 11/16" Neutron	4.33	1.69	25.00
NEU	0.63					



Dataset:	light a&b #15-19.db: field/well/run1/pass1
Total Length:	10.92 ft
Total Weight:	52.50 lb
O.D.	1.69 in

Database File:	light a&b #15-19.db
Dataset Pathname:	pass1
Presentation Format:	gr-n-ccl
Dataset Creation:	Tue Nov 19 12:42:49 2019 by Log Std Casedhole 09061
Charted by:	Depth in Feet scaled 1:240

PERFORATIONS
2" RTG
3 SPF
896'-906' 30 SHOTS
917'-927' 30 SHOTS

CORNISH WIRELINE SERVICES, INC.
CHANUTE, KANSAS

Company	LAYMON OIL II, LLC
Well	LIGHT A&B #15-19
Field	OWL CREEK
County	WOODSON SEC 16 TWP 25S R 16E
State	KS Date 11-19-2019