

DUAL INDUCTION LOG

Company	VINCENT OIL CORPORATION	Company	VINCENT OIL CORPORATION
Well	KEOUGH #8-34	Well	KEOUGH #8-34
Field	MULLBERRY CREEK	Field	MULLBERRY CREEK
County	FORD	County	FORD
State	KANSAS	State	KANSAS
Location:	APL # : 15-057-20986-0000 3015' FSL & 865' FEL NE - SW - SE - NE	Other Services CDL/CNL/PE MEL/SONIC	
Permanent Datum	GROUND LEVEL	Elevation	2494
Log Measured From	KELLY BUSHING 12' A.G.L.		
Drilling Measured From	KELLY BUSHING		
SEC 34 TWP 28S RGE 23W			
Date	10/11/17		
Run Number	ONE		
Depth Driller	5335		
Depth Logger	5338		
Bottom Logged Interval	5336		
Top Log Interval	00		
Casing Driller	8 5/8"@648'		
Casing Logger	646		
Bit Size	7 7/8"		
Type Fluid in Hole	CHEMICAL MUD	CHLORIDES 10,800 PPM	
Density / Viscosity	9.1/78		
pH / Fluid Loss	9.0/11.6		
Source of Sample	FLOWLINE		
Rim @ Meas. Temp	.400@80F		
Rmf @ Meas. Temp	.300@80F		
Rmc @ Meas. Temp	.480@80F		
Source of Rmf / Rmc	MEASUREMENT		
Rim @ BHT	.250@128F		
Time Circulation Stopped	3 HOURS		
Time Logger on Bottom	10:15 P.M.		
Maximum Recorded Temperature	128F		
Equipment Number	922339		
Location	HAYS, KANSAS		
Recorded By	JEFF LUEBBERS		
Witnessed By	JIM HALL		

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

THANK YOU FOR USING ELI WIRELINE HAYS, KANSAS (785) 628-6395
DIRECTIONS
KINGSDOWN, KS. & HWY 54, 2N. ON "RD. 125" TO "WILBURN RD.", 3 1/4W., N. INTO AT GATE



MAIN SECTION

Database File: 1832pe.db
Dataset Pathname: pass4.6
Presentation Format: dil2
Dataset Creation: Thu Oct 12 00:15:37 2017
Charted by: Depth in Feet scaled 1:600

0	Gamma Ray (GAPI)	150
-100	SP (mV)	100
0	RWA (Ohm-m)	1


0	RLL3 (Ohm-m)	50
---	--------------	----

0	RILD (Ohm-m)	50
---	--------------	----



1000	CILD (mmho/m)	0
------	---------------	---


50	RILD X10 (Ohm-m)	500
----	------------------	-----

50	RLL3 X10 (Ohm-m)	500
----	------------------	-----



0
50
100
150
200
250
300
350
400





450

500

550

600

650

700


750



800



850


900

950









2100

2150

2200

2250

2300

2350



2400


2450

2500

2550

2600





2650

2700

2750

2800

2850

2900


2950


3000

3050

3100

3150





3200

3250

3300

3350

3400

3450


3500


3550

3600

3650

3700





3750

3800

3850

3900

3950

4000


4050


4100

4150

4200

4250





4300

4350

4400

4450

4500

4550


4600


4650

4700

4750

4800





4850

4900

4950

5000

5050

5100

5150

5200


5250

5300

0 Gamma Ray (GAPI) 150

-100 SP (mV) 100

0 RWA (Ohm-m) 1




0 RLL3 (Ohm-m) 50

0 RILD (Ohm-m) 50

1000 CILD (mmho/m) 0

50	RILD X10 (Ohm-m)	500
50	RLL3 X10 (Ohm-m)	500




MAIN SECTION

Database File: 1832pe.db
 Dataset Pathname: pass4.6
 Presentation Format: _dil
 Dataset Creation: Thu Oct 12 00:15:37 2017
 Charted by: Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	Rxo/Rt	50
0	MINMK	20


0.2	SHALLOW GUARD (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000




4000

4050

4100






4150


4200

4250

4300

4350







4400

4450

4500

4550







4600

4650

4700

4750






4800


4850

4900

4950

5000







5050

5100

5150

5200






5250


5300

LTD 5338

0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	Rxo/Rt	50
0	MINMK	20



0.2	SHALLOW GUARD (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000




REPEAT SECTION


Database File: 1832pe.db
 Dataset Pathname: pass3.3
 Presentation Format: _dil
 Dataset Creation: Wed Oct 11 23:09:50 2017
 Charted by: Depth in Feet scaled 1:240


0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	Rxo/Rt	50
0	MINMK	20

0.2	SHALLOW GUARD (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000



5000






5050

5100

5150

5200






5250

5300

0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	Rxo/Rt	50
0	MINMK	20



0.2	SHALLOW GUARD (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000

Calibration Report

Database File: 1598ddn.db
 Dataset Pathname: pass4
 Dataset Creation: Wed Aug 30 02:13:00 2017 by Log SOC 120430

Dual Induction Calibration Report

Serial-Model: PROBE7-DILG
 Surface Cal Performed: Wed Aug 30 00:06:33 2017
 Downhole Cal Performed: Mon Jul 28 12:02:56 2008
 After Survey Verification Performed: Mon Jul 28 12:02:56 2008

Surface Calibration

Readings				References			Results	
Loop:	Air	Loop		Air	Loop		m	b
Deep	-0.014	0.629	V	0.000	400.000	mmho/m	620.000	0.000
Medium	0.039	0.728	V	0.000	464.000	mmho/m	675.000	-44.000
Internal:	Zero	Cal		Zero	Cal		m	b
Deep	0.011	0.610	V	0.000	400.000	mmho/m	667.135	-7.256
Medium	0.005	0.712	V	0.000	464.000	mmho/m	655.677	-3.102

Downhole Calibration			Readings		References		Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	14.508	388.384	mmho/m	1.000	0.000
Medium	0.000	0.000	mmho/m	166.367	504.400	mmho/m	1.000	0.000
LL3		7.500	V		1400.000	Ohm-m		
		0.000	V		20.000	Ohm-m		
		-7.200	V		4000.000	mmho-m		

After Survey Verification			Readings		Targets		Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
Medium	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
LL3		1.000	Ohm-m		1.000	Ohm-m		
		0.000	Ohm-m		0.000	Ohm-m		
		1.000	mmho-m		1.000	mmho-m		

Litho Density Calibration Report Serial: 002 Model: PRB								
---	--	--	--	--	--	--	--	--

Master Calibration			Performed Mon Aug 21 11:27:42 2017		
	Background	Magnesium	Aluminum	Sandstone	
Window 1	837.1	10632.5	2945.1	12110.1	cps
Window 2	772.0	9117.4	2570.1	10197.3	cps
Window 3	631.7	4669.0	1481.9	5042.9	cps
Window 4	187.0	187.5	185.9	189.9	cps
Long Space	0.0	8345.4	1798.1	9425.3	cps
Short Space	1.1	1927.9	1285.9	2050.2	cps
Rho		1.7100	2.5960	1.3800	g/cc
Pe		0.0000	2.5700	1.5500	
Rib Angle	: 45.2	Rib Slope	: 1.008	Density/Spine Ratio	: 0.558
Spine Angle	: 75.2	Spine Slope	: 3.790	Spine Intercept	: -19.6

Before Survey Verification			Performed Wed Dec 31 18:00:00 1969		
Window 1	0.0	0.0	0.0	0.0	cps
Window 2	0.0	0.0	0.0	0.0	cps
Window 3	0.0	0.0	0.0	0.0	cps
Window 4	0.0	0.0	0.0	0.0	cps
Long Space	0.0	0.0	0.0	0.0	cps
Short Space	0.0	0.0	0.0	0.0	cps
Measured Rho		0.0000	0.0000	0.0000	g/cc
Measured Correction		0.0000	0.0000	0.0000	g/cc
Measured Pe			0.0000	0.0000	

After Survey Verification			Performed Wed Dec 31 18:00:00 1969		
Window 1	0.0	0.0	0.0	0.0	cps
Window 2	0.0	0.0	0.0	0.0	cps
Window 3	0.0	0.0	0.0	0.0	cps
Window 4	0.0	0.0	0.0	0.0	cps
Long Space	0.0	0.0	0.0	0.0	cps
Short Space	0.0	0.0	0.0	0.0	cps
Measured Rho		0.0000	0.0000	0.0000	g/cc
Measured Correction		0.0000	0.0000	0.0000	g/cc
Measured Pe			0.0000	0.0000	

Compensated Neutron Calibration Report			
Serial Number:		070808	
Tool Model:		Probe	
PRE-SURVEY VERIFICATION			
Detector	Readings	Measured	Target
Short Space	cps		
Long Space	cps	pu	pu
POST-SURVEY VERIFICATION			
Detector	Readings	Measured	Target
Short Space	cps		
Long Space	cps	pu	pu
Gamma Ray Calibration Report			
Serial Number:		070558	
Tool Model:		OPEN_GR	
Performed:		Wed May 31 00:09:32 2017	
Calibrator Value:	1.0	GAPI	
Background Reading:	0.0	cps	
Calibrator Reading:	1.0	cps	
Sensitivity:	0.2800	GAPI/cps	