



DUAL INDUCTION LOG


Company LOTUS OPERATING COMPANY, LLC.	
Well #4 HASKARD "C"	
Field HARDTNER	
County BARBER	
State KANSAS	
Location: API # : 15-007-24363-0000	
SEC 7 TWP 35S RGE 12W	
Permanent Datum GROUND LEVEL	Elevation 1446
Log Measured From KELLY BUSHING 13' A.G.L.	
Drilling Measured From KELLY BUSHING	
Other Services CDL/CNL/PE MEL/SON/FF	
Elevation K.B. 1459 D.F. 1457 G.L. 1446	
Date 11/5/19	
Run Number ONE	
Depth Driller 5630	
Depth Logger 5632	
Bottom Logged Interval 5630	
Top Log Interval 00	
Casing Driller 8 5/8"@265'	
Casing Logger 266	
Bit Size 7 7/8"	
Type Fluid in Hole CHEMICAL MUD	CHLORIDES 3,000 PPM
Density / Viscosity 9.6/47	
pH / Fluid Loss 11.0/8.8	
Source of Sample FLOWLINE	
Rim @ Meas. Temp .660@86F	
Rmf @ Meas. Temp .495@86F	
Rmc @ Meas. Temp .792@86F	
Source of Rmf / Rmc MEASUREMENT	
Rim @ BHT .433@131F	
Time Circulation Stopped 3 HOURS	
Time Logger on Bottom 5:00 P.M.	
Maximum Recorded Temperature 131F	
Equipment Number 922339	
Location HAYS, KANSAS	
Recorded By JEFF LUEBBERS	
Witnessed By TIM HELLMAN	

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

THANK YOU FOR USING ELI WIRELINE HAYS, KANSAS (785) 628-6395
DIRECTIONS
HARDTNER, KS., 1 W. ON "HACKBERRY RD." N. INTO @ TANK BATTERY



MAIN SECTION

Database File: 4379pe.db
Dataset Pathname: pass3.9
Presentation Format: dil2
Dataset Creation: Tue Nov 05 18:35:48 2019 by Calc SOC 120430
Charted by: Depth in Feet scaled 1:600

0	Gamma Ray (GAPI)	150
-100	SP (mV)	100
0	RWA (Ohm-m)	1


0	RLL3 (Ohm-m)	50
---	--------------	----

0	RILD (Ohm-m)	50
---	--------------	----



1000	CILD (mmho/m)	0
------	---------------	---


50	RILD X10 (Ohm-m)	500
----	------------------	-----

50	RLL3 X10 (Ohm-m)	500
----	------------------	-----



0
50
100
150
200
250
300
350
400





450

500

550

600

650

700


750


800

850

900

950





1000

1050

1100

1150

1200

1250



1300


1350

1400

1450

1500





1550

1600

1650

1700

1750

1800


1850


1900

1950

2000

2050





2100

2150

2200

2250

2300

2350


2400


2450

2500

2550

2600





2650

2700

2750

2800

2850

2900


2950


3000

3050

3100

3150





3200

3250

3300

3350

3400

3450



3500


3550

3600

3650

3700





3750

3800

3850

3900

3950

4000


4050


4100

4150

4200

4250





4300

4350

4400

4450

4500

4550



4600


4650

4700

4750

4800





4850

4900

4950

5000

5050

5100



5150



5200

5250

5300

5350







MAIN SECTION


Database File: 4379pe.db
 Dataset Pathname: pass3.9
 Presentation Format: _dil
 Dataset Creation: Tue Nov 05 18:35:48 2019 by Calc SOC 120430
 Charted by: Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150	0.2	SHALLOW GUARD (Ohm-m)	2000
-100	SP (mV)	100	0.2	DEEP INDUCTION (Ohm-m)	2000
-250	Rxo/Rt	50	0.2	MEDIUM INDUCTION (Ohm-m)	2000
0	MINMK	20			



3800







3850

3900

3950

4000






4050


4100

4150

4200

4250







4300

4350

4400

4450







4500

4550

4600

4650






4700


4750

4800

4850

4900







4950

5000

5050

5100






5150


5200

5250

5300

5350









5400

5450

5500




5550






REPEAT SECTION


Database File: 4379pe.db
 Dataset Pathname: pass2.4
 Presentation Format: _dil
 Dataset Creation: Tue Nov 05 17:23:41 2019
 Charted by: Depth in Feet scaled 1:240



5400

5450






5500

5550

5600



Calibration Report

Database File: 1598ddn.db
 Dataset Pathname: pass4
 Dataset Creation: Wed Aug 30 02:13:00 2017 by Log SOC 120430

Dual Induction Calibration Report

Serial-Model: PROBE7-DILG
 Surface Cal Performed: Wed Aug 30 00:06:33 2017
 Downhole Cal Performed: Mon Jul 28 12:02:56 2008
 After Survey Verification Performed: Mon Jul 28 12:02:56 2008

Surface Calibration

Loop:	Readings			References			Results	
	Air	Loop		Air	Loop		m	b
Deep	-0.014	0.629	V	0.000	400.000	mmho/m	620.000	0.000
Medium	0.039	0.728	V	0.000	464.000	mmho/m	675.000	-44.000
Internal:	Zero	Cal		Zero	Cal		m	b
Deep	0.011	0.610	V	0.000	400.000	mmho/m	667.135	-7.256
Medium	0.005	0.712	V	0.000	464.000	mmho/m	655.677	-3.102

Downhole Calibration

	Readings			References			Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	14.508	388.384	mmho/m	1.000	0.000
Medium	0.000	0.000	mmho/m	166.367	504.400	mmho/m	1.000	0.000
LL3		7.500	V		1400.000	Ohm-m		
		0.000	V		20.000	Ohm-m		
		-7.200	V		4000.000	mmho-m		

After Survey Verification

	Readings			Targets			Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
Medium	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
LL3		1.000	Ohm-m		1.000	Ohm-m		
		0.000	Ohm-m		0.000	Ohm-m		
		1.000	mmho-m		1.000	mmho-m		

Litho Density Calibration Report
Serial: 002 Model: PRB

Master Calibration

Performed Mon Aug 21 11:27:42 2017

	Background	Magnesium	Aluminum	Sandstone	
Window 1	837.1	10632.5	2945.1	12110.1	cps
Window 2	772.0	9117.4	2570.1	10197.3	cps
Window 3	631.7	4669.0	1481.9	5042.9	cps
Window 4	187.0	187.5	185.9	189.9	cps
Long Space	0.0	8345.4	1798.1	9425.3	cps
Short Space	1.1	1927.9	1285.9	2050.2	cps
Rho		1.7100	2.5960	1.3800	g/cc
Pe		0.0000	2.5700	1.5500	
Rib Angle	: 45.2	Rib Slope	: 1.008	Density/Spine Ratio	: 0.558
Spine Angle	: 75.2	Spine Slope	: 3.790	Spine Intercept	: -19.6

Before Survey Verification

Performed Wed Dec 31 18:00:00 1969

Window 1	0.0	0.0	0.0	0.0	cps
Window 2	0.0	0.0	0.0	0.0	cps
Window 3	0.0	0.0	0.0	0.0	cps

Window 4	0.0	0.0	0.0	0.0	cps
Long Space	0.0	0.0	0.0	0.0	cps
Short Space	0.0	0.0	0.0	0.0	cps
Measured Rho		0.0000	0.0000	0.0000	g/cc
Measured Correction		0.0000	0.0000	0.0000	g/cc
Measured Pe			0.0000	0.0000	

After Survey Verification			Performed Wed Dec 31 18:00:00 1969		
Window 1	0.0	0.0	0.0	0.0	cps
Window 2	0.0	0.0	0.0	0.0	cps
Window 3	0.0	0.0	0.0	0.0	cps
Window 4	0.0	0.0	0.0	0.0	cps
Long Space	0.0	0.0	0.0	0.0	cps
Short Space	0.0	0.0	0.0	0.0	cps
Measured Rho		0.0000	0.0000	0.0000	g/cc
Measured Correction		0.0000	0.0000	0.0000	g/cc
Measured Pe			0.0000	0.0000	

Compensated Neutron Calibration Report

Serial Number:	070808
Tool Model:	Probe

PRE-SURVEY VERIFICATION			
Detector	Readings	Measured	Target
Short Space	cps		
Long Space	cps	pu	pu

POST-SURVEY VERIFICATION			
Detector	Readings	Measured	Target
Short Space	cps		
Long Space	cps	pu	pu

Gamma Ray Calibration Report

Serial Number:	070558	
Tool Model:	OPEN_GR	
Performed:	Wed May 31 00:09:32 2017	
Calibrator Value:	1.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	1.0	cps
Sensitivity:	0.2800	GAPI/cps