



DUAL INDUCTION LOG

Company	VINCENT OIL CORPORATION	Company	VINCENT OIL CORPORATION
Well	SMITH #2-6	Well	SMITH #2-6
Field	KINGSDOWN NORTHWEST	Field	KINGSDOWN NORTHWEST
County	FORD	County	FORD
State	KANSAS	State	KANSAS
Location:	API # : 15-057-20998-0000 1568' FSL & 1993' FEL	Other Services CDL/CNL/PE MEL/SONIC	
Permanent Datum	GROUND LEVEL	Elevation	2511
Log Measured From	KELLY BUSHING 13' A.G.L.	K.B. 2524 D.F. 2522 G.L. 2511	
Drilling Measured From	KELLY BUSHING		
SEC 6	TWP 29S	RGE 22W	
Date	5/15/18		
Run Number	ONE		
Depth Driller	5400		
Depth Logger	5396		
Bottom Logged Interval	5394		
Top Log Interval	00		
Casing Driller	8 5/8"@678'		
Casing Logger	680		
Bit Size	7 7/8"		
Type Fluid in Hole	CHEMICAL MUD	CHLORIDES 11,400 PPM	
Density / Viscosity	9.2/5.1		
pH / Fluid Loss	9.5/12.4		
Source of Sample	FLOWLINE		
Rim @ Meas. Temp	.400@80F		
Rmf @ Meas. Temp	.300@80F		
Rmc @ Meas. Temp	.480@80F		
Source of Rmf / Rmc	MEASUREMENT		
Rim @ BHT	.248@129F		
Time Circulation Stopped	2.5 HOURS		
Time Logger on Bottom	5:00 P.M.		
Maximum Recorded Temperature	129F		
Equipment Number	922339		
Location	HAYS, KANSAS		
Recorded By	JEFF LUEBBERS		
Witnessed By	KEN LeBLANC		

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

THANK YOU FOR USING ELI WIRELINE HAYS, KANSAS (785) 628-6395
DIRECTIONS
KINGSDOWN, KS., (HWY 54 & RD. 125), 1 1/2N. TO TANK BATTERY 1/2W. INTO




MAIN SECTION

Database File: 2495pe.db
Dataset Pathname: pass4.2M
Presentation Format: dil2
Dataset Creation: Tue May 15 19:15:55 2018
Charted by: Depth in Feet scaled 1:600



0	Gamma Ray (GAPI)	150
-100	SP (mV)	100
0	RWA (Ohm-m)	1


0	RLL3 (Ohm-m)	50
0	RILD (Ohm-m)	50
1000	CILD (mmho/m)	0

50	RILD X10 (Ohm-m)	500
50	RLL3 X10 (Ohm-m)	500



0
50
100
150
200
250
300
350
400





450

500

550

600

650

700



750



800



850


900

950









2100

2150

2200

2250

2300

2350



2400


2450

2500

2550

2600





2650

2700

2750

2800

2850

2900



2950


3000

3050

3100

3150





3200

3250

3300

3350

3400

3450


3500


3550

3600

3650

3700





3750

3800

3850

3900

3950

4000


4050


4100

4150

4200

4250





4300

4350

4400

4450

4500

4550



4600


4650

4700

4750

4800





4850

4900

4950

5000

5050

5100


5150


5200

5250



5300

5350








5400



MAIN SECTION


Database File: 2495pe.db
 Dataset Pathname: pass4.2M
 Presentation Format: _dil
 Dataset Creation: Tue May 15 19:15:55 2018
 Charted by: Depth in Feet scaled 1:240




4200

4250

4300







4350

4400

4450

4500






4550


4600

4650

4700

4750







4800

4850

4900

4950








5000

5050

5100


5150





-100	SP (mV)	100
-250	Rxo/Rt	50
0	MINMK	20

0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000




REPEAT SECTION

Database File: 2495pe.db
 Dataset Pathname: pass3.5
 Presentation Format: _dil
 Dataset Creation: Tue May 15 17:43:42 2018
 Charted by: Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150
-100	SP (mV)	100
-250	Rxo/Rt	50
0	MINMK	20


0.2	SHALLOW GUARD (Ohm-m)	2000
0.2	DEEP INDUCTION (Ohm-m)	2000
0.2	MEDIUM INDUCTION (Ohm-m)	2000




5200

5250

5300





Calibration Report								
Database File:	1598ddn.db							
Dataset Pathname:	pass4							
Dataset Creation:	Wed Aug 30 02:13:00 2017 by Log SOC 120430							
Dual Induction Calibration Report								
Serial-Model:			PROBE7-DILG					
Surface Cal Performed:			Wed Aug 30 00:06:33 2017					
Downhole Cal Performed:			Mon Jul 28 12:02:56 2008					
After Survey Verification Performed:			Mon Jul 28 12:02:56 2008					
Surface Calibration								
		Readings		References			Results	
Loop:	Air	Loop		Air	Loop		m	b
Deep	-0.014	0.629	V	0.000	400.000	mmho/m	620.000	0.000
Medium	0.039	0.728	V	0.000	464.000	mmho/m	675.000	-44.000
Internal:	Zero	Cal		Zero	Cal		m	b
Deep	0.011	0.610	V	0.000	400.000	mmho/m	667.135	-7.256
Medium	0.005	0.712	V	0.000	464.000	mmho/m	655.677	-3.102
Downhole Calibration								
		Readings		References			Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	14.508	388.384	mmho/m	1.000	0.000
Medium	0.000	0.000	mmho/m	166.367	504.400	mmho/m	1.000	0.000
LLS	0.000	0.000	V	0.000	1400.000	Ohm-m		

LL3	7.500	V	1400.000	Ohm-m
	0.000	V	20.000	Ohm-m
	-7.200	V	4000.000	mmho-m

After Survey Verification								
	Readings			Targets			Results	
	Zero	Cal		Zero	Cal		m'	b'
Deep	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
Medium	0.000	0.000	mmho/m	0.000	0.000	mmho/m	0.000	0.000
LL3		1.000	Ohm-m		1.000	Ohm-m		
		0.000	Ohm-m		0.000	Ohm-m		
		1.000	mmho-m		1.000	mmho-m		

Litho Density Calibration Report								
Serial: 002			Model: PRB					

Master Calibration					Performed Mon Aug 21 11:27:42 2017			
	Background	Magnesium	Aluminum	Sandstone				
Window 1	837.1	10632.5	2945.1	12110.1				cps
Window 2	772.0	9117.4	2570.1	10197.3				cps
Window 3	631.7	4669.0	1481.9	5042.9				cps
Window 4	187.0	187.5	185.9	189.9				cps
Long Space	0.0	8345.4	1798.1	9425.3				cps
Short Space	1.1	1927.9	1285.9	2050.2				cps
Rho		1.7100	2.5960	1.3800				g/cc
Pe		0.0000	2.5700	1.5500				
Rib Angle	: 45.2	Rib Slope	: 1.008	Density/Spine Ratio			: 0.558	
Spine Angle	: 75.2	Spine Slope	: 3.790	Spine Intercept			: -19.6	

Before Survey Verification					Performed Wed Dec 31 18:00:00 1969			
Window 1	0.0	0.0	0.0	0.0				cps
Window 2	0.0	0.0	0.0	0.0				cps
Window 3	0.0	0.0	0.0	0.0				cps
Window 4	0.0	0.0	0.0	0.0				cps
Long Space	0.0	0.0	0.0	0.0				cps
Short Space	0.0	0.0	0.0	0.0				cps
Measured Rho		0.0000	0.0000	0.0000				g/cc
Measured Correction		0.0000	0.0000	0.0000				g/cc
Measured Pe			0.0000	0.0000				

After Survey Verification					Performed Wed Dec 31 18:00:00 1969			
Window 1	0.0	0.0	0.0	0.0				cps
Window 2	0.0	0.0	0.0	0.0				cps
Window 3	0.0	0.0	0.0	0.0				cps
Window 4	0.0	0.0	0.0	0.0				cps
Long Space	0.0	0.0	0.0	0.0				cps
Short Space	0.0	0.0	0.0	0.0				cps
Measured Rho		0.0000	0.0000	0.0000				g/cc
Measured Correction		0.0000	0.0000	0.0000				g/cc
Measured Pe			0.0000	0.0000				

Compensated Neutron Calibration Report								
--	--	--	--	--	--	--	--	--

Serial Number:			070808					
Tool Model:			Probe					

PRE-SURVEY VERIFICATION			
Detector	Readings	Measured	Target
Short Space	cps		
Long Space	cps	pu	pu
POST-SURVEY VERIFICATION			
Detector	Readings	Measured	Target
Short Space	cps		
Long Space	cps	pu	pu
Gamma Ray Calibration Report			
Serial Number:	070558		
Tool Model:	OPEN_GR		
Performed:	Wed May 31 00:09:32 2017		
Calibrator Value:	1.0	GAPI	
Background Reading:	0.0	cps	
Calibrator Reading:	1.0	cps	
Sensitivity:	0.2800	GAPI/cps	