PIONEER
Pioneer Energy Services

MICRORESISTIVITY LOG

Company THOMAS GARNER, INC.
Well GARNER #8
Field LEISS NW
County STAFFORD State KANSAS

Location: API # : 15-185-24037-00-00
NE SW NE
1716' FNL & 1737' FEL
SEC 15 TWP 25S RGE 13W

Other Services
CNL/CDL
DIL

Permanent Datum GROUND LEVEL Elevation 1926'
Log Measured From KELLY BUSHING
Drilling Measured From KELLY BUSHING

Elevation
K.B. 1937'
D.F. N/A
G.L. 1926'

Date	11/20/2018		
Run Number	TWO		
Depth Driller	4320'		
Depth Logger	4318'		
Bottom Logged Interval	4317'		
Top Log Interval	3300'		
Casing Driller	8.625" @ 307'		
Casing Logger	308'		
Bit Size	7.875"		
Type Fluid in Hole	CHEMICAL		
Salinity,ppm CL	6200		
Density / Viscosity	9.0 65		
pH / Fluid Loss	10.5 9.2		
Source of Sample	FLOWLINE		
Rm @ Meas. Temp	0.40 @ 50		
Rmf @ Meas. Temp	0.30 @ 50		
Rmc @ Meas. Temp	0.54 @ 50		
Source of Rmf / Rmc	CHARTS		
Rm @ BHT	0.17 @ 119		
Operating Rig Time	3 HOURS		
Max Rec. Temp. F	119		
Equipment Number	108		
Location	HAYS		
Recorded By	D. SCHMIDT		
Witnessed By	THOMAS GARNER		

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and Pioneer Wireline Services, LLC cannot and does not guarantee the accuracy or correctness of any interpretation, and Pioneer Wireline Services, LLC will not be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees.

Comments

N/A DENOTES NOT AVAILABLE OR NON-APPLICABLE.

ST JOHN,
5 SOUTH, 1/2 EAST,
SOUTH INTO

Log Measured From: KELLY BUSHING 11 Ft. Above Permanent Datum

THANK YOU FOR USING PIONEER ENERGY SERVICES
www.pioneeres.com 785-625-3858

Your Pioneer Energy Services Crew	This Log Record Was Witnessed By
Engineer: D. SCHMIDT	Primary Witness: THOMAS GARNER
Operator:	Secondary Witness:
Operator:	Secondary Witness:
Operator:	Secondary Witness:

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb
			ML-Armadillo (Armadillo-1) Pengo micro log tool mandrel with Armadillo Electronics	5.00	3.50	100.00
MCAL	1.00					
MI	1.00					
MN	1.00					

Dataset: thomas garner_garner 8.db: field/well/MEL/pass2
Total length: 5.00 ft
Total weight: 100.00 lb
O.D.: 3.50 in

Log Variables

DatabaseC:\ProgramData\Warrior\Data\thomas garner_garner 8.db
Dataset field/well/STACK/pass3.4/_vars_

Top - Bottom

A	BOREID in	BOTTEMP degF	CASEOD in	CASETHCK in	FLUIDDEN g/cc	M	MATRXDEN g/cc
1	7.875	119	5.5	0	1	2	2.71
NPORSEL	**PERFS**	**SNDERR mmho/m**	**SNDERRM mmho/m**	**SPSHIFT mV**	**SRFTEMP degF**	**SZCOR**	**TDEPTH ft**
Limestone	0	0	0	-230	50	Off	4318


PIONEER
Pioneer Energy Services


MAIN PASS


Database File thomas garner_garner 8.db
Dataset Pathname STACK/pass4.1
Presentation Format micro
Dataset Creation Tue Nov 20 10:58:10 2018
Charted by Depth in Feet scaled 1:240


0	GAMMA RAY (GAPI)	150
6	MICRO CALIPER (in)	16
6	BIT SIZE (in)	16
-200	SP (mV)	0


0	MICRO INVERSE 1 X 1 (Ohm-m)	40
0	MICRO NORMAL 2" (Ohm-m)	40
15000	LINE TENSION (lb)	0




3500
3550
3600
3650
3700


3750
3800
3850
3900


3950
4000
4050
4100
4150



0	GAMMA RAY (GAPI)	150
6	MICRO CALIPER (in)	16
6	BIT SIZE (in)	16
-200	SP (mV)	0

0	MICRO INVERSE 1 X 1 (Ohm-m)	40
0	MICRO NORMAL 2" (Ohm-m)	40
15000	LINE TENSION (lb)	0


PIONEER
Pioneer Energy Services


REPEAT SECTION

Database File	thomas garner_garner 8.db
Dataset Pathname	STACK/pass2.6
Presentation Format	micro
Dataset Creation	Tue Nov 20 10:21:14 2018
Charted by	Depth in Feet scaled 1:240

0	GAMMA RAY (GAPI)	150
6	MICRO CALIPER (in)	16
6	BIT SIZE (in)	16
-200	SP (mV)	0

0	MICRO INVERSE 1 X 1 (Ohm-m)	40
0	MICRO NORMAL 2" (Ohm-m)	40
15000	LINE TENSION (lb)	0





Calibration Report

Database File	thomas garner_garner 8.db
Dataset Pathname	STACK/pass3.4
Dataset Creation	Tue Nov 20 10:18:45 2018

Dual Induction Calibration Report

Serial-Model:	PSI 988-M&W
Calibration Performed:	Thu Sep 06 14:52:38 2018

	Readings		References			Results	
Loop:	Air	Loop	Air	Loop		Gain	Offset
Deep	178.615	710.235	0.000	255.800	mmho/m	0.525	-44.000
Medium	161.982	1441.110	0.000	255.800	mmho/m	0.380	-16.500

Compensated Density Calibration Report

Serial-Model:	934-5002-M&W
Source / Verifier:	/
Master Calibration Performed:	Wed Aug 29 11:03:55 2018

Master Calibration

	Density		Far Detector	Near Detector	
Magnesium	1.755	g/cc	3720.16	2661.79	cps
Aluminum	2.685	g/cc	696.57	1725.83	cps

Spine Angle = 75.50

Density/Spine Ratio = 0.537

	Size		Reading
Small Ring	4.00	in	1.16
Large Ring	16.00	in	1.01

Compensated Neutron Calibration Report

Serial Number:	tk10-MW

Tool Model: M&W
Calibration Performed: Wed Nov 16 11:21:36 2016

Detector	Readings	Target	Normalization
Short Space	6240.00 cps	1000.00 cps	1.6025
Long Space	460.00 cps	1000.00 cps	1.9500

Gamma Ray Calibration Report

Serial Number:	89-M&W	
Tool Model:	M&W	
Calibration Performed:	Tue Apr 11 17:08:01 2017	
Calibrator Value:	1000.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	6.2	cps
Sensitivity:	0.5200	GAPI/cps

Calibration Report

Database File	thomas garner_garner 8.db
Dataset Pathname	MEL/pass2
Dataset Creation	Tue Nov 20 11:40:51 2018

Microlog Calibration Report

Serial-Model: Armadillo-1-Armadillo
Performed: Fri Nov 18 11:19:49 2016

	Readings			References			Results	
	Zero	Cal		Zero	Cal		m	b
Normal	0.0122	1.0361	V	0.0000	10.0000	Ohm-m	35.0000	-2.0000
Inverse	-0.0037	0.9549	V	0.0000	10.0000	Ohm-m	25.0000	-0.6000
Caliper	1.1139	8.3644	V	5.0000	19.0000	in	1.9309	3.7493

PIONEER
Pioneer Energy Services

Company	THOMAS GARNER, INC.
Well	GARNER #8
Field	LEISS NW
County	STAFFORD
State	KANSAS