



# PEAK WIRELINE SERVICES, INC.

## DUAL SPACED CEMENT BOND LOG

Company: MULL DRILLING COMPANY, INC.  
Well: COMSTOCK #1-4

Field: WILDCAT  
County: CLARK  
State: KANSAS

Location: 1795 FSJ & 2200 F/WL  
C/N/E NE  
SEC 4 TWP 33S RGE 22W

Permanent Datum: GROUND LEVEL Elevation: 2200  
Log Measured From: KELLY BUSHING  
Drilling Measured From: KELLY BUSHING

Date: 8-5-2019  
Run Number: 4796  
Depth: 4860  
Bottom Logged Interval: 3480

Other Services: Elevation: K.B. 2211 D.F. 2209 G.L. 2200

Estimated Cement Top: 3640

Time Last Read: Bottom  
Checked By: CHEYENNE WELLS, JOC  
Equipment Number: HENDERSON  
Recorded By: BILL STOLZ

Run Number: 0  
Bit Size: 7/8" 810  
TWC: 0 4752

Casing Record: 8100  
Spiral String: 8100  
Foundation String: 4172'

Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200



Collar Locator: 9  
GR (GAPI): 0

Amplitude (mV): 0 100 200  
Travel Time (usec): 800 200

Variable Density: 1200

