



MIDWEST WIRELINE

DUAL INDUCTION LOG

Company **Cholla Production, LLC**
 Well **Zimmerman-Elmore Unit #1-3**
 Field **District 30**
 County **Rush** State **Kansas**

Company **Cholla Production, LLC**
 Well **Zimmerman-Elmore Unit #1-3**
 Field **District 30**
 County **Rush**
 State **Kansas**

Location: **95' FNL & 1300' FWL**
 Permanent Datum **SEC 3 TWP 16S RGE 20W**
 Log Measured From **Kelly Bushing** Ground Level **Elevation 2157'**
 Drilling Measured From **Kelly Bushing** Elevation **2157'**
 Other Services **CNL/CDL MEL**
 Elevation **2165'**
 K.B. **N/A**
 D.F. **N/A**
 G.L. **2157'**

Date	9/4/2020
Run Number	One
Depth Driller	3839'
Depth Logger	3836'
Bottom Logged Interval	3835'
Top Log Interval	1350'
Casing Driller	8.625" @ 1391'
Casing Logger	1390'
Bit Size	7.875"
Type Fluid in Hole	Chemical
Salinity, ppm CL	7900
Density / Viscosity	9.3 59
pH / Fluid Loss	10.0 8.8
Source of Sample	FLOWLINE
Rm @ Meas. Temp	0.40 @ 80
Rmt @ Meas. Temp	0.30 @ 80
Rmc @ Meas. Temp	0.54 @ 80
Source of Rmf / Rmc	CHARTS
Rm @ BHT	0.28 @ 114
Operating Rig Time	3 Hours
Max Rec. Temp. F	114
Equipment Number	P-24
Location	HAYS
Recorded By	D. Schmidt
Witnessed By	Charles Sturdavant

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and Midwest Wireline LLC cannot and does not guarantee the accuracy or correctness of any interpretation, and Midwest Wireline LLC will not be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees.

Comments

N/A DENOTES NOT AVAILABLE OR NON-APPLICABLE.

Schoenchen,
 11 West, 1 South, 1/2 West,
 South into

Log Measured From: Kelly Bushing 8 Ft. Above Permanent Datum

THANK YOU FOR USING MIDWEST WIRELINE LLC
 785-625-3858

Your Midwest Wireline Crew

Engineer: D. Schmidt
 Operator:
 Operator:
 Operator:

This Log Record Was Witnessed By

Primary Witness: Charles Sturdavant
 Secondary Witness:
 Secondary Witness:
 Secondary Witness:

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb)
GR	40.58		GR-M&W (233-M&W)	3.00	3.50	50.00
CNLSC CNSSC	37.48 36.73		CNT-M&W (207-MW)	5.50	3.50	100.00
LSD DCAL SSD	28.43 28.42 27.93		CDL-M&W (817-947)	8.50	4.00	250.00
MCAL MI MN	19.83 19.83 19.83		ML-PSIML (PSI-01) GO Micro log tools converted to Simplec electronics	7.58	4.00	65.00
RLL3F RLL3	15.80 15.80					
CILD	8.00		DIL-PSI HIGH TEMP (952-828)	18.50	3.50	220.00
CILM	4.70					
SP	0.20					

Dataset: cholla_zimmerman elmore unit_1-3.db: field/well/STKML/pass3.1
 Total length: 43.08 ft
 Total weight: 685.00 lb
 O.D.: 4.00 in

Log Variables

DatabaseC:\ProgramData\Warrior\Data\cholla_zimmerman elmore unit_1-3.db
 Dataset field/well/STKML/pass3.1/_vars_

Top - Bottom

A	BOREID in	BOTTEMP degF	CASEOD in	CASETHCK in	FLUIDDEN g/cc	M	MATRXDEN g/cc
1	7.875	100	5.5	0	1	2	2.71
NPORSEL	PERFS	SNDERR mmho/m	SNDERRM mmho/m	SPSHIFT mV	SRFTEMP degF	SZCOR	TDEPTH ft
Limestone	0	0	0	197	0	Off	0

Variable Description

A : Cement Factor (a)
 BOREID : Borehole I.D.
 BOTTEMP : Bottom Hole Temperature
 CASEOD : Casing O.D.
 CASETHCK : Casing Thickness
 FLUIDDEN : Fluid Density
 M : Cement Exp (m)
 MATRXDEN : Matrix Density


NPORSEL : Neutron Porosity Curve Select
 PERFS : Perforation Flag
 SNDERR : Deep Sonde Error Correction
 SNDERRM : Medium Sonde Error Correction
 SPSHIFT : S.P. Baseline Offset
 SRFTEMP : Surface Temperature
 SZCOR : CN Size Cor. ?
 TDEPTH : Total Depth






MAIN PASS

Database File cholla_zimmerman elmore unit_1-3.db
 Dataset Pathname STKML/pass4.1
 Presentation Format _dil2in
 Dataset Creation Fri Sep 04 19:12:50 2020
 Charted by Depth in Feet scaled 1:600



GAMMA RAY (GAPI) 150	1000	CONDUCTIVITY (mmho/m)	0
	15000	Line Tension (lb)	0
	0	RLL3 (Ohm-m)	50
	0	RILD (Ohm-m)	50
	50	RLL3 (Ohm-m)	200
	50	Deep Resistivity (Ohm-m)	200












2050
2100
2150
2200
2250
2300
2350
2400
2450
2500
2550
2600











MAIN PASS

Database File cholla_zimmerman elmore unit_1-3.db
 Dataset Pathname STKML/pass4.1
 Presentation Format _dil
 Dataset Creation Fri Sep 04 19:12:50 2020
 Charted by Depth in Feet scaled 1:240


0	GAMMA RAY (GAPI)	150	0.2	DEEP RESISTIVITY (Ohm-m)	2000
-200	SP (mV)	0	0.2	MEDIUM RESISTIVITY (Ohm-m)	2000
			0.2	RLL3 (Ohm-m)	2000
			10000	LINE TENSION (lb)	0





1450

0	GAMMA RAY (GAPI)	150
-200	SP (mV)	0



0.2	DEEP RESISTIVITY (Ohm-m)	2000
0.2	MEDIUM RESISTIVITY (Ohm-m)	2000
0.2	RLL3 (Ohm-m)	2000
10000	LINE TENSION (lb)	0




MIDWEST WIRELINE

MAIN PASS

Database File cholla_zimmerman elmore unit_1-3.db
 Dataset Pathname STKML/pass3.1
 Presentation Format _dil
 Dataset Creation Fri Sep 04 18:22:33 2020
 Charted by Depth in Feet scaled 1:240


0	GAMMA RAY (GAPI)	150
-200	SP (mV)	0


0.2	DEEP RESISTIVITY (Ohm-m)	2000
0.2	MEDIUM RESISTIVITY (Ohm-m)	2000
0.2	RLL3 (Ohm-m)	2000
10000	LINE TENSION (lb)	0



2950

3000






3050


3100

3150

3200

3250







3300

3350

3400

3450







3500

3550

3600

3650






REPEAT SECTION

Database File cholla_zimmerman elmore unit_1-3.db
 Dataset Pathname STKML/pass2.1
 Presentation Format _dil
 Dataset Creation Fri Sep 04 18:09:57 2020
 Charted by Depth in Feet scaled 1:240



SP (mV) -200 0

MEDIUM RESISTIVITY (Ohm-m) 0.2 2000
RLL3 (Ohm-m) 0.2 2000
LINE TENSION (lb) 10000 0




3650

3700

3750

3800



GAMMA RAY (GAPI) 0 150

DEEP RESISTIVITY (Ohm-m) 0.2 2000

GAMMA RAY (GAPI)	150
-200 SP (mV)	0

0.2	DEEP RESISTIVITY (Ohm-m)	2000
0.2	MEDIUM RESISTIVITY (Ohm-m)	2000
0.2	RLL3 (Ohm-m)	2000
10000	LINE TENSION (lb)	0

Calibration Report

Database File cholla_zimmerman elmore unit_1-3.db
 Dataset Pathname STKML/pass3.1
 Dataset Creation Fri Sep 04 18:22:33 2020

Dual Induction Calibration Report

Serial-Model: 952-828-PSI HIGH TEMP
 Calibration Performed: Sun Jun 28 08:39:24 2020

Loop:	Readings		References			Results	
	Air	Loop	Air	Loop		Gain	Offset
Deep	167.000	835.000	0.000	255.000	mmho/m	0.455	-32.000
Medium	0.000	1348.000	142.000	255.000	mmho/m	0.325	-28.000

Microlog Calibration Report

Serial-Model: PSI-01-PSIML
 Performed: Tue Jun 16 01:32:04 2020

	Readings		References			Results	
	Zero	Cal	Zero	Cal		m	b
Normal	0.0000	1.0000	0.0000	1.0000	Ohm-m	14000.0000	-1.8500
Inverse	0.0000	1.0000	0.0000	1.0000	Ohm-m	15000.0000	-1.3000
Caliper	1.0033	1.0841	5.0000	16.5000	in	142.3500	-138.3500

Compensated Density Calibration Report

Serial-Model: 817-947-M&W
 Source / Verifier: 16955B / 2ci
 Master Calibration Performed: Tue Sep 24 21:18:50 2019

Master Calibration

	Density		Far Detector	Near Detector	
Magnesium	1.755	g/cc	6127.15	5922.31	cps
Aluminum	2.680	g/cc	1141.85	3762.09	cps
Spine Angle = 74.89			Density/Spine Ratio = 0.532		
	Size		Reading		
Small Ring	4.50	in	1.02		
Large Ring	14.50	in	1.23		

Compensated Neutron Calibration Report

Serial Number: 207-MW
 Tool Model: M&W
 Calibration Performed: WED FEB 12 10:20:20 2010

Detector	Readings	Target	Normalization
Short Space	6240.00 cps	1000.00 cps	1.6025
Long Space	460.00 cps	1000.00 cps	1.9500

Gamma Ray Calibration Report

Serial Number:	233-M&W	
Tool Model:	M&W	
Calibration Performed:	Fri Feb 07 01:42:40 2014	
Calibrator Value:	1.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	1.0	cps
Sensitivity:	0.5500	GAPI/cps