Company: Jason Oil Co, LLC
Well: Russell
Field: Trask
County: Kansas
State: Kansas
Permanent Datum: Ground Level
Elevation: 2,251 ft
Log Measured From: Kelly Bushing
Drilling Measured From: Kelly Bushing
Elevation: K.B. 2,261 ft, G.L. 2,251 ft
Date: 10-Feb-21
Run Number: ONE
Depth-Driller: 3,600 ft
Depth-Logger: 3,600 ft
Bottom Logged Interval: 3,600 ft
Top Logged Interval: 3,000 ft
Casing-Driller: 8.625 in @ 1,700 ft
Casing-Logger: 8.625 in @ 1,700 ft
Bit Size: 7.875 in
Type Fluid in Hole: Water Based Mud
Density: 9.2 lb/gal
Viscosity: 50 s/qt
pH: 10.5
Fluid Loss: 8.4 cc
Source of Sample: Flowline
Rm @ Measured Temp: 0.2 @ 70 °F
Rmf @ Measured Temp: 0.15 @ 70 °F
Rmc @ Measured Temp: 0.3 @ 70 °F
Source of Rmf and Rmc: Calculated
Rm @ BHT: 0.1 @ 120 °F
Time Since Circulation: 12 hrs
Max Rec. Temp.: 120 °F
Equipment Number: 3
Location: Sec 1 Twp 19S Rge 22W
Recorded By: Jason Oil Co, LLC
Witnessed By: Russell, Kirk

Run 1 Data Only


All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions as set out in our current Price Schedule.

Comments


Russell, KS South on 281 Hwy. To Mitchell Rd(4mi), 1/2 West on Mitchell Rd
North Into Location

Thanks for using Gemini Wireline LLC
785-625-1102

MAIN PASS



REPEAT SECTION



Calibration Report

Database File jonsrv4finh.db
Dataset Pathname pass1
Dataset Creation Mon Aug 09 19:15:39 2021

Dual Induction Calibration Report

Serial Number	1402,4254
Surface Cal Performed	Sun Feb 14 09:56:32 2016
Internal Cal Performed	Sun Feb 14 09:56:32 2016
After Survey Verification Performed	Sun Feb 14 10:36:32 2016

Surface Calibration

	Readings			References			Results	
	Air	Loop		Air	Loop		m	b
Long	0.018	0.653	%	0.000	150.000	mmho/m	159.479	-8.948
Medium	0.003	0.768	%	0.000	450.000	mmho/m	522.407	-1.745
	Internal			Zero	Cal		m	b
Deep	0.018	0.613	%	0.000	150.000	mmho/m	530.040	-8.948
Medium	0.003	0.768	%	0.000	450.000	mmho/m	718.637	-2.088

Downhole Calibration

	Readings			References			Results	
	Internal	Zero	Cal	Zero	Cal		m	b
Deep	0.018	599.808	mmho/m	0.000	599.810	mmho/m	1.000	0.124
Medium	0.118	399.722	mmho/m	0.000	399.740	mmho/m	1.000	0.124
Shallow	0.000	0.000	Ohm-m	500.000	500.000	Ohm-m	1.000	0.000

After Survey Verification

	Readings			Targets			m	b
	Internal	Zero	Cal	Zero	Cal			
Deep	0.000	0.000	mmho/m	0.000	599.808	mmho/m	1.000	0.124
Medium	0.000	0.000	mmho/m	0.000	399.722	mmho/m	1.000	0.124
Shallow	0.000	0.000	Ohm-m	500.000	0.000	Ohm-m	1.000	0.000

Neutron Calibration Report

Serial Number	N3K139
Tool Model	NGRT3138
Cal Performed	Sun Feb 14 10:36:32 2016
Calibrator Value	NAPI
Calibrator Reading	1
Sensitivity	NAPI/cps

Temperature Calibration Report

Serial Number	2002457
Cal Performed	Fri Apr 16 12:15:34 2016

	Reference	Reading	
Low Reference	0.00	0.00	degF
High Reference	200.00	1.00	degF
Gain	1.00		
Offset	0.00		
Data Spacing	0.1		

Inclinometer Calibration Report

Performed	Mon May 3 15:02:48 2021			
	Low Read.	High Read.	Low Ref.	High Ref.
X Accelerometer	205.00	1843.00	-1.00	1.00 g/a
Y Accelerometer	205.00	1843.00	-1.00	1.00 g/a
Z Accelerometer				g/a

Gamma Ray Calibration Report

Serial Number	2660SC
Tool Model	SGRJ
Cal Performed	Wed Sep 8 19:21:08 2021
Calibrator Value	1.0 GAPI
Background Reading	0.0 cps
Background Reading	0.0 GAPI/cps
Sensitivity	1.0000 GAPI/cps

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb)
			CHD-STC	0.50	1.69	1.00
GR	39.71		HNGS-A			
AUCH	37.54		ECAT-HNGS-A(A00) Hsng/ Sleeve(s) 500-Mudcal	4.58	3.50	120.00
AUCA	37.54					
PSTC	36.29					
PSTA	36.29					
ASTAT	36.29					
NEU	31.38		NGJ-A(A00)/TSJ-B(A00)/SS Sensor Set(1.22)(TSJ)	5.65	3.50	50.00
NEU	31.38					
			CDL-SDA/HNGRT (2021)	9.69	4.00	240.00
LSD	22.52					
SSD	21.46					
SND	21.46					
SP	10.60		SL-A(A00-ONE)	19.71	4.00	300.00
CILD	10.60		Dual Induction			
CILM	8.89					
RLL3	1.70					

Dataset: jonsrv4finh.db: NaN/null/run1/pass1 1
Total length: 30.13 ft
Max OD: 4.00 in
Max weight: 910.00 lb