
Company: Texaco Inc.
Well: Texaco Inc. #1
Field: Wildcat
County: Lincoln
State: Nevada
Location: 1980' FSL & 660' FEL
Sec. 14, T. 3 S., R. 68 E.
Permanent Datum: Ground Level
Elevation: 5,847 ft
Log Measured From: KB
Drilling Measured From: KB
Elevation: KB 5,862 ft
DF 5,861 ft
GL 5,847 ft
Date: 03-Jul-1978
Run No.: ONE
Depth Driller: 12,450 ft
Depth Logger: 12,448 ft
Bottom Log Interval: 12,446 ft
Top Log Interval: 1,200 ft
Casing Driller: 13 3/8 in @ 1,200 ft
Casing Logger: 1,198 ft
Bit Size: 12 1/4 in
Type Fluid in Hole: Gel-Chem Mud
Density: 10.2 lb/gal
Viscosity: 42 s
Fluid Loss: 6.8 cc
Source of Sample: Flowline
Rm @ Meas. Temp: 0.62 @ 118 °F
Rmf @ Meas. Temp: 0.48 @ 118 °F
Rmc @ Meas. Temp: 0.74 @ 118 °F
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.31 @ 198 °F
Time Since Circ.: 14 hr
Max Rec. Temp.: 198 °F
Equip. No.: 4417
Location: Pioche, NV
Recorded By: J. Whitfield
Witnessed By: R. Calloway
RUN 1
Bit Run: 1
Type: 12 1/4 in Tricone
Size: 12.250 in
From: 1,200 ft
To: 12,450 ft
Total Depth: 12,450 ft
Weight: 38 lb/ft
Grade: N-80
Type Joint: LT&C
Top: 0 ft
Bottom: 1,198 ft
Number of Joints: 28
Type: 9 5/8 in Intermediate
Size: 9.625 in
From: 0 ft
To: 8,412 ft
Weight: 47 lb/ft
Grade: S-95
Type Joint: LT&C
Top: 0 ft
Bottom: 8,412 ft
Number of Joints: 199
Type: 7 in Liner
Size: 7.000 in
From: 8,210 ft
To: 12,446 ft
Weight: 29 lb/ft
Grade: P-110
Type Joint: LT&C
Top: 8,210 ft
Bottom: 12,446 ft
Number of Joints: 109
Type: 5 in Drill Pipe
Size: 5.000 in
From: 0 ft
To: 12,450 ft
Weight: 19.5 lb/ft
Grade: S-135
Type Joint: NC50
Top: 0 ft
Bottom: 12,450 ft
Number of Joints: 396
Type: 6 1/2 in Drill Collar
Size: 6.500 in
From: 12,420 ft
To: 12,450 ft
Weight: 120 lb/ft
Grade: —
Type Joint: NC50
Top: 12,420 ft
Bottom: 12,450 ft
Number of Joints: 10
Type: 8 in Drill Collar
Size: 8.000 in
From: 12,390 ft
To: 12,420 ft
Weight: 175 lb/ft
Grade: —
Type Joint: NC50
Top: 12,390 ft
Bottom: 12,420 ft
Number of Joints: 10
Type: 12 1/4 in Tricone
Size: 12.250 in
From: 1,200 ft
To: 12,450 ft
Total Depth: 12,450 ft
Weight: 38 lb/ft
Grade: N-80
Type Joint: LT&C
Top: 0 ft
Bottom: 1,198 ft
Number of Joints: 28
Type: 9 5/8 in Intermediate
Size: 9.625 in
From: 0 ft
To: 8,412 ft
Weight: 47 lb/ft
Grade: S-95
Type Joint: LT&C
Top: 0 ft
Bottom: 8,412 ft
Number of Joints: 199
Type: 7 in Liner
Size: 7.000 in
From: 8,210 ft
To: 12,446 ft
Weight: 29 lb/ft
Grade: P-110
Type Joint: LT&C
Top: 8,210 ft
Bottom: 12,446 ft
Number of Joints: 109
Type: 5 in Drill Pipe
Size: 5.000 in
From: 0 ft
To: 12,450 ft
Weight: 19.5 lb/ft
Grade: S-135
Type Joint: NC50
Top: 0 ft
Bottom: 12,450 ft
Number of Joints: 396
Type: 6 1/2 in Drill Collar
Size: 6.500 in
From: 12,420 ft
To: 12,450 ft
Weight: 120 lb/ft
Grade: —
Type Joint: NC50
Top: 12,420 ft
Bottom: 12,450 ft
Number of Joints: 10
Type: 8 in Drill Collar
Size: 8.000 in
From: 12,390 ft
To: 12,420 ft
Weight: 175 lb/ft
Grade: —
Type Joint: NC50
Top: 12,390 ft
Bottom: 12,420 ft
Number of Joints: 10
Texaco Inc.
Texaco Inc. #1
Wildcat
Lincoln
Nevada
1980' FSL & 660' FEL
Sec. 14, T. 3 S., R. 68 E.
Ground Level
KB
DF
GL
03-Jul-1978
ONE
12,448 ft
12,446 ft
1,200 ft
1,198 ft
12 1/4 in @ 1,200 ft
Gel-Chem Mud
10.2 lb/gal
42 s
6.8 cc
Flowline
0.62 @ 118 °F
0.48 @ 118 °F
0.74 @ 118 °F
Measured
Measured
0.31 @ 198 °F
14 hr
198 °F
4417
Pioche, NV
J. Whitfield
R. Calloway
1
12 1/4 in Tricone
12.250 in
1,200 ft
12,450 ft
12,450 ft
38 lb/ft
N-80
LT&C
0 ft
1,198 ft
28
9 5/8 in Intermediate
9.625 in
0 ft
8,412 ft
47 lb/ft
S-95
LT&C
0 ft
8,412 ft
199
7 in Liner
7.000 in
8,210 ft
12,446 ft
29 lb/ft
P-110
LT&C
8,210 ft
12,446 ft
109
5 in Drill Pipe
5.000 in
0 ft
12,450 ft
19.5 lb/ft
S-135
NC50
0 ft
12,450 ft
396
6 1/2 in Drill Collar
6.500 in
12,420 ft
12,450 ft
120 lb/ft
—
NC50
12,420 ft
12,450 ft
10
8 in Drill Collar
8.000 in
12,390 ft
12,420 ft
175 lb/ft
—
NC50
12,390 ft
12,420 ft
10
TEXACO INC.
Texaco Inc. #1
Wildcat Field
Lincoln County, Nevada
1980' FSL & 660' FEL
Sec. 14, T. 3 S., R. 68 E.
Elevation: KB 5,862 ft
DF 5,861 ft
GL 5,847 ft
Permanent Datum: Ground Level
Log Measured From: KB
Drilling Measured From: KB
Run No.: ONE
Date: 03-Jul-1978
Depth Driller: 12,450 ft
Depth Logger: 12,448 ft
Bottom Log Interval: 12,446 ft
Top Log Interval: 1,200 ft
Casing Driller: 13 3/8 in @ 1,200 ft
Casing Logger: 1,198 ft
Bit Size: 12 1/4 in
Type Fluid in Hole: Gel-Chem Mud
Density: 10.2 lb/gal
Viscosity: 42 s
Fluid Loss: 6.8 cc
Source of Sample: Flowline
Rm @ Meas. Temp: 0.62 @ 118 °F
Rmf @ Meas. Temp: 0.48 @ 118 °F
Rmc @ Meas. Temp: 0.74 @ 118 °F
Source of Rmf: Measured
Source of Rmc: Measured
Rm @ BHT: 0.31 @ 198 °F
Time Since Circ.: 14 hr
Max Rec. Temp.: 198 °F
Equip. No.: 4417
Location: Pioche, NV
Recorded By: J. Whitfield
Witnessed By: R. Calloway
RUN 1
Bit Run: 1
Type: 12 1/4 in Tricone
Size: 12.250 in
From: 1,200 ft
To: 12,450 ft
Total Depth: 12,450 ft
Weight: 38 lb/ft
Grade: N-80
Type Joint: LT&C
Top: 0 ft
Bottom: 1,198 ft
Number of Joints: 28
Type: 9 5/8 in Intermediate
Size: 9.625 in
From: 0 ft
To: 8,412 ft
Weight: 47 lb/ft
Grade: S-95
Type Joint: LT&C
Top: 0 ft
Bottom: 8,412 ft
Number of Joints: 199
Type: 7 in Liner
Size: 7.000 in
From: 8,210 ft
To: 12,446 ft
Weight: 29 lb/ft
Grade: P-110
Type Joint: LT&C
Top: 8,210 ft
Bottom: 12,446 ft
Number of Joints: 109
Type: 5 in Drill Pipe
Size: 5.000 in
From: 0 ft
To: 12,450 ft
Weight: 19.5 lb/ft
Grade: S-135
Type Joint: NC50
Top: 0 ft
Bottom: 12,450 ft
Number of Joints: 396
Type: 6 1/2 in Drill Collar
Size: 6.500 in
From: 12,420 ft
To: 12,450 ft
Weight: 120 lb/ft
Grade: —
Type Joint: NC50
Top: 12,420 ft
Bottom: 12,450 ft
Number of Joints: 10
Type: 8 in Drill Collar
Size: 8.000 in
From: 12,390 ft
To: 12,420 ft
Weight: 175 lb/ft
Grade: —
Type Joint: NC50
Top: 12,390 ft
Bottom: 12,420 ft
Number of Joints:


Drilling Rig (m/hr)
Torque (Kft-lbs)
Hookload (klbs)
Rotary RPM
Surface WOB (klbs)
Standpipe Pressure (psi)
Flow In (gpm)
Flow Out (gpm)
Pit Volume (bbl)
Gamma Ray (API)
Resistivity (ohm.m)
Density (g/cm3)
Neutron Porosity (%)
Hole Depth (ft)
Bit Depth (ft)
Vertical Depth (ft)
Depth (ft)
Time
Date
Connection Gas (units)
Total Gas (units)
Bit Run
Formation
Lithology
Description
Cum Vol
ROP
WOB
RPM
TQ
Bit Weight
Hole Size
Mud Wt
Mud Type
Mud Loss
Mud Gas
Mud Chlorides
Mud Solids
Mud Oil
Mud Water
Mud Sand
Mud Viscosity
Mud Yield Point
Mud Gel Strength
Mud Filtrate
Mud Filter Cake
Mud pH
Mud Alkalinity
Mud Calcium
Mud Magnesium
Mud Potassium
Mud Lime
Mud Chromium
Mud Glycol
Mud Salinity
Mud Temperature
Mud Resistivity
Mud Density
Mud Oil/Water Ratio
Mud Solids Content
Mud Water Content
Mud Oil Content
Mud Sand Content