DUAL INDUCTION LOG

Company	M G Oil Inc.
Well	Lawrence-Dixon Unit #1
Field	N & J
County	Lane
State	Kansas
Location:	1526' FNL & 2198' FWL SEC. 15 TWP. 18S RGE. 28W API # 15-101-22660
Date	3-Nov-21
Run Number	ONE
Depth Driller	4500
Depth Logger	4500
Bottom Logged Interval	4497
Top Log Interval	250
Casing Driller	8 5/8" @ 247
Casing Logger	247
Bit Size	7 7/8"
Type Fluid in Hole	Chemical LSD gelm
Density / Viscosity	9.4/53
PH / Fluid Loss	10.5 / 8
Source of Sample	Pit
Rm @ Meas. Temp	1.48@70
Rmf @ Meas. Temp	1.12@70
Rmc @ Meas. Temp	1.85@70
Source: Rmf / Rmc	CALCULATED / CALCULATED
Rm @ BHT	1.03@117
Time Circ. on Bottom	11:00
Time Logger on Bottom	11:45
Equipment Number	10-5
Location	Hays, KS
Recorded By	C.Pearson
Witnessed By	Mr. Dale Cavers

Elevations: KB: 2807 DF: 2806 GL: 2798

Measured From: KB 6' AGL

All Depths Are Measured From Drilling Measure Point

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Shields,KS East Side North on Laredo Rd. 3 mi. to 280th,
East on 280th 1.8 mi. to Newton Rd. South to East into Location

LAT/LONG
38.6655221,-100.4056943

Thanks for using Gemini Wireline LLC
785-625-1182

MAIN PASS

Database File mgolawrence-dixonunit#1oh.db
Dataset Pathname pass5
Presentation Format kdil
Dataset Creation Fri Nov 05 11:23:49 2021
Charted by Depth in Feet scaled 1:600

0	GR (GAPI)	150	
-100	SP (mV)	100	
1000	CILD (mmho/m)	0	
10000	LTEN (lb)	0	
0	RILD (Ohm-m)	50	
0	RLL3 (Ohm-m)	50	
50	RILD x 10 (Ohm-m)	500	
50	RLL3 x 10 (Ohm-m)	500	

Gamma Ray Calibration Report

Serial Number:	WithMC	
Tool Model:	WMC	
Performed:	Wed May 5 19:21:08 2021	
Calibrator Value:	1.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	1.0	cps
Sensitivity:	1.0000	GAPI/cps

Sensor	Offset (ft)
GR	38.77
ACCY	37.60
ACCX	37.60
SSTAT	37.19
PSTAT	36.35
ASTAT	36.35
GRD	35.52
TEMP	35.52
NEU	31.49
LStat	22.54
LS8	21.88
LS7	21.88
LS6	21.88
LS5	21.88
LS4	21.88
LS3	21.88
LS2	21.88
LS1	21.88
LSV	21.88
LSD	21.86
SSV	21.67
SS8	21.67
SS7	21.67
SS6	21.67
SS5	21.67
SS4	21.67
SS3	21.67
SS2	21.67
SS1	21.67
DCAL	21.61
SSD	21.27
SP	10.60
CILD	10.60
CILM	6.89
RLL3	1.70
TR_Mon	0.00

Schematic



Description	Length (ft)	O.D. (in)	Weight (lb)
CHD-STD	0.50	1.69	1.00
ADT-WMC (WithMC) Admyr Telemetry With Mudcell	4.58	3.50	120.00
NEU-ADMY5139 (AD5139) Admyer NEU DIGITAL	5.65	3.50	50.00
ADT1LITH-A (2388LITHO) Admyr Litho Density Tool	9.75	3.50	240.00
DIL-ADM (1842) Dual Induction	19.71	4.00	300.00

Dataset:	mgolawrence-dixonunit#1oh.db: field/well/run1/pass5
Total length:	40.19 ft
Total weight:	711.00 lb
O.D.:	4.00 in