



MIDWEST WIRELINE

MICRORESISTIVITY LOG

Company Griffin Management, LLC
 Well Whitley #4
 Field Moffett West
 County Barber
 State Kansas

Company Griffin Management, LLC
 Well Whitley #4
 Field Moffett West
 County Barber
 State Kansas

Location: 900 FNL & 2635 FEL
 SEC 8 TWP 30S RGE 15W
 API #: 15-007-24452-00-00
 Permanent Datum Ground Level Elevation 1936
 Log Measured From Kelly Bushing
 Drilling Measured From Kelly Bushing

Other Services
 CNL/CDL
 DIL
 Elevation
 K.B. 1941
 D.F.
 G.L. 1936

Date	11/20/2022
Run Number	One
Depth Driller	4875
Depth Logger	4873
Bottom Logged Interval	4872
Top Log Interval	2800
Casing Driller	8.625 @ 260
Casing Logger	260
Bit Size	7.875
Type Fluid in Hole	Chemical
Salinity, ppm CL	5000
Density / Viscosity	9.5 47
pH / Fluid Loss	10.0 9.0
Source of Sample	Flowline
Rm @ Meas. Temp	0.40 @ 50
Rmt @ Meas. Temp	0.30 @ 50
Rmc @ Meas. Temp	0.54 @ 50
Source of Rmf / Rmc	Charts
Rm @ BHT	0.16 @ 125
Operating Rig Time	3 Hours
Max Rec. Temp. F	125
Equipment Number	P-24
Location	Hays
Recorded By	D. Schmidt
Witnessed By	Charles Griffin

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and Midwest Wireline LLC cannot and does not guarantee the accuracy or correctness of any interpretation, and Midwest Wireline LLC will not be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees.

Comments

N/A DENOTES NOT AVAILABLE OR NON-APPLICABLE.

Croft,
 South to 110, East to 130,
 South to location

Log Measured From: Kelly Bushing 5 Ft. Above Permanent Datum

THANK YOU FOR USING MIDWEST WIRELINE LLC
 785-625-3858

Your Midwest Wireline Crew

Engineer: D. Schmidt
 Operator:
 Operator:
 Operator:

This Log Record Was Witnessed By

Primary Witness: Charles Griffin
 Secondary Witness: Eli Felts
 Secondary Witness:
 Secondary Witness:

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb)
GR	40.33		GR-M&W (106)	3.00	3.50	50.00
CNLSC CNSSC	37.23 36.48		CNT-M&W (207-MW)	5.00	3.50	100.00
LSD DCAL SSD	28.18 28.17 27.68		CDL-M&W (305-24)	8.50	4.00	250.00
MCAL MI MN	19.58 19.58 19.58		ML-PSIML (401)	7.58	4.00	65.00
RLL3F RLL3	15.50 15.50					
CILD	8.33		DIL-M&W (502 HT)	18.25	3.50	220.00
CILM	4.50					
SP	0.20					

Dataset: griffin_whitley 4.db: field/well/stkml/pass4.11
 Total length: 42.33 ft
 Total weight: 685.00 lb
 O.D.: 4.00 in

Log Variables

DatabaseC:\ProgramData\Warrior\Data\griffin_whitley 4.db
Dataset field/well/stkml/pass4.11/_vars_

Top - Bottom

A	BOREID in	BOTTEMP degF	CASEOD in	CASETHCK in	FLUIDDEN g/cc	M	MATRXDEN g/cc
1	7.875	125	5.5	0	1	2	2.71
NPORSEL	PERFS	SNDERR mmho/m	SNDERRM mmho/m	SPSHIFT mV	SRFTEMP degF	SZCOR	TDEPTH ft
Limestone	0	0	0	280	40	Off	4873

Variable Description

A : Cement Factor (a)
BOREID : Borehole I.D.
BOTTEMP : Bottom Hole Temperature
CASEOD : Casing O.D.
CASETHCK : Casing Thickness
FLUIDDEN : Fluid Density
M : Cement Exp (m)
MATRXDEN : Matrix Density

NPORSEL : Neutron Porosity Curve Select
PERFS : Perforation Flag
SNDERR : Deep Sonde Error Correction
SNDERRM : Medium Sonde Error Correction
SPSHIFT : S.P. Baseline Offset
SRFTEMP : Surface Temperature
SZCOR : CN Size Cor. ?
TDEPTH : Total Depth




DETAIL SECTION

MAIN PASS

Database File griffin_whitley 4.db
Dataset Pathname stkml/pass4.1
Presentation Format _micro
Dataset Creation Sun Nov 20 23:31:53 2022
Charted by Depth in Feet scaled 1:240


0	Gamma Ray (GAPI)	150
6	Caliper (in)	16
2.875	mcal (in)	7.875
-200	sp (mV)	0


0	Micro Inverse 1 X 1 (Ohm-m)	40
0	Micro Normal 2" (Ohm-m)	40
10000	Line Weight (lb)	0



2800

2850








2900

2950

3000

3050






3100


3150

3200

3250

3300







3350

3400

3450

3500







3550

3600

3650

3700






3750


3800

3850

3900

3950







4000

4050

4100

4150






4200


4250

4300

4350

4400







4450

4500

4550

4600






4650


4700

4750


4800

FR Gamma Ray








4850



REPEAT SECTION

REPEAT PASS


Database File griffin_whitley 4.db
 Dataset Pathname stkml/pass2.1
 Presentation Format _micro
 Dataset Creation Sun Nov 20 22:14:50 2022
 Charted by Depth in Feet scaled 1:240






4500

4550


4600







4850



0	Gamma Ray (GAPI)	150
6	Caliper (in)	16
2.875	mcal (in)	7.875
-200	sp (mV)	0

0	Micro Inverse 1 X 1 (Ohm-m)	40
0	Micro Normal 2" (Ohm-m)	40
10000	Line Weight (lb)	0

Calibration Report

Database File griffin_whitley 4.db
 Dataset Pathname stkml/pass4.11
 Dataset Creation Sun Nov 20 22:33:32 2022

Dual Induction Calibration Report

Serial-Model: 502 HT-M&W
 Surface Cal Performed: Mon Nov 7 15:53:48 2022

Loop:	Readings		References		Results	
	Air	Loop	Air	Loop	m	b
Deep	83.639	487.104	0.000	255.800	mmho/m	0.454 -31.000
Medium	113.335	1585.690	0.000	255.800	mmho/m	0.350 -11.000

Microlog Calibration Report

Serial-Model: 401-PSIML
 Performed: Mon Nov 7 15:53:59 2022

	Readings		References		Results	
	Zero	Cal	Zero	Cal	m	b
Normal	0.0000	1.0000	0.0000	1.0000	Ohm-m	11500.0000 -0.6000
Inverse	0.0000	1.0000	0.0000	1.0000	Ohm-m	9500.0000 0.0000
Caliper	1.0052	1.0858	5.0000	16.5000	in	98.0000 -93.2200

Compensated Density Calibration Report

Serial-Model: 305-24-M&W
 Source #: 20762B
 Master Calibration Performed: Mon Jun 20 16:54:11 2022

Master Calibration

Density Far Detector Near Detector

	Density		Far Detector		Near Detector	
Magnesium	1.755	g/cc	4771.35	5494.27	cps	
Aluminum	2.650	g/cc	908.54	3539.54	cps	
Spine Angle = 75.15			Density/Spine Ratio = 0.522			
	Size		Reading			
Small Ring	4.00	in	1.74			
Large Ring	14.00	in	1.38			

Compensated Neutron Calibration Report

Serial Number:	207-MW
Tool Model:	M&W

CALIBRATION

Detector	Readings	Target	Normalization
Short Space	6240.00 cps	1000.00 cps	1.6025
Long Space	460.00 cps	1000.00 cps	1.9500

PRE-SURVEY VERIFICATION

	Detector	Readings	Measured	Target
1)	Short Space	cps		
	Long Space	cps	pu	pu
2)	Short Space	cps		
	Long Space	cps	pu	
3)	Short Space	cps		
	Long Space	cps	pu	

POST-SURVEY VERIFICATION

	Detector	Readings	Measured	Target
1)	Short Space	cps		
	Long Space	cps	pu	pu
2)	Short Space	cps		
	Long Space	cps	pu	pu
3)	Short Space	cps		
	Long Space	cps	pu	pu

Gamma Ray Calibration Report

Serial Number:	106
Tool Model:	M&W
Performed:	Fri Dec 3 15:10:46 2021
Calibrator Value:	500.0 GAPI
Background Reading:	24.0 cps
Calibrator Reading:	637.0 cps
Sensitivity:	0.5500 GAPI/cps



MIDWEST WIRELINE

Field	Moffett West
County	Barber
State	Kansas