



DUAL INDUCTION

MIDWEST WIRELINE

Company		Excilbur Production Co, Inc	
Well	Eshelman #2		
Field	Burrtton		
County	Reno	State	Kansas
Location:		API #: 15-155-21815-00-00	Other Services
SEC 36 TWP 23S RGE 4W		CNL/CDL	
Permanent Datum	Ground Level	Elevation	1461
Log Measured From	Kelly Bushing	K.B.	1473
Drilling Measured From	Kelly Bushing	D.F.	1461
Date 7/12/2025			
Run Number	One		
Depth Driller	3430		
Depth Logger	3431		
Bottom Logged Interval	3430		
Top Log Interval	650		
Casing Driller	8.625 @ 650		
Casing Logger	643		
Bit Size	7.875		
Type Fluid in Hole	Chemical		
Salinity, ppm CL	1650		
Density / Viscosity	9.05 48		
pH / Fluid Loss	11.0 8.0		
Source of Sample	Flowline		
Rm @ Meas. Temp	0.72 @ 74		
Rmt @ Meas. Temp	0.54 @ 74		
Rmc @ Meas. Temp	0.97 @ 74		
Source of Rmt / Rmc	Charts		
Rm @ BHT	0.48 @ 110		
Operating Rig Time	3 Hours		
Max Rec. Temp. F	110		
Equipment Number	110		
Location	Hays, KS		
Recorded By	D. Schmidt		
Witnessed By	Larry Ressler	Brandon Wolfe	

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and Midwest Wireline LLC cannot and does not guarantee the accuracy or correctness of any interpretation, and Midwest Wireline LLC will not be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees.

Comments

N/A DENOTES NOT AVAILABLE OR NON-APPLICABLE.

Burrtton,
West to Worthington Rd, 1 1/2 South,
East into

Log Measured From: Kelly Bushing

12 Ft. Above Permanent Datum

THANK YOU FOR USING MIDWEST WIRELINE LLC
785-625-3858

Your Midwest Wireline Crew

Engineer: D. Schmidt
Operator:
Operator:
Operator:

This Log Record Was Witnessed By

Primary Witness: Larry Ressler
Secondary Witness: Brandon Wolfe
Secondary Witness:
Secondary Witness:

Log Variables

DatabaseC:\ProgramData\Warrior\Data\excalibur_eshelman 2.db
Dataset field/well/stack/pass3.1/_vars_

Top - Bottom

A	BOREID	BOTTEMP	CASEOD	CASETHCK	FLUIDDEN	M	MATRXDEN
1	in	degF	in	in	g/cc	2	g/cc
	7.875	110	5.5	0	1		2.71
NPORSEL	PERFS	SNDERR	SNDERRM	SPSHIFT	SRFTEMP	SZCOR	TDEPTH
Limestone	No	mmho/m	mmho/m	mV	degF	Off	ft
		0	0	-120	75		3430





2" SCALE RESISTIVITY

MAIN PASS


Database File excalibur_eshelman 2.db
Dataset Pathname stack/pass3.3
Presentation Format _dil2in
Dataset Creation Sat Jul 12 08:59:17 2025
Charted by Depth in Feet scaled 1:600


0	Gamma Ray (GAPI)	150	1000	Conductivity (mmho/m)	0
			15000	Line Tension (lb)	0
			0	Shallow Resistivity (Ohm-m)	50
			0	Deep Resistivity (Ohm-m)	50
				Shallow Resistivity	
			50	(Ohm-m)	200
			50	Deep Resistivity (Ohm-m)	200





850
900
950
1000
1050
1100
1150
1200
1250
1300
1350





1400

1450

1500

1550

1600

1650


1700


1750

1800

1850

1900





1950

2000

2050

2100

2150

2200


2250



2300


2350

2400

2450








DETAIL SECTION

MAIN PASS

Database File excalibur_eshelman 2.db
Dataset Pathname stack/pass3.1
Presentation Format _dil
Dataset Creation Sat Jul 12 08:56:04 2025
Charted by Depth in Feet scaled 1:240

0	Gamma Ray (GAPI)	150
50	RXORT	250
-200	SP (mV)	0

0.2	Deep Resistivity (Ohm-m)	2000
0.2	Medium Resistivity (Ohm-m)	2000
0.2	RLL3 (Ohm-m)	2000
10000	Line Tension (lb)	0





2300

2350

2400

2450







2500

2550

2600

2650






2700


2750

2800

2850

2900







2950

3000

3050

3100






3150


3200

3250

3300

3350








MIDWEST WIRELINE

REPEAT SECTION

REPEAT PASS

Database File: excalibur_eshelman 2.db
 Dataset Pathname: stack/pass2.1
 Presentation Format: _dil
 Dataset Creation: Sat Jul 12 08:40:01 2025
 Charted by: Depth in Feet scaled 1:240






3250

3300

3350

3400



0.2

Deep Resistivity (Ohm-m)

2000

0.2

Medium Resistivity (Ohm-m)

2000

0.2

RLL3 (Ohm-m)

2000

10000

Line Tension (lb)

0

Database File		excalibur_eshelman 2.db		Calibration Report			
Dataset Pathname		stack/pass3.1					
Dataset Creation		Sat Jul 12 08:56:04 2025					
Dual Induction Calibration Report							
Serial-Model:				506-M&W			
Surface Cal Performed:				Thu Apr 3 15:09:39 2025			
		Readings		References		Results	
Loop:	Air	Loop		Air	Loop	m	b
Deep	84.211	428.152		0.000	255.800	mmho/m	0.480
Medium	141.000	670.654		0.000	255.800	mmho/m	-29.000
							-16.000
Compensated Density Calibration Report							
Serial-Model:				308-05-M&W			
Source #:				21170B			
Master Calibration Performed:				Wed May 14 15:44:32 2025			
Master Calibration							
		Density		Far Detector		Near Detector	
Magnesium	1.755	g/cc		5263.39	6024.11	cps	
Aluminum	2.570	g/cc		1137.62	4032.96	cps	
Spine Angle = 75.32				Density/Spine Ratio = 0.515			
		Size		Reading			
Small Ring	6.00	in		1.03			
Large Ring	14.00	in		1.15			
Compensated Neutron Calibration Report							
Serial Number:				210			
Tool Model:				M&W			
CALIBRATION							
Detector		Readings		Target		Normalization	
Short Space		6240.00	cps	1000.00	cps	1.6025	
Long Space		460.00	cps	1000.00	cps	1.9500	
Gamma Ray Calibration Report							
Serial Number:		105					
Tool Model:		M&W					
Performed:		Sat Oct 21 23:48:19 2023					
Calibrator Value:		500.0		GAPI			
Background Reading:		24.0		cps			
Calibrator Reading:		637.0		cps			
Sensitivity:		0.6000		GAPI/cps			



MIDWEST WIRELINE

Company	Excalibur Production Co, Inc
Well	Eshelman #2
Field	Burrton
County	Reno
State	Kansas