GAMMA RAY
NEUTRON
COMPLETION LOG

CORNISH
WIRELINE
SERVICES, INC.
CHANUTE, KANSAS

Company	TAILWATER, INC.
Well	WHITESIDE #7-IW
Field	GARNETT SHOESTRING
County	ANDERSON State KANSAS
Location:	API #: 15-003-25445-00-00 660' FSL & 1320' FWL S/2 SW SEC 22 TWP 20S RGE 20E
Other Services	
Elevation	K.B. D.F. G.L. 957'EST.
Permanent Datum	GL Elevation 957'EST.
Log Measured From	GL
Drilling Measured From	GL

Company TAILWATER, INC.
Well WHITESIDE #7-IW
Field GARNETT SHOESTRING
County ANDERSON
State KANSAS

Date	2-5-13		
Run Number	1 NW		
Depth Driller	826'		
Depth Logger	808.7'		
Top Log Interval	0		
Bottom Logged Interval	808.7'		
Fluid Level	FULL		
Type Fluid	WATER		
Production Casing	2 7/8" @ TD	@	@
Max. Recorded Temp.			
Estimated Cement Top			
Calculated Cement Top			
Amount & Type Cement			
Amount & Type Admix			
Drilling Contractor			
Equipment Number	103		
Location			
Recorded By	SOLOMON, B.		
Witnessed By	HUTCHINSON, D.		

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

THANK YOU

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
GR	7.59		GR-TITAN_169 (TIT169_001) Titan 1 11/16" Gamma Ray	4.75	1.69	20.00
CCL	5.05		CCL-TITAN_169 (TIT169) Titan 1 11/16" Logging CCL	1.83	1.69	7.50
NEU	0.63		NEU-TITAN (TIT801) TITAN 1 11/16" Neutron	4.33	1.69	25.00

Dataset: whiteside # 7-iw.db: field/well/run1/pass1
Total Length: 10.92 ft
Total Weight: 52.50 lb
O.D. 1.69 in

Database File: e:\whiteside # 7-iw.db
Dataset Pathname: pass1
Presentation Format: gr-n-ccl
Dataset Creation: Tue Feb 05 14:28:27 2013 by Log Std Casedhole 09061
Charted by: Depth in Feet scaled 1:240

PERFORATIONS
2" DML-RTG
11 SHOTS @ 776' - 781'
9 SHOTS @ 746' - 750'
9 SHOTS @ 716' - 720'
11 SHOTS @ 671.5' - 677.5'
2 SHOTS/FT.

CORNISH
WIRELINE
SERVICES, INC.
CHANUTE, KANSAS

Company TAILWATER, INC.
Well WHITESIDE #7-IW
Field GARNETT SHOESTRING
County ANDERSON SEC. 22 TWP. 20S RGE. 20E
State KANSAS Date 2-5-13