MIDWEST SURVEYS
LOGGING, PERFORATING, PUMPING SERVICES
P.O. Box 70, Osawatomie, KS 66064
913.755. 2578

GAMMA RAY / CEMENT BOND / CCL

API# 15-205-28,545-00-00

Pa No

Company: SEC Energy, LLC
Well: Burgher No. 4-34
Field: Buffalo - Vilas
County: Wilson
State: Kansas

Location: 34 - 27S - 15E
153'FNL & 193'FEL
NE-NE-SW-NE
Elev.: Gr. 824' Kb. 829'
Log Measured From: Ground Level
Drilling Measured From: Kb

Permanent Datum: Ground Level
Elevation: 824'
Log Measured From: Kb
Drilling Measured From: Kb

Date: 10/26/2024
Run Number: ONE
Depth Driller: 1200'
Depth Logger: 1200'
Bottom Logged Interval: 1200'
Top Logged Interval: 0'
Casing Driller: 7" @ 1200'
Casing Logger: 7" @ 1200'
Bit Size: 6 1/4"
Type Fluid: Water
Density / Viscosity: 8.4
PH / Fluid Loss: NA
Source of Sample: NA
Rm @ Meas. Temp.: NA
Rmf @ Meas. Temp.: NA
Rmc @ Meas. Temp.: NA
Source of Rmf / Rmc: NA
Rm @ BHT: NA
Time Since Circulation: NA
Max. Rec. Temp.: 70°
Equipment / Location: 1 Chanute
Recorded By: Tyler
Witnessed By: Owner

RUN 1 | BOREHOLE RECORD | CASING RECORD
Bit | From | To | Size | Wgt. | From | To
1 | 0' | 1200' | 6 1/4" | 7# | 0' | 1200'

Tool Type: Gamma Ray / Cement Bond / CCL
Tool Size / Model: 1 3/8" / CBL
Max. Recorded Temp.: 70°
Equipment / Location: 1 Chanute
Recorded By: Tyler
Witnessed By: Owner

--- Field Interpretation ---

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Drilling Contractor :
WoCo Drilling, LLC

Database File: burghart 4-34.db
Dataset Pathname: pass2
Presentation Format: telco-gr
Dataset Creation: Mon Mar 04 10:26:49 2024
Charted by: Depth in Feet scaled 1:240

0 Gamma Ray (cps) 150
150 Gamma Ray (cps) 300
AMP/SFT
(mV)
-50 10

0 Amplified Amplitude (mV) 50
0 Amplitude (mV) 100
CCL 0.0 200
1000 TT/3FT (usec) 250

Variable Density
1200

11-1-24
Perforated Interval
1020.0 - 1026.0 19 Perfs
3 3/8" DP - 21" - EHV

Amplified Amplitude
Amplitude
Gamma Ray
TT/3FT