MIDWEST SURVEYS

LOGGING - PERFORATING - CONSULTING SERVICES
P.O. Box 68, Osawatomie, KS 66064
913 / 755 - 2128

GAMMA RAY / CEMENT BOND / CCL

File No.

API# 15-059-27,411

Company	Utah Oil, LLC		
Well	Cox No. KOI-4		
Field	Paola / Rantoul		
County	Franklin	State	Kansas
Location	3325' FSL & 350' FEL SW-NE-SE-NE	Other Services	Perforate
Sec. 6	Twp. 17s	Rge. 21e	
Permanent Datum	GL	Elevation 960'	Elevation K.B. NA D.F. NA G.L. 960'
Log Measured From	GL		
Drilling Measured From	GL		

Date	03-37-2024		
Run Number	One		
Depth Driller	735.0		
Depth Logger	698.5		
Bottom Logged Interval	695.5		
Top Log Interval	15.0		
Fluid Level	Full		
Type Fluid	Water		
Density / Viscosity	NA		
Salinity - PPM Cl	NA		
Max Recorded Temp	NA		
Estimated Cement Top	0.0		
Equipment No. / Location	104 / Osawatomie		
Recorded By	Steve Windisch		
Witnessed By	Brad Leach		

BORE-HOLE RECORD				CASING RECORD			
RUN No.	BIT	FROM	TO	SIZE	WGT.	FROM	TO
One	9.00"	0.0	22.0	7.00"	15.0	0.0	22.0
Two	5.875"	22.0	735.0	2.875"	6.5	0.0	733.0
				Baffle	Set	At	703.95

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Drilling Contractor :
McGown Drilling, Inc.

Database File: cox 4 koi.db
Dataset Pathname: pass2
Presentation Format: tekco-gr
Dataset Creation: Wed Mar 27 12:39:56 2024
Charted by: Depth in Feet scaled 1:240

0	Gamma Ray (cps)	150	AMP3FT (mV)	0	Amplified Amplitude (mV)	50	Variable Density	
150	Gamma Ray (cps)	300		0	Amplitude (mV)	100		
			-50 10	-8	CCL	0.9	200	1200
				1600	TT3FT (usec)	250		

05-22-2024
Perforated Interval
665.0 - 672.0 22 Perfs
2" DML RTG 120º Phase

0	Gamma Ray (cps)	150	AMP3FT (mV)	0	Amplified Amplitude (mV)	50	Variable Density	
150	Gamma Ray (cps)	300		0	Amplitude (mV)	100		
			-50 10	-8	CCL	0.9	200	1200
				1600	TT3FT (usec)	250		